

CEER-C-036

CEER 6-36

; WATER HYACINTHS FOR THE CLARIFICATION OF
WASTEWATERS AND THE PRODUCTION OF ENERGY

?CENTER FOR ENERGY AND ENVIRONMENT RESEARCH

axp

PUERTO RICO AQUEDUCTS AND SEWERS AUTHORITY

JUNE 1979

erty,

CENTER FOR ENERGY AND ENVIRONMENT RESEARCH,

est Oney,

Cnrrssa

?PR, 00t

---Page Break---

WATER HYACINTHS FOR THE CLARIFICATION OF WASTEWATER
AND THE PRODUCTION OF ENERGY

VELLAMIL, R.G, CLEMENTS, A.MCB. BLOCK, ENG, P.

WEIL, ENG, A, GARGIA®, ENG, W. LAO*, L.T.

ROSA, F. SANTOS

CENTER FOR ENERGY AND ENVIRONMENT RESEARCH
TERRESTRIAL ECOLOGY DIVISION
CAPARRA HEIGHTS STATION

SAN JUAN, P.R. 00935

PUERTO RICO AQUEDUCTS AND SEWERS AUTHORITY
LONG TERM PLANNING DEPARTMENT
SAN JUAN, PUERTO RICO
00916

---Page Break---

TABLE OF CONTENTS

ABSTRACT

INTRODUCTION . .

METHODS ..

RESULTS

WATER CLARIFICATION PERFORMANCE...

WATER HYACINTH-BASED TREATMENT SYSTEM ..

SYSTEM ENERGY GENERATION ..

CONCLUSION ce

[REFERENCES

12

16

20

26

29

---Page Break---

WATER HYACINTHS FOR THE CLARIFICATION OF WASTEWATER AND THE PRODUCTION OF ENERGY

J. Villamil, RG, Clements, A.McB, Block , Eng. P.

Weil, Eng. A. Garcfa®, Eng. W. Lao*, L.I.

Rosa, F, Santos

Center for Energy and Environment Research

Terrestrial Ecology Division

Caparre Heights Station

San Juan, PLR, 00935

?Puerto Rico Aqueducts and Sewers Authority

LONG TERM PLANNING DEPARTMENT

San Juan, P, . 00916

ABSTRACT

Water hyacinth (*Eichhornia crassipes*) (Mart) Solms) has been proposed by several authors as a nutrient scavenger plant for the improvement of water quality in eutrophied water and wastewater. Withies high productivity, the water hyacinths if properly managed, could be used for a wastewater tertiary treatment and as a quickly renewable source of biomass for conversion to methane. This work presents the conceptual and engineering design of the total utilization of the hyacinth as bio-filter in a new prototype of tertiary treatment plant which could be energy self-sufficient.

---Page Break---

?The system has been designed for the domestic and industrial reuse of wastewater and it incorporates energy-conservative features such as the conversion of waste sludge to compost, the utilization of solar and wind power for lagoon development and some new concepts in sanitary engineering.

INTRODUCTION

Since its introduction in Puerto Rico, the water hyacinth, *Eichhornia crassipes*, has gone from a floral curiosity to a nuisance and pest in waterways. Much effort and money have been spent to eradicate this aquatic vascular plant, but because of its capacity to reproduce vegetatively, the results have not been satisfactory.

Penfound and Earle (1948) stated that several investigators were of the opinion that the hyacinth problem could be solved if a commercial use were available. However, they took the position of Bucknam (1920), that "no commercial utilization of the hyacinth on any scale was likely to be a factor in the campaign for eradication or control". Bock (1970) concluded "that until control methods are more effective than those been used today or until some economic use can be made of the plants, water hyacinths, will continue to increase its wide distribution", Thus it is not surprising that most of the literature on the water hyacinths has dealt with control measures.

Today, the role of the water hyacinth has changed from a nuisance plant into a promise for the future. Several authors have proposed the use of hyacinths for a wide variety of applications. Some have proposed the use of the hyacinth as a nutrient and contaminant scavenger for the clarification of sewage and industrial ef-

Fluents (Steward, 1970, Haller, 1970, Boyd, 1970, Calvin, 1976, Denton

---Page Break---

1970, Dinges, 1976, Dunningam, 1974 and Wlverton, 1975, 1976, 1978). Others, have proposed and tested the water hyacinth's high productivity as a source of biomass for its conversion to methane by anaerobic digestion. Hyacinths have been also proposed as cattle feed (Chatterjee, 1938 Baldwin, 1975, Combs, 1970)

?The increase of the Puerto Rican population has created many strains on services provided by the Commonwealth government. Population concentration in the cities creates an ever-increasing volume of sewage making necessary the augmentation of capacity of existing primary and secondary wastewater treatment plants and requiring the construction of new ones.

?The complex worldwide energy outlook coupled with Puerto Rico's complete dependence upon imported oil for her electrical energy generation are factors which tend to discourage planning and design of energy intensive tertiary treatment systems. An

energy conservative system capable of meeting U.S.E.P.A. effluent quality standards projected for 1985, would save operation and maintenance costs and encounter less resistance to initial investment by public agencies and municipal treatment corporations and from the industrial sector

This report presents the results of the first research phase, toward the total utilization of the water hyacinth. Cultivation is directed toward energy-conservative approaches to water treatment including wastewater clarification, production of sludge compost, methane production, and using relatively new conceptual and engineering designs. The project is presently supported by CEER's Research

Institutional Program working in close cooperation with

---Page Break---

Puerto Rico's Aqueducts and Sewers Authority Water Hyacinths Research Group, supported by PRASA Institutional Funds.

METHODS

Realistic optimal design/operation for a hyacinth treatment system cannot be established before ecological, public health

considerations, legal aspects and treatment efficiency parameters are examined. A substantial research effort was required in order to resolve these questions, The research needs quoted in Table 1 are directly from Robinson et. al, 1976. Our research effort has followed Robinson's research priorities.

?The ecological and clarification performance of the hyacinth association has been studied using a retention pools system, constructed at El Conquistador Secondary Treatment Plant located in Bo. Carrafzo, Trujillo Alto (Figure 1).

?The system consisted of fifteen plastic lined pools provided with an inflow and outflow system (Fig. 2 and 3). ?The hyacinth growth media was secondary treated effluent, pumped from the plant chlorination chamber on a 24 hrs. basis

?The objectives of the initial studies were to measure the plant growth rate, the hyacinth biomass doubling time, the plant tissue water percent composition and the relationship between effluent retention time and the plant growth rate

?Three hundred juvenile plants (100 g to 450 g) were harvested from Lake Carrefzo for use in these experiments. Five treatments with three replicas of each were applied to the plants for the growth rate study. The treatment consisted of exposure of a known number of plants to five different retention times, which were one day,

two four, eight, and sixteen days, respectively

---Page Break---

30" be suyotuo

sygoa bersesod> aonpe1 pina

rungeoe auieent 16H0) TEN wosixo paatossra ?5

---Page Break---

oor]!

pasodog ? ? ?

sunsixg

puster

---Page Break---

FIGURE

our

2 RETENTION POOLS SYSTEM LAYOUT

---Page Break---

The plants were assigned at random to their pool location, retention time, harvest schedule and grid location in the pool.

The nylon cord grid positioned over the pool provided a fixed position and the same effective surface area for growth to each of the plants (Fig. 4). Plants were physically attached to intersection lines of the grid using nylon cord.

The calculation of the daily incremental constant was

made using the following equation.

«(ee

*

in which

Le

Ws first weight

ip second weight

t = number of days between weighing

x

daily incremental constant

Kjeldahl nitrogen, total suspended solids and total phos

phorus measurements of the effluent from each pool were performed according to APHA Standard Methods 13th. edition. Effluent dissolved oxygen measurements were performed using » YSI dissolved oxygen meter. The effluent pit was measured by means of a Corning pH meter.

RESULTS

The mean incremental constant was determined to be 0.290.
Thus, on the average, the hyacinth biomass doubles every seven days.

The biomass doubling time is a very important parameter for the

---Page Break---

}-__ ? 3.394 ? __+4

® aL

+

Inflow Ourtiow

Figure 3. Retention Pool Detail

Figure 4. Grid Used Over The Retention Pools During
The Growth Rate Studies

---Page Break---

operation of a hyacinth wastewater treatment plant. To maintain a high (logarithmic type) growth rate, juvenile plants with @ corresponding high metabolic rate are preferred and a harvesting program has to take into consideration the biomass doubling time.

The plant water content was determined by drying the harvested hyacinths at 70°C for 3 days, after weighing them drip dried for five minutes. The mean dry weight percent of the plant was found to be 5.2%. A direct linear relationship was found between the wet weight and the dry weight of the hyacinths (Fig. 5).

?The regression equation of this relationship could be used for the determination of the dry weight of any particular wetweighed plant:

$$Y = 0.05129 + 0.3130 x$$

where:

Y= dry weight

X = wet weight

No significant relationship was found between the water retention time and the growth rate of the water hyacinth. Probably, the high nutrient content of the wastewater provided as the growth media was the reason for the non-observance of significant differences between the pools and the treatments

?The productivity study took place during the months of

Jan. and Feb., 1979 which are the months of low solar radiation in Puerto Rico. The mean productivity in terms of wet weight was 216.39 g/m²/day. The productivity per hectare on a wet a weight basis was determined to be 2163.9 Kg/ha/day or on dry weight 108.195 Kg/ha/day based on a 5.2% dry weight composition. The hyacinth's

---Page Break---

u

$$Y = 0.05129 + 0.3130 x$$

so]

45

40)

35

20]

25.

Ory Weight fo)

20

001

002:

008:

28 38 8 3 8

wet Weight(g)

FIGURE 6: Linear regression between wet weight and dry weight of *Eichhornia crassipes*.

Plants were dried at 70°C for three days.

---Page Break---

12

high productivity provides an exceptional amount of biomass for
use in various conversion options e.g. compost, biomass conversion

to methane, fiber and cattle feed production

WATER CLARIFICATION PERFORMANCE

The wastewater clarification performance of the hyacinth lagoon association it is not only due solely to the hyacinth metabolism. The nutrient and contaminant removal from the wastewater is affected by various processes, which are as follows

1. Hyacinth metabolism
- 2, Other aquatic vascular plant metabolism such as Lemma and Pistia.
3. Metabolism of algae and other phytoplankton in the water column.
- 4, Trophic relationships in the hyacinth Lagoon
5. Recycle of nutrients in the suspended and settled solids by bacteria and other detritovores.
6. Physical hold-up in the surface tissue of the organisms in the Lagoon.

?The biological interactions responsible for the nutrient contaminant removal are represented in Figure 6. This Figure includes the energy and nutrient flows using the standard notation of Odum (1967) for the hyacinth association; other symbols used have the following definitions

0 - Dissolved oxygen in the water

---Page Break---

© ¢

Dd Hrecinns

>> x, Lemme

> xX Algae

Figure 6: Biological Interactions in the Hyacinth lagunal Association

---Page Break---

14

Ng - Nitrogen from the influent

N = Nitrogen in the system water

Po - Phosphorus from the influent

P - Phosphorus in the system water

My - Trace metals from the influent

TH - Trace metals in the system water

D = Detritus or settled solids

ou - organic matter exported from the Lagoon system

1 - Primary consumers, insects, amphibian

larvae, protozoans, annelids, molluscs and others

2 = Secondary consumers, insects, amphibians, lizards

and others

3 - Tertiary consumers - birds, amphibians, lizards

and others

?The removal of nutrients in the hyacinth-based system is

mostly accomplished by the system primary productivity. Further removal and fixing of nutrients takes place at various other trophic levels and with their interactions with consumers from outside of the lagoon system. Photosynthesis of the algae in the water column would provide surplus dissolved oxygen, which in turn would be available for aerobic bacteria and to the lagoon zooplankton. This in turn will promote a greater removal and oxidation of the suspended and settled solids in the Lagoon.

The nutrient and contaminant removal processes in the lagunal association could be accelerated and maximized by:

1. pH, adjustment of the nutrient media (wastewater).
2. Thus, the primary productivity (hyacinths) will be higher by buffering at pH 7.0 (Chadwick and Obeid, 1966).

---Page Break---

1s

Keeping a high growth and metabolic rate by means

of @ harvesting program

4, Increasing the dissolved oxygen levels of the water.

5. Physical extraction and collection of the precipitated solids.

6. Post-lagoon chemical precipitation and collection of contaminants.

7. More contact of the wastewater with the ambient ultraviolet light and ozone, by means of water station.

8. Filtration of the final effluent.

The water clarification performance of the hyacinth association treatment is very promising. A mean 95% reduction of total N has been obtained, from a concentration of 30.4 mg/l to 0.05 mg/l. The removal of total phosphorus accomplished was 25% from 1.12 mg/L to 0.84 mg/l. Additional treatment will be needed for a maximum removal of phosphate. A 90% removal of total suspended solids was accomplished, from a concentration of 43.28 mg/l to 0.48 mg/l.

The average dissolved oxygen concentration in the effluent of the pools was 5.61 ppm, the average dissolved oxygen in the effluent of the secondary treatment plant was 3.0 ppm. On the

average, the hyacinth system increased the dissolved oxygen concentration in the wastewater by 2.61 ppm. The pH in the Lagoon system was 6.60, compared to 6.52 for the secondary treated effluent.

The BOD₅ levels in the hyacinth system proved to be within

the U.S. EPA standards. The average BODs in the hyacinth system was 4.2 mg/l. The BODs in the secondary effluent was slightly lower than those of the hyacinth lagoons. One possible reason for this

was the high algae population in the pools

---Page Break---

16

WATER HYACINTH-BASED TREATMENT SYSTEM

PRASA Research Group on Water Hyacinths has collaborated with CEER for the preliminary conceptual and engineering design of several alternatives of a water hyacinth based system. A

water recycle or reuse system for domestic applications based on water hyacinths is presented on Figure 7

Before the secondary treated water enters the hyacinth lagoon system, it will be aerated by two means, 1) wind powered aerator, and 2) cascade aerator (Figure 8 and 9). These two systems could provide a very high dissolved oxygen content to the lagoon, they will provide enough dissolved oxygen to support an extensive association of aquatic fauna which will further remove nutrients from the water. Light vents or passages through the water column will be provided at the water level using floating frames to prevent hyacinths from fully covering the water surface (Figure 8 and 9). This will permit increased algal growth and improved nutrient removal as well as a higher dissolved oxygen content, product of algal photosynthesis. The expected high dissolved oxygen content will provide a less suitable environment for mosquito larvae development than currently employed facultative Lagoons.

Two hyacinth lagoons connected in series and with water recirculation from the second lagoon to the first are also proposed. This configuration will provide a dilution factor for a decreased nutrient load and contaminants (Figure 7). After the water has passed the lagoon system it will be flocculated with lime. The lime flocculation serves as an additional treatment for phosphorus and for an anticipated 99% removal of virus and bacteria. (Grabow, 1978). After

---Page Break---

4 aunois

sysujo04H 1810M wo pasog wassks a/2h204 1940M

---Page Break---

18

Jo1wei2y pesemog pUIM

miwpuim 04 Burtdno:

8 aunols

NOOOV7 HLNIDVAH G3SOdOUd ?NOILITS YOIWFLNY ?MZIA FOIS

---Page Break---

a

voy129g

19

(U0I122S PIN) MIA sv01d

v

vores

6 aunots

MBIA dOL NOO9Y7 HLINIDVAH

---Page Break---

20

flocculation the supernatant will pass through a sand filter and

then to a chlorination chamber (Fig. 10)

SYSTEM ENERGY GENERATION

le is proposed that hyacinths from the lagoon be harvested

every seven days by means of a harvester machine (Figure 11) located

at the end of each hyacinth lagoon. The harvested plants may be used in two ways: for sludge compost as enrichment and bulking agent and for biomass conversion to methane after combining with sludge

Previous investigation into the production of methane from the bioconversion of the water hyacinth have been conducted by Wolverton, 1975 and Lecuyer, 1976. Wolverton, 1975, conducted hyacinth fermentation studies using 3 liter Erlenmeyer flasks at temperatures ranging

from 25° ranging from 25°C \pm 5°C to 36°C using both chopped hyacinths, There were no significant differences between the methane yields of chopped and blended hyacinths. The chopped water hyacinths produced 11.0 and 6.4 ml. methane per gram wet weight as compared with production of 7.9 ml. methane per wet gram weight of the blended hyacinths, All fermentation units were seeded with already decomposed hyacinth plants

Temperature played an important role in the rate of biogas and methane production. The time lag between the production of biogas and the production of methane gas was reduced from an average of eight days for those maintained at 25°C \pm 5°C to approxi-

mately one day for those incubated at 36°C. The methane content

of the total bio-gas produced in the experiment at 36°C was 69.2%,

This percent methane was higher than the average methane content

of 59.9% for the experiments conducted at room temperature.

---Page Break---

2

wassks juawsoas, 4840M jours

0: aunois

?:

Site mmr 7 sn } ~ _

souriiirane oo

q exerueds

Ly owe

---Page Break---

eae ee

o

cL >

NOODV7 HLNIDVAH G3SOdOYd ?NOILIZS YOIWTLSoD ?MZIA FAIS

---Page Break---

Lecuyer, 1976, working on a commercial basis reported a bio-gas production rate of 6 ft³./1b of dry hyacinth based upon a productivity of 373.2 Kg dry/Ha/day. The 600 Bru/Scf bio-g:

containing 60% CH₄ and 40% CO₂ was upgraded by the Benfield scrubbing Process to PQG (1,000 Btu/Sef) by removing the CO). The total production of the plant was set at 392 million Scf/day of bio-gas.

No details were given on temperature, seeding or retention time of the fermentation process

Based upon Lecuyer?

(1976) methane production rates of

6 Scf/tb dry hyacinths, the estimated Sef production on the proposed system will be 4,868.78 Scf per day assuming a dry weight productivity of 2,365.64 lbs/acre/day. Two lagoons of 1.5 acre

each, are proposed to be used to process 1.0 GD, the total productivity for this area will be 7,096.92 lbs/3 acres/day. The energetic content of one methane Sef is 1,000 BTU according to Lecuyer, 1976, Thus, the estimated energetic value of the methane expected to be produced from hyacinths will be an average of 4,868,775 BTU/day, in terms of Kw hr/year the production will be 155,887.85 Kw hr/year. A typical 1.0 MoD trickling filter treatment plant consumes 426,960 Kw hr/year, an activated sludge plant uses 505,270 kw hr/year for its operation. If hyacinths solely anaerobically digested could provide 30.9% of the energetic needs of a trickling filter plant and 36.5% of the needs of an activated sludge plant.

In the proposed wastewater treatment plant the sludge and hyacinths will be digested together. A domestic 1.0 MGD wastewater treatment plant, according to EPA, produces 2,096 lbs/day of dry solids from which 723 lbs/day are volatile solids which in turn

could be converted into methane. The expected methane yield from

---Page Break---

2%

the sludge produced from the treatment process will be 10,845.00

Se this in turn will provide 6.5 million BTU/day. The methane expected to be produced from the sludge will provide 208,115.7 Kw hr/year. Thus, the methane expected to be produced from hyacinths and sludge combined will provide the proposed plant with 364,000.25 Kw hr/year. The combined mixture of hyacinth and sludge batches could provide 85.25% of the total energetic needs of a typical 1 NGD trickling filter plant and 72% of the needs of an activated sludge plant. The combined batch could make the proposed treatment plant almost energy self sufficient.

In the proposed system, the digester is heated by solar radiation, the proposed digestion tanks are expected to be constructed utilizing the most cost effective material. The mixture to be digested will be periodically mixed by bubbling compressed air, along a pipe on the bottom of the tank. The heating and mixing of the digester batch should allow a methane production in even higher yields than those observed by Wolverton (1975) and Lecuyer (1976)

Two biogas scrubbing systems have been studied for use at

the proposed plant. Methane purity and cost of the system will be the two criteria for the implementation of either of the proposed scrubbing systems. The Benfield process is illustrated in Figure 12. This scrubbing process yields CH₄ of high purity, but the operation and maintenance of the plant are costly due to the relatively expensive regeneration of Benfield reagent. The steam necessary for the reagent regeneration could be provided by a solar steam generator which is presently under development at CEER. A

considerably simpler biogas scrubbing process is illustrated in

---Page Break---

DIGESTOR

COMPRESSED
CH₄ for MIXTURE

MIXING
Kp 603

FIGURE 12 S

Methane Production Process

| sesuana

KgC05t 60g + 420

---Page Break---

26

Figure 13. This system will be provided with cartridges of iron filings to scrub the hydrogen sulfide (ii,5) and aerosols. The product is expected to be a mix of 60% CH₄ and 30-40% CO, (600

BIU/SCF, Lecuyer, 1976) which still could be used in motors with

Some carburation adjustments. The iron filings cartridges will be regenerated by roasting them using solar radiation (u.v.).

Figure 14 represents the system energy generation diagram.

The wind mill aerator could be provided with a 2 kw generator to Provide electrical power for some of the equipment. The methane Produced from the digestion of hyacinths and sludge will be useful

for electrical power generation in the proposed system.

cCONCLUSIO:

(2) While this system is totally viable in tropical or sub-tropical climates only, it is hoped that innovations with respect

to wind and solar utilization will help stimulate applications of

aerobic and facultative lagooning world-wide.

(2) Most of the existing wastewater treatment plants in P. R. could be upgraded, polishing their effluents with water hyacinth lagoons to comply with EPA and EQS regulations with regard to TSS, BOD, Total N and Total P.

---Page Break---

Me, Coz

oc} SF

| Mes, send

|

||

||

! i

Digestor

Po

FIGURE 13.

IRON

Ges

Compressor

coz pretest

tron

Fuungs

Seruber

H+ C0, Recircuterion tor

Wining

FILINGS SCRUBBER

27

?chia

co;

---Page Break---

woibolg

uojj019ua5 Absaug wWasshks

vi aunois

po

?30am

nooor7

7) sung

Joreseue9 1021212213 pu so10942¥ pum

---Page Break---

29

REFERENCES

Bock, J... 1970. An Ecological Study of *Eichhornia crassipes* with Spectal taphasts on its Reproductive Biology. PRD
Dissertation Univeresity of California, Berkeley?

Boyd, C.E., 1970. Vascular Plants for Mineral Nutrients Removal
from Polluted Waters, *Economic Botany* 24: 95-103

and R. D. Blackburn, 1970. Seasonal Changes in
ERE ?Approximate Composition of Some Common Aquatic Weeds.
Hyacinth Control Jour. 8: 42

Buckman, & Company, Engineers, 1920. A report on an investigation of Water Hyacinths. City Commission of Jacksonville, FL

Chadwick, M.H. and Obeid, M., 1966. *Eichhornia crassipes* and *Pistia stratiotes*. The Journal of Ecology 54: 547-553

Chatterjee, I. and Hye, M.A., 1938. Can Water Hyacinths be used as a cattle feed? Agr. and Live-stock in India 8: 547-553

Denton, J. S., 1970. Certain Relationships between the Chemical Composition of Aquatic Plants and Water Quality. Proc 20th. Weed Conf., pp, 354-362.

Dinges, R., 1976. Water Hyacinth Culture for Wastewater Treatment, Texas Department of Health Resources.

Dunigan, E. P., Shamsuddin, Z. H. and Phelan, R. A., 1974. Water Hyacinth Tested for Cleaning Polluted Water: Louisiana Agriculture 18: 12-13

Haller, W. J., Snipling, E. S. and Wost, S., 1970. Phosphorus Absorption by and Distribution in Water Hyacinth. Soil and Crop Society of Florida 30: 64-68

Odum, 1967, Energetics of world food production, En: The World Food Problem, A report of the President's Science Advisory Committee. Panel on World Food Supply (I. L. Bennett,

?The White House, Washington, D. C. Vol. 3,

Steward, K.K., 1970. Nutrient Removal Potentials of Various Aquatic Plants. Hyacinth Control 8: 34-35.

Wolverton

B. C., 1975. Water Hyacinths for Removal of Cadmium and Nickel from Polluted Waters. NASA Technical Memorandum TM-X-72721.

1975. Water Hyacinths for Removal of Phenols

?From FoITuted Waters.? NASA Technical Memorandum TM-X-72722,

---Page Break---

30

"yang B,C McDonald, 1975. Water Hyacinths

© SRUTATITpatOr ?Weeds for ?Reaooet ce 2275 and Mercury from
Polluted Waters. NASA Technical Menorandes Tareey 723,
and R.C. McDonald, 1975. Water Hyacinth
?FOE UEFaEING? sewage Lagoons ra tkeer Advanced Wastewater
Tree pengoStaneares, Pare 1. ?NASA Technical ?Messe eeae
TM-X-72730

"gang R.C. McDonald, 1976. Water Hyacinths

"FOE Upgrading? sewage Lazoose raiser Advanced Wastewater

TTT ameaEas. Pare IT.? NASA Technics] Hoses sam
TM-X-72730

bedtd RC: McDonald, 1976. Water Hyacinthe
Cursed Tora tentry Nay Redon tegere 6 Submitted for
Publication in New Scientist.

yand 8. C. McDonald, 1978. Water Hyacinth |
© (EESRROENTA Gtassipes). Proaucrsvity sng Harvesting Studies,
fart 3. Mask Earth te at

Part 3. Nasi Sources Laboratory Report Now?.

sping R: ,o- McDonald, 1978. Upgrading Faculta-
© ERREWESEE Stabilization Ponde with Weccuree ?Aquatic Plants

---Page Break---

---Page Break---