

"Solar Ponds: Research, Applications and Development" by Gy Ts Pytlinski
Center for Energy and Environment Research (CEER-S-15)

CEER-S-151 "Solar Ponds: Research, Applications and Development" by Gy Ts Pytlinski,
December 1982.

Center for Energy and Environment Research

Proceedings of the Condensed Papers of the 5th International Conference on Alternative Energy
Sources, 13-15 December 1982, Miami, Florida, U.S.A.

"Solar Ponds: Research, Applications and Development" by G. T. Pytlinski, Center for Energy and
Environment Research, University of Puerto Rico, Mayaguez, Puerto Rico 00708.

Extended Abstract:

Introduction: Fossil fuels are not readily available in many countries, forcing them to rely on imported oil, coal, or nuclear technology. This often exacerbates their existing balance of payment issues. Over the past few years, solar ponds have gained attention as a viable solar technology with the potential to compete economically and technically with fossil fuel-based energy conversion technologies (see Fig. 1).

In addition to their low cost, solar ponds offer built-in storage, making them independent of intermittent solar radiation. Shallow solar ponds appear to be the most developed and market-ready technology.

The concept of collecting and storing solar energy with salt-gradient ponds comes from research on natural salt lakes. In recent years, salt-gradient solar ponds have reached the application level, though some aspects of their construction, operation, and maintenance are still in the research and development stage.

Some of the most significant work in this area is described by Tabor, who discusses the current technology status and the physical and thermal phenomena that occur in the salt-gradient solar ponds, and by Nielsen, who focuses on research results related to the physics of ponds. Other areas of...

Pond studies are addressed by Fynn [12] and Zagrande [13], who detail various aspects of salt-gradient pond operation and the maintenance of salt inventory during heat extraction. Cha et al. [14] and Coates et al. [15] focus on pond construction methodology and cost. Laboratory investigations have also been conducted on saturated salt ponds [16, 17, 18] and gel ponds [19,20]. Both of these solar heat collection and storage techniques are still in the research stage. They currently lack the interest and financial support that shallow solar ponds and salt-gradient solar ponds receive. Shallow solar pond technology and salt-gradient pond technology are suitable for on-site pond construction, using well-known techniques and readily available components. Proposed and studied solar pond applications include commercial and residential space and water heating, low-temperature (between 50°C and 70°C) industrial and agricultural process heat

production, electric power generation, irrigation water pumping, and absorption and dehumidification cooling.

Development work on solar ponds primarily focuses on large scale (up to 50 Mi) modular salt-gradient ponds for electricity generation [21-24]. The economies of scale, simplicity of construction and technological readiness make such stand-alone plants especially attractive in areas where natural salt lakes already exist and can be converted into production ponds with minimal technical effort and financial support. Selected research, application and development efforts in the field of solar ponds are described below.

RESEARCH PONDS

Currently, research activities on shallow solar ponds, gradient ponds, salt-saturated solar ponds, and gel ponds are being conducted at several locations. Figure 2 shows a cross-sectional view of a laboratory-sized research pond at the Brace Research Institute at McGill University [25]. The first shallow solar pond system...

The design and operation of a system was conducted by the Lawrence Livermore Laboratory of California. It was built in 1975 in New Mexico. There were three prototype ponds, each measuring 210 square meters (2260 square feet), which provided heat for the Sohie Company's uranium processing mill during several months of successful operation. A cross-sectional view of a typical shallow pond is shown in Figure 3.

Currently, a shallow solar pond of 22 square meters (240 square feet) and 2.54 cm (1 inch) in depth is being installed on the roof of a high school in Mayaguez, Puerto Rico. It is intended to deliver hot water at 57°C (135°F) to the school cafeteria.

A salt-gradient solar pond of 200 square meters (2152 square feet), with a depth of 2.5 meters (8.2 feet) and 45° tapered walls, has been operating since 1975 at Ohio State University in Columbus, Ohio. In 1976, this pond reached a maximum temperature of 62°C (144°F). Experimental and theoretical research has been conducted on the physics of this salt-gradient pond and its operation and maintenance.

A second salt-gradient solar pond, measuring 408 square meters (4390 square feet), was installed at Ohio State University in 1979. This pond is 4.5 meters (14.8 feet) deep at the center and 1.5 meters (4.9 feet) deep near the walls. The walls of the pond are vertical and are made out of wood planks, thermally insulated by styrofoam and urethane. The pond is extensively instrumented to provide data on solar input, heat gain by the pond, heat loss to the ground, and heat conducted upward through the gradient layer. A cross-sectional view of a salt-gradient solar pond is shown in Figure 4.

Another pond of this type, measuring 156 square meters (1678 square feet) with a depth of 3.6 meters (11.8 feet) and vertical wooden walls, has been operating successfully on an experimental basis since 1877. It provides heat for a greenhouse at the Ohio Agricultural Research and Development Center in Wooster, Ohio. Although this pond provides heat for a greenhouse, its main purpose is to serve as a research base where various aspects of the pond operation and heat extraction are studied.

A research salt-gradient solar pond, measuring 177 sq. m. (1901 sq. ft.) with a depth of 2.5 meters and walls tapered at 34°, was installed at the University of New Mexico in Albuquerque, New Mexico, in 1975 [13]. In the pond's second year of operation, the storage layer reached a temperature of 93°C (199°F). Studies are being conducted on the operational parameters, the criteria for the materials to be used, cost and performance data, and the physical behavior of the pond when exposed to the environment. Proof of the technical feasibility of heat extraction was obtained through the pond's successful operation year-round and by extracting an amount of heat adequate for heating a 185 sq. m. (1990 sq. ft.) house located in the region. The same pond reached a boiling temperature of 108°C (226°F) during the summer of 1980.

Research on gel ponds has also been conducted at the University of New Mexico since 1981 using an experimental pond of 18.7 sq. m. (201 sq. ft.) [19,20]. The effect of the polymer gel thickness on the performance of the gel pond is being studied. It was found that the surface heat losses from the pond containing a 0.25 m. (0.82 ft.) layer of gel over about 1.22 m. (4 ft.) of low salinity water were approximately half those from a salt-gradient pond with a 1m. (3.28 ft.) stratified salt zone under the same conditions. For optimal operation of a gel pond, the research indicates that a 0.15 m. (0.49 ft.) gel thickness is adequate. The chemical formula for the gel, which is the subject of a patent, is not available. The current estimate is that the polymer gel will last three years in a pond under natural solar exposure. Heat is extracted from a gel pond in the same way as from salt-gradient and salt-saturated ponds; that is, by using in-pond or out-pond heat exchangers.

Laboratory work on salt-saturated ponds has been done by the Desert Research Institute in Nevada using borax as the salt [16,17], and by Inter Technology Company in Virginia using disodium phosphate as the salt [18]. In the

In the former case, the size of the pond, built in 1979, was 10 sq. m. (108 sq. ft.) and 1m. (3.28 ft.) deep. In the latter case, the pond size was 0.37 sq. m. (3.7 sq. ft.) and 0.91 m. (3.0 ft.) deep. The maximum temperature reached by the Desert Research Institute pond was 47°C (117°F).

Reduced maintenance and lower fresh water usage are some of the advantages of using saturated ponds. The saturated pond also has the property of a self-established and maintained stable density profile during the heat injection and/or extraction process. A saturated pond may, however, require much more salt than an unsaturated pond, which may be a financial disadvantage. Some studies were done on the chemical and biological contamination of saturated ponds, thermal behavior, and operation and maintenance problems. The research performed so far, however, has been restricted to laboratory-sized ponds and the available data does not cover operating conditions of large size production ponds.

Work on the construction of a salt-gradient solar pond was also initiated in 1971 by the University of Utah, in Utah. The research pond of 850 sq.m. (9146 sq. ft.) and a depth of 1.1m. (3.6 ft.) was built during 1979 on the southwest side of the Great Salt Lake. The maximum temperature reached by the pond was 55°C (131°F), which was reached after about six weeks of pond operation.

At the beginning of 1960, however, a very strong wind of approximately 35.8 m/s (80 m.p.h.) destroyed the salt gradient and emptied almost one-fourth of the pond into the dike surrounding it. The pond was built to investigate the physical processes that occur in a salt-gradient pond and to

develop an experimental base for computer modeling of various design schemes for electrical power generation using large size production ponds.

A salt-gradient pond has been operating at the Argonne National Laboratory in Illinois since 1980. The pond has 1075 sq. m. (11567 sq. ft.) and its sides are tapered at an angle of 45° to a depth of 4.27 m. (14 ft.).

At the end of 1981, the pond reached a temperature of 63°C (145°F). The major objective of building this pond was to have a research tool to assess the salt-gradient pond as a heat collection and storage system for various types of applications, and to set up an operations base for a future U.S. solar ponds program. This pond is very well instrumented and has already provided data that can be used initially to guide future builders of salt-gradient solar pond systems.

The Tennessee Valley Authority (TVA) installed a 4047 sq.m. (43543 sq. ft.) pond in Tennessee in 1981 [34,35,36]. This pond will work in conjunction with a 2484 sq. m. (26724 sq. ft.) evaporation pond which is 1.2 sq. m. (4 ft.) deep and has walls tapered at 34°. The TVA pond is extensively instrumented, and it will provide important information on pond reliability, operating costs, and energy collection efficiency, thus making a significant contribution toward the commercialization of pond technology. This pond is available to outside users as a testing site.

The Center for Energy and Environment Research (CEER) of the University of Puerto Rico in Mayaguez is currently installing a research pond of 39 sq. m. (415 sq. ft.) with a depth of 0.9-1.5 m. (3-5 ft.), and vertical walls [27]. This pond will work in conjunction with an evaporation pond of a similar area. The research pond will be well instrumented to study the physics and engineering aspects of pond operation, maintenance, and control. Some computer simulation work will also be performed. This research pond will be a pilot system for a one-half acre production pond to be used to generate process heat for a food processing company in Puerto Rico.

In Israel, research on salt-gradient solar ponds has been underway since 1954, the year the concept was conceived there (9). After a nine-year pause, work in this area was revived again in 1975. Because of Israel's almost total reliance on imported fossil fuels, salt-gradient solar pond research is oriented.

Primarily, the focus is on electricity generation. In 1977, a 1500 sq. m. (16140 sq. ft.) pond was made operational at Yavne Turbine Ltd. The pond reached a temperature of 90°C (194°F) the same year. The pond generated electric power output in the range of 6 kWe, using an organic cycle system equipped with a turbine as the primary mover. This closed-loop, self-contained system used chlorobenzene as the working fluid. Water of 29°C (84°F) from the surface of the pond was used to cool the condenser. A larger pond of 7500 sq. m. (80700 sq. ft.) and 2.5 m. (8 ft.) deep was installed at Ein Bokek by the Dead Sea in 1978. When the temperature of the storage layer reached 80°C (176°F), the pond began to produce electricity using a 6 kWe capacity Ormat system. A larger Ormat system of 300 kWe capacity was installed in 1979, and the pond delivered 145 kWe of electricity the same year, operating at 93°-100°C (199-212°F) evaporator temperature and at about 30°C (86°F) condenser temperature. Desalination activities are also planned here as secondary research efforts. The main thrust of the Israeli research effort is toward obtaining a complete understanding of salt-gradient pond technology for electric power production in order to commercialize such systems for domestic and export markets as "turnkey" plants. In Canada, the first research salt-gradient solar pond was installed in 1980. The pond area is 17 sq.m. (183 sq. ft.)

and the depth is 0.86 m. (2.82 ft.). The walls of the pond are vertical. An external, brine-to-air heat exchanger made out of copper tubing is being used. The maximum temperature reached by the storage layer in 1981 was about 50°C (122°F). J.T.P.

The general objectives of installing this research pond were to obtain firsthand practical knowledge of methods and problems associated with construction, operation, and maintenance of solar ponds in preparation for the design and operation of larger ponds. Research is being financed by the National Research Council of Canada to

Develop equipment and procedures for automating the maintenance of salt-gradient ponds. In Australia, the first salt-gradient pond was built in AsponcaTe in 1964. This pond had an area of 106 sq. m. (1140 sq. ft.) and a depth of 0.86 m (2.82 ft.). Locally available clay soil was used to seal the bottom and the walls of the pond; no liner was used. The storage layer reached a maximum temperature of 63°C (145°F) in the summer of the second year of operation. The same year, the pond developed a leak which contributed to the discontinuation of the project. The results of this research, which was oriented towards the study of the pond's thermal efficiency, the sealing techniques, and the control of the salinity gradient, were published in the form of a report (38). The second salt-gradient solar pond was built by the University of Melbourne in 1981 for research purposes (39). The pond area is 240 sq. m. (2582 sq. ft.). The research is focused on the stability of the salt gradient, methodology of pond filling, and computer simulation of thermal phenomena. In Saudi Arabia, a research pond of 4 sq. m. (45 sq. ft.) with a depth of 2.3m. (7.5 ft.) was built in 1901 by the Research Institute of the University of Petroleum and Minerals in Dhahran (40). This research pond is being used to gain operating experience and to design proper instrumentation for a future large production pond. The activities are focused on computer simulation of pond behavior and on gaining experience in designing and building salt-gradient solar ponds by employing indigenous labor and techniques. In India, a salt-gradient solar pond of 100 sq.m (1075 sq. ft.) with a depth of 2.25 m. (7.4 ft.) was built in 1980 by Tata Energy Research Institute in Pondicherry (41). The pond has vertical walls and works in conjunction with an evaporation pond of 50 sq. m. (538 sq. ft.) area and 0.3m. (1 ft.) depth. The maximum temperature reached by the pond the same year was 70°C (158°F). The pond is instrumented to provide research results on thermal performance and on the

Behavior of the stratification layer. Experience was gained about which locally available materials can be used to build a pond and about construction and operation costs in India's rural environment.

APPLICATION ACTIVITIES

The most immediate applications of solar ponds seem to be for space heating and for water heating/preheating for residential, commercial, industrial, and agricultural uses where the temperature requirement is in the region of 49°C to 66°C (120°F to 151°F). In tropical climates such as, for example, the Caribbean, salt-gradient ponds may be used in the future for dehumidification cooling as proposed by Bonnet et al. [42].

In the United States, a production salt-gradient solar pond of 2044 sq. m. (21993 sq. ft.) was built in 1978 by the city of Miamisburg, Ohio, to supply heat to an outdoor swimming pool in the summer

and to a recreational building in the winter [43-46]. The pond depth is 3.0 m. (10 ft.) and the walls are tapered at an angle of 45°. The maximum temperature reached by the storage layer of the pond was 65°C (149°F) during the summer of 1979. The temperature required at the end use is 25°C (77°F). The pond was equipped with a heat exchanger made out of copper tubing of 2.54 cm. (1 in.) diameter which was placed in the pond. The effective surface area of the heat exchanger was 180 sq. m. (1937 sq. ft.). The cost of the pond construction was \$35/sq. m. (\$3.26/sq. ft.), excluding the land cost. After a successful initial operation of two years, this pond developed a leak in the liner in 1980 and had to be rebuilt.

In 1979, a shallow solar pond system was designed to supply 2000000 liters (528401 gal.) of hot water per day to two army barracks and the laundry at Fort Benning in Georgia [37]. Some 80 shallow pond modules with a total area of 25000 sq. m. (269000 sq. ft.) are being built. The system will be fully operational in 1983. Because of the large size of the installation, the fixed cost of the project will be relatively low. In addition to

Despite its size, the project attracted some attention due to certain system requirements. For instance, the distance between the ponds and the barracks is 2 miles and very high morning and evening hour peak flows of water had to be accommodated. In Canada, a production salt-gradient solar pond of 700 sq. m. (7532 sq. ft.) was constructed in 1981 in Quebec by the Contract Research Company [47]. The pond is 3m (10 ft.) deep and has walls tapered at an angle of 45°. During 1981, the pond reached a maximum temperature of approximately 53°C (127°F). The pond is used to generate heat for a commercial size grain dryer. A brine-to-air heat exchanger made out of copper tubing with aluminum fins is situated outside the pond. The frontal area of the heat exchanger is 2.3 sq. m. (25 sq. ft.) The heat extraction rate exceeded 100 kilowatts in the fall of 1981. The construction cost of this pond was less than \$50/sq. m. (\$5/sq. ft.), not including the land cost.

DEVELOPMENT WORK

Currently, development work is primarily taking place in countries where research and application activities have gained momentum. As a natural extension of these activities, the development work is centered on stand-alone plants to produce hot water, heat, and/or electricity, the selection of materials and components to ensure durability and reliability, and the automation of operation and maintenance. Two typical development projects, one in the United States and one in Israel, can serve as examples. In the United States, the Salton Sea Pond Project in Southern California, sponsored by Southern California Edison and the State of California, has received significant publicity [48]. The project consists of three phases. Phase 1, the concept and feasibility study, was completed in 1981. Phase 2 involves designing, constructing, and testing a 5 MW prototype power plant by 1988. Satisfactory results will lead to the construction of a 600 MW plant comprising 20 to 50 MW commercial modules.

The area to be covered is 1 square kilometer (0.4 sq. mi.) and it will cost \$4,000/km. The 600 MW commercial plant will cover 120 sq. km. (46 sq. mi) and will cost \$2,000/km when installed. Based on 30 years of operation time, the cost of electricity is projected to be between \$0.05 and \$0.08/kWh (1980 dollars). The concept of this project is presented in Figure 5.

The electric power generation from the low-temperature heat provided by a salt-gradient pond can

be accomplished by using an organic fluid turbogenerator as shown in Figure 6 for the proposed Salton Sea plant. In Level 1, the development plan of salt-gradient ponds technology calls for, in the first stages, the use of solar pond power plants interconnected to the power grid as peaking plants, operating between 750 and 1250 hours per year.

It is expected that by 1990, solar pond power plants can be economically used to supply intermediate loads for power grids. It is assumed that by 1995, large scale pond plates can be built to supply the base load. By following this development plan, Israel will be ready by the end of this century to operate a Dead Sea pond of about 500 sq. km. (190 sq. mi) which can supply up to 2000 MW of electric power by using satellite technologies and modular units of 50 MW each.

Conclusions: Solar ponds are technically feasible and can be economically competitive, as proven by some users. It is important to get direct experience by operating a research pond. More production ponds should be built to gain market acceptability through the reliable and economical operation of large size ponds integrated into an industrial, commercial or agricultural process.

The text has been studied for possible salts for saturated ponds. Due to the scarcity of information about metal corrosion in solutions with high salt concentration, an external heat exchanger may be more suitable for the heat extraction system. Copper and brass piping are commonly used as heat exchanger elements. PVC piping is typically employed to transport the brine to the heat exchangers. A heavy-duty plastic liner made of a chemically resistant polymer-coated polyester fabric, a vinyl liner, EPDM liner, or XR-5 liner seems to work satisfactorily. Leak detection is one of the most difficult problems in a salt-gradient solar pond. Leaks most often occur in the seams of the liner. Copper-constantan thermocouples in stainless steel jackets are normally used for pond temperature measurements.

Generally, the present cost of man-made salt-gradient ponds is in the range of \$50 to \$100 per square meter (\$4.60 to \$9.30 per sq. ft.). Naturally occurring salt lakes can be converted into ponds at a cost significantly below \$50 per square meter (\$4.60 per sq. ft.). The major capital costs are for salt, excavation, the liner, and the heat extraction equipment. The cost of salt can be up to half of the total cost. In the case of a salt lake and the construction of an electric power plant, the total cost can be divided equally between the pond construction cost and the cost of the power equipment. In some locations, for example, the Middle East countries, the cost of water may not be negligible, and in others, such as the Caribbean islands, the cost of land is an important factor. Depths of ponds range between 0.9 m and 4.5 m (3 ft and 14 ft) with deeper ponds used in areas where seasonal heating is required. Energy costs between \$6.60 and \$9.50 per GJ (\$7 to \$10 per million BTUs) are projected in the case of large-sized production ponds of over 40,000 sq. m (430,400 sq. ft.) The construction cost of shallow solar ponds is higher and can be estimated to be in the range of \$150 and \$200 per sq. m. (\$14 and \$18.5 per sq. ft.). ---Page

Break - Although only a few production ponds have been built and operated, the technical simplicity and the research results obtained indicate that the shallow solar ponds technology is market-ready, while the salt-gradient solar ponds may be on the fringe of market readiness. Whereas the technical and engineering problems related to the pond applications are being addressed by current research and development activities, the environmental, institutional, and political issues lag behind and could act as obstacles to the large-scale use of solar ponds in the future.

REFERENCES

1. A.B. Casamajor and R.E. Parsons, "Design Guide for Shallow Solar Ponds," UCRL-52365, January 8, 1979, Lawrence Livermore Laboratory, University of California, Livermore, California, 94550, U.S.A.
2. A.P. Clark and W.C. Dickinson, "Shallow Solar Ponds," Chapter 12, pp. 377-402, Solar Energy Technology Handbook, Marcel Dekker, Inc., New York, 1980.
3. A. Kalecsinsky, "Ungarische Warme und Heisse Kochsalzeen als Natuerliche Waérmeaccumulatoren," Annales der Physik, Vol.7, No. 4, pp. 408-416, 1902.
4. J.H. Short, P.C. Badger and W.L. Roller, "The Development and Demonstration of a Solar Pond for Heating Greenhouses," Proceedings of the Silver Jubilee Congress of the International Solar Energy Society, pp. 1021-1026, Vol. 2, Atlanta, Georgia, May 1979.
5. M.J. Harris, D.E. Etter and L.J. Wittenberg, "Observations Regarding Materials and Site Preparation for Salt-Gradient Solar Ponds," Proceedings of the Annual Meeting of the American Section of the International Solar Energy Society, Vol. 4.1, pp. 787-790, May 1961, Philadelphia, Pennsylvania, U.S.A.
6. J.R. Mull, Y.S. Cha, and W.S. Sha, "Major Design, Construction, and Operational Considerations of Salt-Gradient Ponds," XVII Convencion de Union Panamericana de Asociaciones de Ingenieros (UPADI-82), August 1982, San Juan, Puerto Rico.
7. H. Tabor, "Large Area Solar Collectors for Power Production," Solar Energy, Vol. 7, No. 4, pp. 189-194, 1963.
8. H. Tabor and R. Matz, "Solar
"Pond Project," Solar Energy, Vol. 9, No. 4, pp. 177-182, 1965.
10. N. A. 13. L. A. 16. V. W. 1. S. H. Tabor, "Solar Ponds," Solar Energy, Vol. 27, No. 3, pp. 181-194, 1981. H. Tabor and Z. Weinberger, "Nonconvecting Solar Ponds," Solar Energy Handbook, Chapter 10, pp. 1-29, McGraw Hill, New York, 1981. C. E. Nielsen, "Nonconvective Salt-Gradient Solar Ponds," Chapter 11, pp. 345-376, Solar Energy Technology Handbook, Marcel Dekker, Inc., New York, 1980. R. P. Fynn, J. H. Short and S. A. Shah, "The Practical Operation and Maintenance of a Solar Pond for Greenhouse Heating," Proceedings of the Annual Meeting of the ASME, October 1980, Kansas City, Missouri, U.S.A. F. Gangrando and H. C. Bryant, "A Salt-Gradient Solar Pond," Solar Age, pp. 21-35, April 1978. Y. B. Cha, W. T. Sha and J. R. Hull, "Design, Construction, and Initial Operation of the AML Research Salt-Gradient Solar Pond," ANL-81-85, August 1981, Argonne National Laboratory, Argonne, Illinois 60439, U.S.A. R. Coates, R. Fench and S. Schweitzer, "Solar Pond Construction and Cost Performance Analysis," XVII Convention de Unión Panamericana de Asociaciones de Ingenieros (UPAPI-82), August 1962, San Juan, Puerto Rico. T. J. Ochs and J. O. Bradley, "The Physics of a Saturated $\text{Na}_2\text{O}+2\text{P}_2\text{O}_5+10\text{H}_2\text{O}$ Non-Convecting Solar Pond," Proceedings of the Silver Jubilee Congress of the International Solar Energy Society, Vol. 2, pp. 1026-1028, May 1979, Atlanta, Georgia, U.S.A.

T. Ochs, "Operational Experience with a Saturated Borax Solar Pond," Proceedings of the 15th Intersociety Energy Conversion Engineering Conference, Vol. 2, pp. 1444-1447, August 1980, Seattle, Washington, U.S.A. S.C. Jain and G. D. Mehta, "Laboratory Demonstration of Self-creation, Self-maintenance and Self-Correction of Saturated Solar Ponds," Proceedings of the 15th Intersociety Energy Conversion Engineering Conference, Vol. 2, pp. 1448-1452, August 1980, Seattle, Washington, U.S.A. E. S. Wilkins, E. Yang and C. Kim, "The Gel Pond," Proceedings of the 16th Intersociety

Energy Conversion Engineering Conference, Vol. 2, pp. 1726-1731, 1981.

20. Wilkins, M. El-Genk, K. Al-Husseini and D. Thakur, "An Evaluation of the Gel Pond Performances," Proceedings of the Winter Annual Meeting of ASME, November 1982, Phoenix, Arizona.

26. Assaf, G. "The Dead Sea: A Scheme for a Solar Lake," Solar Energy, Vol. 18, pp. 293-299, 1976.

27. French, R. L. and Meitlis, I. "Salton Sea Solar Pond Project," Proceedings of the 15th Intersociety Energy Conversion Engineering Conference, Vol. 2, pp. 1430-1431, August 1980, Seattle, Washington.

28. Polon, "Power from the Dead Sea via Solar Ponds," Popular Science, pp. 84-86, April 1981.

29. Winsberg, "Solar Perspectives: Israel, Solar Pond Innovator," Sunworld, Vol. 5, No. 4, pp. 123-125, 1981.

30. Annual Report, 1 June 1980 to 31 May 1981, Brace Research Institute Report Number N-43, McGill University, Quebec, Canada.

8. Pytlinski, J. "Industrial Uses of Solar Energy in the United States," Proceedings of COMPLES 18th International Conference on Solar Energy, Vol. 1, pp. 267-283, September 1979, Milan, Italy.

26. Annual Report of 1982, Solar Division, Center for Energy and Environment Research, University of Puerto Rico, Mayaguez, Puerto Rico 00708.

27. Nielsen, C. E. "Experience with a Prototype Solar Pond for Space Heating," Proceedings of the International Solar Energy Society Conference, Vol. 5, pp. 169-182, August 1976, Winnipeg, Canada.

28. Short, H. Roller, W. U. and Badger, P. C. "A Solar Pond for Heating Greenhouses and Rural Residences - A Preliminary Report," Proceedings of the Solar Energy Workshop on Food/Fuel, pp. 41-50, April 1976, Tucson, Arizona, U.S.A.

29. Short, T. H. Badger, P. C. and Roller, W. L. "The Development and Demonstration of a Solar Pond for Heating Greenhouses," Proceedings of the International Solar Energy Society Silver Jubilee Congress, Vol. 2, pp. 1020-1026, May 1979, Atlanta, Georgia, U.S.A.

32. Nielsen, B.

"Design and Initial Operation of a 400 m² Solar Pond," Proceedings of the Annual Meeting of the American Section of the International Solar Energy Society, Vol. 3, pp. 381-385, June 1980, Phoenix, Arizona, USA. C. B. Nielsen and J. Kamal, "The 400 m² Solar Pond: One Year of Operation," Proceedings of the Annual Meeting of the American Section of the International Solar Energy Society, Vol. 4, pp. 758-762, May 1981, Philadelphia, Pennsylvania, USA. E. Kuberg, "Solar Ponds in the Region Served by the Tennessee Valley Authority," Proceedings of the 15th Inter-Society Energy Conversion Engineering Conference, pp. 1432-1434, August 1989, Seattle, Washington, USA. D. W. Kuberg, "A Review of TVA's Non-Convecting Solar Pond Activities," Proceedings of the Annual Meeting of the American Section of the International Solar Energy Society, Vol. 4, pp. 777-781, 1981, Philadelphia, Pennsylvania, USA.

Editorial article "Non-convecting Salt-Gradient Solar Pond - A New Energy Technology," Energy Demonstrations and Technology, Issue 13, 1981, Office of Power, Tennessee Valley Authority, R. P. Beldam and J. F. Lane, "Experimental Operation of a Small Solar Pond," Proceedings of the Conference ENERGEX-82, Vol. 2, pp. 715-508, August 1982, Regina, Saskatchewan, Canada. R. A. Davey, "The Aspendale Solar Pond," Report R15, 1968, CSIRO, Highett, Victoria 3190, Australia.

International Solar Pond Newsletter, No. 4, January 1981, B23, T. Ochs Editor, Desert Research Institute, Boulder City, Nevada 89005. B. Nimmo, A. Dabbagh and S. Said, "Salt-Gradient Solar Ponds," Sunworld, Vol. 5, No. 4, pp. 113-114, 1981. S.M. Patel and C. Gupta, "Experimental Solar Pond in a Hot Humid Climate," Sunworld, Vol. 5, No. 4, pp. 115-118, 1982.

J. Bonnet, Jr., J. T. Pytlinski and K. Soderstrom, "Solar Energy Storage for Cooling Systems in the Caribbean," Proceedings of the International Workshop on Solar Energy Storage, March 1982, Jeddah, Saudi Arabia.

(Page Break)

S. Bryant, R. Browser and L. J. Wittenberg, "Con

"Construction and Initial Operation of the Miamisburg Salt-Gradient Solar Pond," Proceedings of the International Solar Energy Society Silver Jubilee Congress, Vol. 2, Pp. 1005-1009, May 1979, Atlanta, Georgia, U.S.A. M. Tenverg and M. J. Harris, "Evaluation of a Large Convective Solar Pond," Proceedings of the Workshop on Solar Energy Storage Options, Vol. 2, pp. 193-202, March 1979, San Antonio, Texas, U.S.A.

L. J. Wittenberg and M. J. Harris, "Management of a Large, Operational Solar Pond," Proceedings of the 15th Intersociety Energy Conversion Engineering Conference, Vol. 2, pp. 1435-1457, August 1980, Seattle, Washington, U.S.A.

M. O. Norris, D. E. Etter and L. J. Wittenberg, "Observations Regarding Materials and Site Preparation for Salt-Gradient Solar Ponds," Proceedings of the Annual Meeting of the American Section of the International Solar Energy Society, vol. 4, pp. 787-790, May 1981, Philadelphia,

Pennsylvania, U.S.A.

D. Crevier, "An Experimental Solar Pond for Industrial Process Heat," Proceedings of the Conference ENERGEX-82, Vol. 2, pp. 709-714, August 1982, Regina, Saskatchewan, Canada.

R. L. French and I. Meitlis, "Salton Sea Solar Pond Project," Proceedings of the 15th Intersociety Energy Conversion Engineering Conference, Vol. 2, pp. 1430-1431, August 1980, Seattle, Washington, U.S.A.

-Page Break-

-Page Break-

CENTRAL STAND, annotated 'ounce' with a series of pictures and diagrams.

-Page Break-

Figures and diagrams continued, including views of shallow pond, research pond, and various structural elements.

-Page Break-

More figures and diagrams.

Sovayns among people