

CEER-S-185 SOLAR PONDS: RESEARCH, APPLICATIONS, AND DEVELOPMENT by Shone, JuT. PYTLINSKE, a member of the CENTER FOR ENERGY AND ENVIRONMENT RESEARCH.

Proceedings of the 5th Miami International Conference on Alternative Energy Sources, December 13-15, 1962, Miami Beach, Florida, U.S.A.

SOLAR PONDS: RESEARCH, APPLICATIONS, AND DEVELOPMENT by J. T. Pytlinski, Center for Energy and Environment Research, University of Puerto Rico, Mayaguez, Puerto Rico, 00708, U.S.A.

## ABSTRACT

This paper provides a description of the status of solar pond research, applications, and development. Shallow ponds, gel ponds, saturated ponds, and salt-gradient ponds are discussed, and many existing ponds in various countries are described. Ongoing field and laboratory work associated with solar ponds is discussed in relation to residential, commercial, industrial, and agricultural applications of pond-generated heat. Other present or future applications of salt-gradient ponds, such as electricity generation, irrigation water pumping, and the more recent absorption and dehumidification cooling are presented. Pond construction and operation, including costs, are discussed and schematic diagrams are used to illustrate textual explanations. An extensive list of references treating theoretical and practical aspects of pond research, applications, and development is also provided.

## INTRODUCTION

Fossil fuels do not exist as a natural resource in many countries, and these countries are forced to rely on imported oil, coal, or nuclear technology in spite of the continuous balance of payment problems most of them face. Over the past few years, solar ponds have received special attention as one of the solar technologies which have the potential to be economically and technically competitive with energy conversion technologies that use fossil fuels (see Fig. 1). Solar ponds could, therefore, improve the energy situation in some countries. In addition to their low cost, some solar ponds, such as the salt-gradient type, offer built-in storage. This makes them

Independent of the intermittence of solar radiation, it is the shallow solar ponds, first introduced in the mid-seventies by Lawrence Livermore Laboratory of California, that appear to be the most developed and market-ready. This is illustrated by several publications on the theoretical and practical aspects of shallow solar pond use, including applications for generating industrial process heat [1-6]. The construction methodology of shallow ponds [7] and their internal performance testing have been described in detail [8,9]. In one innovative concept that has been tested, a shallow solar pond's performance was enhanced by placing a mirror on its north side [10]. In a theoretical study on pond sizing and design optimization, the simulation and modeling of a shallow solar pond were performed using the TRNSYS program [11]. Although the economics seem to be in favor of shallow solar ponds [2,12], the demonstration program for them has been debated since applications are mainly restricted to users in the South and Southwest of the U.S. For this reason, the shading technology does not contribute much toward the development of solar equipment production and the commercialization of solar technology. However, a renewed interest in shallow solar ponds seems to be taking place, particularly for applications in the Caribbean. The concept of

collecting and storing solar energy by means of salt-gradient ponds, also known as non-convecting solar ponds, was derived from research on natural salt lakes [13]. Salt-gradient solar ponds reached the application level in recent years, although some aspects of their construction, operation, and maintenance are still in the research and development stage. Some of the most important work on salt-gradient ponds was done in Israel [14,15]; the concept of ponds generating process heat was introduced there in the mid-fifties. The continuation of this work in Israel and elsewhere resulted in several review papers and

Reports discuss the current status of technology, cost, and the physical and thermal phenomena that occur in salt gradient solar ponds [16-21]. The physics of salt-gradient solar ponds is the subject of theoretical and experimental studies [22, 23]. Detailed descriptions of pond systems and knowledge of material selection, site preparation and pond construction techniques are available for medium and large-scale ponds [26-48] and small laboratory ponds [49-52]. This is due to the work of many researchers.

Experimental aspects of salt-gradient pond instrumentation have been investigated [53] and theoretical studies of modeling and simulation have been performed [54-62]. In addition, several innovative pond concepts have been proposed [63-68]. Studied and/or implemented salt-gradient pond applications include absorption and dehumidification cooling [68], commercial and residential space heating [69-71], district heating and cooling [72,73], low-temperature (between 50°C and 70°C) industrial water heating [74], agricultural process heat production for grain drying [75], and greenhouse heating [76-79]. Other applications include using salt-gradient solar ponds for salt production enhancement [50-82] and electricity generation [3-87]. The pumping of irrigation water is another area where salt-gradient solar ponds can be used effectively. Some laboratory investigations have also been done on saturated salt ponds [88-91] and gel ponds [92,93]. Both of these techniques for solar heat collection and storage are still in the research stage. They do not attract the interest and financial support that shallow solar ponds and salt-gradient ponds do. The development work on solar ponds is primarily focused on the use of large-scale (up to 50 MW) modular salt-gradient ponds for electricity generation [94-99]. The economics of scale, simplicity of construction, and technological readiness make such stand-alone plants especially attractive in areas where natural resources are abundant.

Salt lakes already exist and can be converted into production ponds with a minimum of technical effort and cost. Selected research, applications, and development efforts in the field of solar ponds are described below to provide a comprehensive description of the present status of solar pond work.

## RESEARCH PONDS:

In the United States, research activities on shallow solar ponds, salt-gradient ponds, salt-saturated solar ponds, and gel ponds are being conducted at several locations. A cross-sectional view of a shallow solar pond is shown in Figure 2. A typical shallow solar pond resembles a thermally insulated, plastic water bag partially filled with water. The bag may have a black bottom for absorbing solar radiation, and a clear top to prevent evaporation and assure the greenhouse effect. The most recent design calls for a black hypalon or polyvinyl chloride (PVC) water bag with a clear fiberglass cover supported by concrete curbs and metal struts.

The hot water from the pond is drained down to a storage tank once or several times per day depending on the system requirements. The first shallow solar pond system, designed and operated by Lawrence Livermore Laboratory of California, was built in 1975 near Grant, New Mexico. The pond system consisted of two modules of 220 sq. m. (2400 sq. ft.) each, which contained 10cm (3.9 in.) of water. This prototype system was built at a uranium mining and milling plant of Sohio Petroleum Company.

Fig.2. Cross-Sectional View of Shallow Solar Pond Module.

The shallow pond modules operated on a stand-alone basis without being interfaced with the plant hot water system. Each pond module heated 25 tons of water per day to about 54°C (130°F) in the summer and to about 35°C (95°F) in the winter. A twelve-month performance survey of the system operation indicated that the solar ponds operated with an annual average energy collection efficiency of about 45 percent and collected close to  $9.37 \times 10^3$  Joules/m<sup>2</sup>-day (825 Btu/ft<sup>2</sup>-day). Figure 3 shows

The text describes a cross-sectional view of a typical salt-gradient solar pond. Salt-gradient ponds are large pools of water that are open to the environment and filled with salty water. The liquid top layer, known as the upper convective zone, has a salt content of 1-4 percent, while the bottom layer, known as the lower convective zone, has a salt content as high as 23-27 percent.

When exposed to solar radiation, the denser bottom layer is heated to a much higher temperature than the surface layer. The heat accumulated in the lower convective zone is trapped due to the low salinity nonconvective zone, which separates the high-density brine at the pond bottom from the upper convective zone. Thus, the use of a salt pond eliminates the need for separate thermal storage that is typically required in many solar installations.

A salt-gradient solar pond with a 200 sq. m. (2152 sq. ft.) area, a depth of 2.5 m. (8.2 ft.), and 45° tapered walls has been operating since 1975 at Ohio State University in Columbus, Ohio. In 1976, this pond reached a maximum temperature of 62°C (144°F). Experimental and theoretical research has been done in relation to some of the physical phenomena occurring in the pond, and on the pond operation and maintenance.

A second salt-gradient solar pond with a 408 sq. m. (4390 sq. ft.) area was installed at Ohio State University in 1979. This pond is 4.5m (14.8 ft.) deep at the center and 1.5m (4.9 ft.) deep close to the walls. The walls of the pond are vertical and are made out of wood planks. The pond is thermally insulated by styrofoam and urethane and is extensively instrumented to provide data on solar input, heat gain by the pond, heat loss to the ground, and heat conducted upward through the gradient layer.

Another pond of this type with a 156 sq. m. (1678 sq. ft.) area and a depth of 3.6 m. (11.8 ft.), and vertical wooden walls has been operating successfully on an experimental basis since 1977, providing heat for a greenhouse.

The following text is about the Ohio Agricultural Research and Development Center in Wooster, Ohio [76-78]. Although this pond provides heat for a greenhouse, its main purpose is to serve as a research base where various aspects of the pond operation and heat extraction are studied. A

research salt-gradient solar pond of 177 sq. m. (1901 sq. ft) with a depth of 2.5 meters and walls tapered at 34° was installed at New Mexico University in Albuquerque, New Mexico, in 1975 [27]. In the second year of the pond's operation, the storage layer reached a temperature of 93°C (199°F). Studies on the operational parameters, the criteria for materials to be used, the cost and performance data, and the physical behavior of the pond exposed to the environment are being performed. Proof of the technical feasibility of heat extraction was obtained by the successful operation of the pond year-round and by the extraction of an amount of heat adequate for heating a 185 sq.m. (1990 sq. ft.) house located in the Southwest region. The same pond reached a boiling temperature of 108°C (226°F) during the summer of 1980.

Work on the construction of a salt-gradient solar pond was also initiated in 1971 by the University of Utah, in Utah. The research pond of 850 sq. m. (9146 sq. ft.) and a depth of 1.1m. (3.6 ft.) was built during 1979 on the southwest side of the Great Salt Lake [34]. The maximum temperature reached by the pond was 55°C (131°F), which was achieved after about six weeks of pond operation. However, at the beginning of 1980, a very strong wind of approximately 35.8 m/s (80 mph) destroyed the salt gradient and emptied almost one-fourth of the pond into the dike surrounding it.

The pond was built to investigate the physical processes that occur in a salt-gradient pond and to develop an experimental base for computer modeling of various design schemes for electrical power generation using large size production ponds.

A salt-gradient pond has been operating at the Argonne National Laboratory in Illinois since 1980 [25,42]. The pond has an

The area of the pond is 1075 sq.m. (11567 sq. ft.) and its sides are tapered at an angle of 45° to a depth of 4.27 m. (14 ft.). By the end of 1981, the pond had reached a temperature of 63°C (145°F). The main objective of building this pond was to provide a research base for assessing the salt-gradient pond as a heat collection and storage system for various applications, and to set up fan operations for a future U.S. solar ponds program. This pond is well-equipped and has already provided data that can be used to guide future builders of salt-gradient solar pond systems.

The Tennessee Valley Authority (TVA) installed a 4047 sq. m. (43543 sq. ft.) pond in Tennessee in 1981 [34,37,43]. This pond works in conjunction with a 2484 sq. m. (26724 sq. ft.) evaporation pond which is 1.2m. (4 ft.) deep and has walls tapered at 34°. The TVA pond is extensively equipped and will provide important information on pond reliability, operating costs, and energy collection efficiency, thus making a significant contribution towards the commercialization of pond technology. This pond is available to outside users as a testing site.

One of the most recently installed ponds is a 234 sq. m. (2518 sq. ft.) salt-gradient solar pond that was built in June 1982 at the Los Alamos National Laboratory in Albuquerque, New Mexico [48]. The pond has a depth of 3.6m. (11.8 ft.) and the walls are vertical. Two liners were used for the pond construction; the first one is a 1.2 mm. (45 mil) thick main Hypalon liner and the second one is a 0.5 mm. (20 mil) thick polyvinyl chloride (PVC) liner. The second liner was laid over 15 cm. (6 in.) of sand spread uniformly over the pond bottom. Also, a 6.4 cm. (2.5 in.) thick layer of sand was spread between the liners. The walls of the pond are thermally insulated with 7.6 cm. (3 in.) thick polyurethane foam insulation. To attain a brine salinity of 21 percent at the pond bottom, about 127 tons of 98 percent pure, granular NaCl were used. The salt was dissolved using a local fire hydrant,

and further salt mixing was done.

The process involves using a couple of pumps, each with a capacity of around 400 liters/min. (105 gal./min.). The salt gradient was established by lowering the diffuser to a depth of 1.2 m. (3.9 ft.) from the bottom, which corresponded to the chosen thickness of the lower convective zone. With the diffuser in that position, 5.1 cm. (2 in.) of fresh water was added. The diffuser was then moved up 10.2 cm. (4 in.), and another 5.1 cm. (2 in.) of fresh water was infused into the pond. This procedure was repeated several times until the pond's depth reached about 2.4m. (7.8 ft.). At this point, an additional 10 cm. (3.9 in.) of fresh water was added at the top of the pond.

This process allowed the pond to reach the predetermined parameters of a 1.2m (3.9 ft.) thick lower convective zone, a 1.2m (3.9 ft.) thick non-convective zone, and a 10 cm thick upper convective zone. One month after the salt gradient had been established, the salinity and temperature of the pond reached 21 percent and 50°C (122°F) respectively. The heating rate of the pond at that time was approximately 1.2°C/day (2.8°F/day).

The pond is equipped with an underwater Eppley pyranometer, two 100 Ohm platinum resistance thermometers (RTD), a platinum point conductivity probe, and an induction salinometer. Four leak detection sensors are embedded in the sand at the pond bottom. Twelve vinyl jacketed copper-constantan thermocouples, in groups of three, are installed in the walls and six are embedded in the pond bottom to determine heat losses from the pond.

A weather station is used in conjunction with the other pond instrumentation. The station consists of a horizontally mounted Eppley Model 8-48 pyranometer, a wind speed and direction measuring anemometer, and a thermally shielded ambient temperature sensor. Data from about 80 channels is processed by a Hewlett Packard Model 87 desktop computer.

The pond is primarily used to study the boundary layer structure at the interface between the convecting and non-convecting zones, interactions between the zones, and diurnal heating.

Effect and wind-induced turbulances. The Los Alamos salt-gradient pond works in conjunction with an evaporation pond of 257 sq. m. (2765 sq. ft.) and a depth of 2.4 m (7.87 ft). All the walls of this pond are vertical except the west wall which is sloped at a 16° angle to create a ramp for salt removal and pond maintenance. The Center for Energy and Environment Research (CEER) of the University of Puerto Rico in Mayaguez is currently installing a research pond of 39 sq. m. (415 sq. ft.) with a depth of 0.9 to 1.5m, (2.95-4.92 ft), and vertical walls. This pond will work in conjunction with an evaporation pond of the same area but with half the depth. The research pond will be well instrumented to study the physics and engineering aspects of pond operations, maintenance, and control. Some computer simulation work will also be performed. This research pond will be a pilot system for a one-half acre production pond to be used to generate process heat for a food processing company in Puerto Rico. Salt-gradient solar pond research is also being done at the Massachusetts Institute of Technology. The work here is primarily directed toward the development of a numerically aided time-dependent vertical temperature and salinity profile in salt ponds. Wind mixing is also being studied by means of a three-dimensional numerical model. Laboratory research work on salt saturated ponds has been done by the Desert Research Institute in Nevada using borax as salt, and by Inter Technology Company in Virginia using monoammonium phosphate as salt. In the former case, the area of the pond built in 1979 was 10 sq. m. (108 sq. ft.) with a depth of 1m (3.28 ft.); in the latter case, the pond was 0.37 sq.m (3.7 sq. ft.) with a depth of

0.91 m. (3.0 ft.). The maximum temperature reached by the Desert Research Institute pond was 47°C (117°F). Reduced maintenance and lower fresh water usage are some of the advantages of using saturated ponds. The salt gradient ponds tested had the property of being self-established.

Research on gel ponds has been conducted at the University Of New Mexico since 1981 using an experimental pond of 18.7 sq. m (201 sq. ft.) [92,93]. The effect of the polymer gel thickness upon the performance of the gel pond is being studied. It was found that the surface heat losses from a pond containing a 25 cm (9.9 in.) layer of gel over about 1.22 m (4 ft.) of low salinity water were approximately half those from a salt-gradient pond with a 1 m (3.28 ft.) stratified salt zone under the same conditions. For the optimum operation of a gel pond, research indicates that a 15 cm (6 in.) gel thickness is adequate. The gel chemical formula, which is the subject of a patent, is not available. The present estimate is that the polymer gel will last three years in a pond under natural solar exposure.

Heat is extracted from a gel pond in the same way as it is from salt gradient and salt-saturated ponds; that is, by using internal or external heat exchangers. In Israel, research on salt-gradient solar ponds has been underway since 1954, the year the concept was conceived there (84). After a nine-year pause, work in this area was revived again in 1975. Because of Israel's almost total reliance on imported fossil fuels, salt-gradient solar pond research is oriented primarily.

Towards electricity generation, in 1977, a 1500 sq.m. (16140 sq. ft.) pond was made operational in Yavne by Ormat Turbine Ltd. The pond reached a temperature of 90°C (194°F) the same year. The pond generated an electric power output in the range of 6 kWe, using an organic cycle system equipped with a turbine as the prime mover. This closed-loop self-contained system employed chlorobenzene as the working fluid. Water at 29°C (84°F) from the surface of the pond was used to cool the condenser. A larger pond of 7500 sq.m. (80700 sq. ft.) area and a depth of 2.5m. (8 ft.) was installed in Ein Bokek by the Dead Sea in 1976 [94,96,97]. When the temperature of the storage layer reached 80°C (176°F), the pond started to produce electricity using a 6 kW capacity Ormat system. A large Ormat system of 300 kW capacity was installed in 1979 and the pond delivered 145 kW of electricity the same year, operating at 93-100°C (199-212°F) evaporator temperature and at about 30°C (86°F) condenser temperature. Desalination activities are also planned here as secondary research efforts. The main thrust of the Israeli research effort is towards obtaining a complete understanding of salt-gradient pond technology for electric power.

Production in order to commercialize such systems for domestic and export markets as "turnkey" plants. In Canada, the first research salt-gradient solar pond was installed in 1980 at the Brace Research Institute in Montreal (80). A cross-sectional view of this pond is shown in Figure 4. The same year, an experimental pond was implemented by the National Research Council of Canada. The pond area is 17 sq.m. (189 sq. ft) and the depth is 0.96 m. (2.62 ft). The walls of the pond are vertical. An external, brine-to-air heat exchanger made out of copper tubing is being used. The maximum temperature reached by the storage layer in 1981 was about 50°C (122°F). The general objectives of installing this research pond were to obtain firsthand practical knowledge of methods and problems.

Associated with the construction, operation, and maintenance of a solar pond in preparation for the design and operation of a larger protection pond. The National Research Council of Canada

finances this research for developing equipment and procedures for automating the operation and maintenance of salt-gradient ponds. In Australia, the first salt-gradient pond was built in Aspendale in 1964. This pond had an area of 106 sq.m. (1140 sq. ft.) and a depth of 0.86 m. (2.82 ft.). Locally available clay was used to seal the bottom and the walls of the ponds. Lime was used. The storage layer reached a maximum temperature of 63°C (145°F) in the summer of the second year of operations. The same year, the pond developed a leak which contributed to the discontinuation of the project. The results of this research, which was oriented toward studying the pond's thermal efficiency, the sealing techniques, and the control of the salinity gradient, were published in the form of a report [26]. The second salt-gradient solar pond was built by the University of Melbourne in 1981 for research purposes [40]. The pond area is 340 sq.m. (3658 sq. ft.). Research is focused on the stability of the salt gradient, the methodology of pond filling, and the expectation of thermal phenomena. In 1961, a 2000 sq.m (21820 sq. ft.) salt-gradient solar pond was built in Alice Springs. Fig. 6. Cross-Sectional view of salt-gradient research pond.

In Saudi Arabia, a research pond of 4 sq.m. (45 sq. ft.) and a depth of 2.3 m. (7.5 ft.) was built in 2000 by the Research Institute of the University of Petroleum and Minerals in Dhahran [52]. This research pond is being used to gain operating experience and to design proper instrumentation for a future large production pond. The activities are focused on computer simulation of sand behavior and on gaining experience in designing and building salt-gradient solar ponds by employing indigenous labor and machinery. In India, a salt-gradient solar pond of 100 sq.m.(1075 sq. ft.) was constructed.

The text should read:

The depth of 2.25 m. (7.4 ft.) was built in 1980 by the Tove Energy Research Institute in Pondicherry [35]. The pond has vertical walls and works in conjunction with an evaporation pond of 50 sq.m. (538 sq. ft.) area and a depth of 0.7 m. (2.3 ft.). The maximum temperature reached by the pond that same year was 10°C (50°F). The pond is instrumented to provide research results on thermal performance and the behavior of the stratification layers. Experience was gained about which locally available materials can be used to build a pond and about pond construction and operation costs in India's rural environment.

### 3. APPLICATION ACTIVITIES

The most immediate applications of solar ponds seem to be for space heating and for water heating/reheating for residential, commercial, industrial, and agricultural uses where the temperature requirement is in the region of 49°C to 66°C (120° to 150°F). A schematic diagram of a possible salt-gradient solar pond system is shown in Figure 5. In tropical climates such as the Caribbean, salt-gradient ponds may be used in the future for dehumidification cooling as proposed by Bonnet et al. [6].

In the United States in March 1983, a shallow solar pond system was installed to supply 2,000,000 liters (528,401 gal.) of hot water per day to two army barracks and the laundry at Fort Benning in Georgia [19]. A total of 89 modules having an area of 25,000 sq. m. (269,000 sq. ft.) were built. Each module contains two water bags made of industrial-grade 9.7 mm. (35 mil.) thick Hypalon. A fiberglass cover over the water bags ensures the greenhouse effect. After the system's installation,

the water bags were sterilized on site by rinsing them twice with Clorox in a four-hour period. An above-ground, 1,892,500 liter (500,000 gal.) capacity steel tank is used for hot water storage. The system is located 1402-1463 m. (4609-4800 ft.) from the end use and the hot water is distributed by 15 cm. (6 in.) diameter PVC pipes. The installed system cost was \$411,000 with a

The construction cost was \$4,000,000 and a dexion cost of \$110,000 which gives a total cost of \$164/sq. m. (\$15.28/sq. ft.). A shallow solar pond of 22 sq. m. (240 sq. ft.) and a depth of 2.54 cm. (1 in.) was installed in January 1903 on the roof of a high school in Mayaguez, Puerto Rico, to deliver daily 40 liters (150 gal.) of hot water at the temperature of 60°C (140°F) to the school cafeteria [74]. Another shallow solar pond of 40 sq.m. (430 sq. ft.) area and a depth of 7.6 cm, (3 in.) is planned to be built to heat water for showers at the swimming pool facility at the Mayaguez Campus of the University of Puerto Rico. The project specifications call for heating 3028 liters (800 gal.) of water to a temperature of 43°C (110°F) daily. The solar pond system could reduce the electricity consumption of the electric water heater by 75 percent. A schematic diagram of a typical shallow solar pond system is shown in Figure 6. A production salt-gradient solar pond of 2044 sq.m. (21,993 sq. ft.) was built in 1978 by the city of Miamisburg, Ohio, to supply heat to an outdoor swimming pool in the summer and to a recreational building in the winter [30,31,33,41]. The pond depth was 2.0 m. (10 ft.) and the walls were tapered at an angle of 45°. Polymer-coated polyester liner XR-5 0.7 mm, (35 mil) thick and sodium chloride as salt were used. The energy storage layer had a thickness of 1.75 m. (5.7 ft.) and contained brine of 28.5 percent concentration. The temperature required at the end use was 25°C (77°F). The maximum temperature reached by the storage layer of the pond was 65°C (149°F) during the summer of 1979. The pond was equipped with a heat exchanger made out of copper tubing of 2.54 cm. (1 in.) diameter which was placed at the bottom of the pond. The effective surface area of the heat exchanger was 180 sq. m. (1937 sq. ft.). The cost of the pond construction was \$35/sq. m. (\$3.26/sq. ft.), excluding the land cost. After a successful initial operation of two years, this pond developed a leak in the liner in 1980 and had.

In Portugal, a salt-gradient solar pond was built in Lisbon to heat a greenhouse complex belonging to the Portuguese Ministry of Agriculture [79]. The pond has an area of 1024 sq. m. (11018 sq. ft.), a depth of 3.60 m. (11.8 ft.), and walls sloped at a 45° angle. The pond uses 1 mm (140 mil) thick hypalon liners and sodium chloride as salt. A heat exchanger, used to extract heat from the pond, consists of four sections, each 2.4 m. x 5.0m, (7.9 ft. x 16.4 ft.), made out of galvanized 2.54 cm (1 in) O.D. iron pipe. The heat exchanger was designed for an expected peak energy extraction rate of 50 kW. A diffuser used for maintaining the salinity gradient consists of a galvanized iron tube of 7.6 cm. (3 in.) O.D. welded to a 1.2 m. x 1.2m. (3.9 ft. x 3.9 ft.) plate attached to another plate of the same dimension in such a way as to form a space of 1.6 cm. (0.6 in.) between both plates. The pond is extensively instrumented with thermocouples, salt solution and soil conductivity probes, underwater and surface pyranometers, and wind-measuring instrumentation. A 16 sq. m. (172 sq. ft.) evaporation pond was built as part of the overall salt-gradient pond system.

In Argentina, a 400 sq. m. (4304 sq. ft.) salt-gradient solar pond was built in Salta to purify sodium sulfate."

Salt is produced using a natural evaporation process [42]. The pond, equipped with vertical wells, has a depth of 2.4m. (7.9 ft.) and a solution depth of 1-5 m (4.9 ft.). Instrumentation of the pond was achieved by placing several thermocouples in the solution at various depths and at three different locations across the pond. An electric wire mesh was created by forming two layers of wire under



the pond to detect leaks. However, this wire mesh was short-circuited due to water condensation under the pond and thus, was rendered ineffective in detecting leaks.

Clay was used to smooth out the pond walls, and 10 cm. (3.3 in.) of sand was laid at the pond bottom before installing two layers of black polyethylene, each 0.25 mm (10 mil.) thick. The pond was filled with 50 cm (1.64 ft.) of water, after which 250 tons of mineral salt, intended for purification, was thrown into the pond.

To establish and later control the salt gradient, a diffuser comprising of two metal plates was used. These plates, separated by a 20.25 cm. (8 in.) space, were shaped like a half-disk with a diameter of 45 cm. (1.47 ft.). The diffuser injected 2.5 cm. (1 in.) of fresh water several times, moving up 5 cm (2 in.) each time. The water velocity was approximately 2 m/sec. (6.56 ft/sec.). Around 10 kg. (22 lbs) of copper sulphate was added to the pond to prevent algae growth.

After twenty days, the pond solution was very clear again. After forty days, the pond bottom reached a temperature of 40°C (104°F) and a fine salt density gradient of 2.32 g/cu.cm at the bottom and 1.05 g/cu.cm at the surface was established. The water evaporation rate from the pond has been 3 to 5 mm. (0.12 to 0.2 in.) per day. The pond produces 0.5 tons of industrial-grade sodium sulphate salt every three days.

#### 4. DEVELOPMENT WORK

Currently, the development work is predominantly taking place in countries where research and application activities have already gained momentum. As a natural extension of these activities, the development work is focused on stand-alone plants that produce large amounts of hot water, heat and/or electricity. The selection of these plants is based on their ability to meet specific energy requirements.

#### Schematic Diagram of Electricity Generation System Using Salt-Gradient Solar Pond 1s

#### SECTION: CONSTRUCTION, OPERATION AND COST

The largest salt-gradient production pond in operation has an area of 2044 sq. m. (21,993 sq. ft.). The largest shallow pond constructed has an area of 25,000 sq. m. (269,000 sq. ft.). Pond shapes vary from circular for small size salt-gradient research ponds, to rectangular (east-west oriented) or square for large ponds. The latter are usually built in modular units to provide the required thermal/electrical capacity.

Before building a pond, 20-30 ft. core sampling should be made to test the soil composition and permeability. The thermal conductivity of the soil around the pond can vary between 1 and 2.5 watts/m\*c. It is recommended to test the soil thermal conductivity and to determine the existence of movable underground water.

Borax, disodium phosphate and sodium sulphate have been experimented with and studied as possible salts for saturated ponds. Sodium-chloride is the salt usually used in salt-gradient ponds,

although magnesium-chloride is being used in Israel since it is commonly available there. Refined salt of 95 percent or more purity should be used. The type of salt is of significance (NaCl, MgCl, CaCl, etc.) because of the brine transmissivity factor, and because the salt solubility changes with temperature.

About 45 kg. (100 lbs.) of salt per approximately 0.1 sq.m. (1 sq. ft.) of pond area are needed to obtain the right salt concentration in the lower convective zone. Out of this, 0.45-0.90 kg (1-2 lbs.) per 0.1 sq. m. (1 sq. ft.) per year will diffuse upward.

Diffusers are used to establish the vertical salinity gradient. This is done by lowering the diffuser to the boundary limits of the lower convective zone; this zone should be previously established by dumping salt at the pond bottom and mixing it with fresh water. In the next step, a layer of fresh water a few centimeters thick (5-10 cm.) is added. This procedure is repeated until the water...

The level in the pond reaches the mark chosen as the pond depth. A similar process is used to maintain and repair the salinity gradient. A diffuser can be made out of two 1 meter (3.28 ft.) diameter disks made of a non-corrosive material such as plexiglass, a few centimeters thick. The gap between the disks and the supply water flow rate should be such as to assure a water velocity from the gap in the range of 0.25-1.0 m/sec. (0.7-3 ft/sec) , depending on the pond size. For a 1/4 acre size pond, two diffusers located in opposite corners of the pond may be adequate to perform the gradient maintenance work, but in the case of a 1/2 acre pond, four diffusers may be necessary. The amount of solar radiation penetrating to the pond bottom can vary between 20 and 40 percent. The thermal efficiency of a large size (1/2 acre) salt gradient solar pond is usually in the range of 15 to 20 percent, although it could be as low as 9 percent for small size laboratory ponds where high heat losses occur. An operational pond temperature of about 60°C (140°F) with temperature fluctuations of above (223°F) can be expected. The pond upper convective layer usually has 1-4 percent of salt and the lower convective layer has 23-27 percent of salt by weight. When an internal heat exchanger is used, the rule of thumb is that about 37 m. (222 ft.) of heat exchanger piping length is needed for every 20 kw of thermal power extraction from the pond. The heat exchanger piping should form a serpentine configuration and be located in the lower convective zone. Copper and brass piping are often used as heat exchangers. To assure the reliability of heat extraction from the pond and equipment durability, a stainless steel heat exchanger and leak-proof pump may be recommended. A galvanized iron pipe heat exchanger will corrode easily when the saturated solution level comes down below the heat exchanger and exposes the piping to a non-saturated water salt solution. Because of the scarcity of information about metal corrosion in

Solutions of high salt concentration, however, an external heat exchanger may be more suitable for a heat extraction system, especially for large-sized ponds. If an external heat exchanger is used, an effort should be made to prevent any air leaks in the external piping or in the pump, because air bubbles will be introduced into the lower convective zone. A continuous injection of air bubbles could destroy the salinity gradient in the pond. To assure the effective maintenance of the salinity gradient zone, the injection of 2-5 kg/sq.m. (4.4-10 lbs/sq.ft.) of salt per month may be required. This should be done just below the boundary of the upper convective zone since this zone has a tendency to grow thick, a process which leads to the destruction of the temperature gradient in the pond. Usually, PVC valves and PVC piping are used to carry the brine to an external heat exchanger. Another rule of thumb is that 1-2 kg. (2.2-4.4 lbs.) of chlorine per week per each 1600 sq. m. (10760 sq.ft.) of pond area may be needed to prevent algae build-up in the pond. An

evaporation pond often works in conjunction with the production pond. The evaporation pond, up to half the size of the production pond, serves to produce highly concentrated brine which is injected into the production pond to maintain the salinity gradient. The evaporation pond can also be used to take care of the rainwater overflow from the production pond. Both ponds may have vertical walls or 45° sloped walls. The latter, however, can increase heat losses through thermal convection at the walls. Heavy-duty plastic liners made from chemically resistant polymer-coated polyester fabric, vinyl liner, EPDM liners or XR-5SP Hypalon fiberglass reinforced liner seem to work satisfactorily. The second liner (backup liner) is usually thinner and also cheaper. Beach sand is recommended for use in a 10 cm. (3.9 in.) thick layer at the bottom of the pond and between the liners. The pond bottom and/or walls are sometimes thermally insulated as well. Floating

PVC pipes can be used to suppress wind disturbances on the pond surface. Detecting and locating leaks is one of the most difficult problems in a salt-gradient solar pond. Most often, the leaks occur in seams of the liner. To locate a leak in the pond, either two scuba divers are used or the following method could be employed: a length of perforated rubber or plastic hose in a serpentine arrangement is buried in the sand layer between the liners during the pond construction. The hose is plugged at the buried end and runs above ground at the other end. Upon suspecting a leak, by routinely checking the salt inventory in the pond, compressed air or nitrogen is introduced into the hose with sufficient pressure to equal the hydrostatic pressure at the bottom of the pond. The leak locations are found by locating gas bubble streams on the pond surface. A sump pump could be connected to the hose to evacuate the leaking solution from beneath the liner. The same pump can also be used to evacuate the brine from the lower convective layer to the evaporative pond; usually, it is necessary to empty the pond to patch up the liner. Recalibrated platinum electric conductivity probes are used for salinity gradient measurement. Probes of the same type are used for leak detection between liners. Copper-constantan thermocouples in stainless steel or vinyl jackets are normally used for ground temperature measurement. Platinum resistance thermometers, e.g. 100 Ohm RTDs, are used for pond temperature measurement. Generally, the present cost of man-made salt-gradient ponds is in the range of \$50 to \$100/sq. m. (\$4.60 to \$8.30/sq. ft.). Naturally occurring salt lakes can be converted into ponds at a cost much below \$50/sq. m. (\$4.60/sq. ft.). The major capital costs are for salt, liner, excavation and heat extraction equipment. The salt cost can be up to half of the total cost. When a salt lake is used as a solar pond for the construction of an electric power plant, the total cost can be divided half and half between.

The cost of pond construction, power, and equipment varies. In some locations, such as countries in the Middle East, the cost of water for the pond make-up operation may not be negligible. In others, like the islands of the Caribbean region, the cost of land may be an important factor. Pond depth ranges from 0.9 m to 4.5 m (3 ft to 15 ft) with deeper ponds being used in areas where seasonal heat extraction is required. Energy costs are projected to be between \$6.60 and \$9.50/cubic meter (37 to 10 per million Btu's) for large size production ponds with an area of 40000 sq. m. (430400 sq. ft.). The construction cost of shallow solar ponds is higher and can be estimated to be in the range of \$150 to \$205/sq. m. (14 to \$19/sq. ft.).

Conclusions: Solar ponds are technically feasible and can be economically competitive, as proven by some users. Building an experimental pond may be a necessary first step to gain direct experience and to demonstrate engineering proof of the concept. However, out of the 25-30 small and large demonstration ponds that have been built around the world, only about seven are production ponds. Therefore, more production ponds should be built to gain market acceptability through the reliable and economical operation of large size ponds integrated into industrial,

commercial or agricultural processes. Although only a few production ponds have been built and operated, the technical simplicity and the research results obtained indicate that shallow solar ponds are market-ready while salt-gradient solar ponds may be on the fringe of market readiness. The technical/engineering problems related to pond applications are being addressed by current research and development activities. However, environmental, institutional, and policy issues lag behind and could act as obstacles to the large-scale use of solar ponds in the future.

#### References:

1. Ay Fy Clark and W. c. Dickinson, Shallow Solar Ponds, Chapter 12, pp. 377-402, Solar Energy Technology Handbook, Marcel

Dekker, Inc., New York, 1980.

2. W. C. Dickinson, A. P. Clark, and A. Yantuono, "Shallow Solar Ponds for Industrial Process Heat: The ERDA'Sohio Project," Report UCRI-78288, 1976, Lawrence Livermore Laboratory, University of California, Livermore, CA, 94550, U.S.A.

3. W. W. Auer and W. R. Cherry, "ERDA Solar Thermal Energy Program for Industrial Process Heat," Proceedings of the International Solar Energy Society Conference (Sharing the Sun, Solar Technology in the Seventies), Vol.1, pp. 176-185, August 15-20, 1976, Winnipeg, Canada.

4. G. R. Guinn and B. R. Hall, "Solar Production of Industrial Process Hot Water Using Shallow Solar Ponds," Proceedings of the Annual Meeting of the American Section of the International Solar Energy Society, Vol.2.1, pp. 947-951, August 28-31, 1978, Denver, Colorado, U.S.A.

5. A.B. Casamajor, "The Application of Shallow Solar Ponds for Industrial Process Heat: Case Histories," Proceedings of the Silver Jubilee Congress of the International Solar Energy Society, Vol.11, pp. 1029-1032, May 1979, Atlanta, Georgia, U.S.A.

6. "Industrial Process Heat," Solar Age, Vol.4, No.3, pp. 19-24, 1979.

7. A.B. Casamajor and R. E. Parsons, "Design Guide for Shallow Solar Ponds," UCRL-52385, January 8, 1973, Lawrence Livermore Laboratory, University of California, Livermore, CA, 94550, U.S.A.

8. A. I. Kudish and D. Wolf, "A Compact Shallow Solar Pond Hot Water Heater," Solar Energy, Vol.21, pp. 317-322, 1978.

9. R. E. Forbes, "Design and Testing of a Plastic Bubble - Film Covered Shallow Solar Pond," Proceedings of the ASHE Solar Energy Division Fourth Annual Conference, pp. 62-89, April 26-29, 1982, Albuquerque, New Mexico, U.S.A.

10. A. F. Clark, A. B. Casamajor, and L. O. Rewett, "Shallow Solar Ponds with Mirrors on the North Side," Proceedings of the International Solar Energy Society Congress, Vol-II, pp. 1078-1079, January 1978, New Delhi, India.

11. J.C. Silver and F.C. Wessling, "Simulation methods Developed for the Design of Commercial Hot Water Systems,"

The rest of the references are missing.

20. A.S. 22. 23. 24. 25. "Shallow Solar Ponds," Proceedings of the Annual Meeting of the American Section of the International Solar Energy Society, Vol. 4-1, pp. 782-785, May 1981, Philadelphia, Pennsylvania, U.S.A. G. Dickinson, "Economics of Process Heat from Solar Energy," Chemical Engineering, pp. 101-104, January 31, 1997. A. Nallecsinsky, "Ungarische Warme und Heisse Kocksalzeen als Natuerliche Warmeaccumulatoren," Annales der Physik, Vol. J, No. 4, pp. 408-416, 1902. B. Tabor, "Large Area Solar Collectors for Power Production," Solar Energy, Vol.7, No.6, pp. 189-194, 1963. H. Tabor and R. Matz, "Solar Pond Project," Solar Energy, Vol.9 No.4, pp. 177-182, 1965. D.L. Styris, R. Zaorski and O.K. Harling, "Nonconvecting Solar Pond: An Overview

of Technological Status and Possible Pond Applications," BNWL-1891, January 1975, Battelle Pacific Northwest Laboratory, Richland, Washington, U.S.A. 7. 8. Jayadev and M. Edesess, "Solar Ponds," SERI/TR-731-587, April 1980, Solar Energy Research Institute, Golden, Colorado 80401, U.S.A. D. Crevier, "State of the Art Review of Solar Ponds," Solar Energy Project Report No. Pond-1, August 1980, National Research Council of Canada, Ottawa, Canada. L. Sargent, "Overview of the DOE National and International Program for Salt-Gradient Solar Ponds," Proceedings of the Annual Meeting of the American Section of the International Solar Energy Society, Vol.3.1, pp. 395-399, June 1980, Phoenix, Arizona, U.S.A. H. Tabor, "Solar Ponds," Solar Energy, Vol.27, No.3, pp. 181- 134, 1981. M. Edesess, "On Solar Ponds: Salty Fare for the World's Energy Appetite," pp. 59-68, Technology Review, November-December, 1982. G.E. Nielsen, "Nonconvective Salt-Gradient Solar Ponds," Chapter 11, pp. 345-376, Solar Energy Technology Handbook, Marcel Dekker, Inc., New York, 1980. H. Tabor and Z. Weinberger, "Nonconvecting Solar Ponds," Solar Energy Handbook, Chapter 16, pp. 1-29, McGraw Hill, New York, 1981. M. Edesess, J. Henderson and T.S. Jayadev, "A Simple Design Tool of Sizing Solar Ponds," SERI/RR-351-347R.

December 1999, Solar Energy Research Institute, Golden, Colorado 80401, U.S.A. J.R. HULL, Y.S. Cha, and W.T. Sha, Major Design, Construction, and Operational Considerations of Salt-Gradient Solar Ponds, Paper 82, XVII Convention of Union Panamericana de Asociaciones de Ingenieros, August 1-7, 1982, CEER/UPR, GPO BOX 3682, San Juan, Puerto Rico 00936.

7. R.A. Davey, 'The Aspendale Solar Pond', CSIRO, Highett, Victoria 3190, Australia, Report R15, 1968. F. Zagrando and H.C. Bryant, 'A Salt-Gradient Solar Pond', pp. 21-35, Solar Age, April 1978.

E. Nielsen, 'Equilibrium Thickness of the Stable Gradient Zone in Solar Ponds', Proceedings of the Annual Meeting of American Section of the International Solar Energy Society, Vol. 2, pp. 932-935, August 28-31, 1978, Denver, Colorado, U.S.A.

B. Nielson, 'Control of Gradient Zone Boundaries', Proceedings of the Silver Jubilee Congress of the International Solar Energy Society, Vol. II, pp. 1010-1014, May 1979, Atlanta, Georgia, U.S.A.

B.S. Bryant, R.P. Bowser, and L.J. Wittenberg, 'Construction and Initial Operation of the Miamisburg Salt-Gradient Solar Pond', Proceedings of the Silver Jubilee Congress of the International Solar Energy Society, Vol. II, pp. 1003-1009, May 1979, Atlanta, Georgia, U.S.A.

L.J. Wittenberg and M.J. Harris, 'Evaluation of a Large Nonconvective Solar Pond', Proceedings of the Workshop on Solar Energy storage options, Vol.1, pp. 193-202, March 1979, San Antonio, Texas, U.S.A.

J.R. Hull, 'Wind Induced Instability in Salt-Gradient Solar Ponds', Proceedings of the Annual Meeting of American Section of the International Solar Energy Society, Vol.3.1, pp. 371-375, June 1980, Phoenix, Arizona, U.S.A.

L.J. Wittenberg and M.J. Harris, 'Management of a Large, Operational Solar Pond', Proceedings of the 15th Intersociety Energy Conversion Engineering Conference, Vol.2, pp. 1435-1437, August 1980, Seattle, Washington, U.S.A.

D.W. Kuber, 'Solar Ponds in the Region Served by the Tennessee Valley'.

Authority. Proceedings of the 15th Inter-Society Energy Conversion Engineering Conference, Vol.2, pp. 1432-1434, August 1980, Seattle, Washington, USA.

E.B. Nielsen, "Design and Initial Operation of a 400 m<sup>2</sup> Solar Pond," Proceedings of the Annual Meeting of the American Section of the International Solar Energy Society, Vol.3.1, pp. 381-385, June 1980, Phoenix, Arizona, USA.

G.E. Nielsen and J. Kemal, "The 400 m<sup>2</sup> Solar Pond: One Year Operation," Proceedings of the Annual Meeting of the American Section of the International Solar Energy Society, Vol. 1, pp. 758-762, May 1961, Philadelphia, Pennsylvania, USA.

Editorial article, "Nonconvecting Salt-Gradient Solar Pond: A New Energy Technology," Energy Demonstration and Technology, Issue 13, 1981, Office of Power, Chattanooga, Tennessee, USA.

S.M. Patel and C.I. Gupta, "Experimental Solar Pond in a Hot Humid Climate," Sunworld, Vol.5, No.4, pp. 115-118, 1981.

D.D. Weeks and H.C. Bryant, "What Happens When a Solar Pond Boils?" Proceedings of the Annual Meeting of the American Section of the International Solar Energy Society, Vol.4.1, pp. 168-171, May 1981, Philadelphia, Pennsylvania, USA.

International Solar Pond Letters, No.4, January 1961, p. 23, T. Ochs, Editor, Desert Research Institute, Boulder City, Nevada, USA.

M.J. Harris, D.B. Etter, and I.J. Wittenberg, "Observations Regarding Materials and Site Preparation for Salt-Gradient Solar Ponds," Proceedings of the Annual Meeting of the American Section of the International Solar Energy Society, Vol.4.1, pp. 787-790, May 1981, Philadelphia, Pennsylvania, USA.

S. Cha, W.T. Sha, and J.R. Hull, "Design, Construction and Initial Operation of the AL Research Salt-Gradient Solar Pond," ANL-81-55, August 1981, Argonne National Laboratory, Argonne, Illinois, USA.

D.W. Kuberg, "A Review of TVA's Nonconvecting Solar Pond Activities," Proceedings of the Annual Meeting of the American Section of the International Solar Energy Society.

"Energy Society, Vol. 4-1, pp. 777-781, May 1981, Philadelphia, Pennsylvania, USA. GB. Nielsen, 'Salt Transport and Gradient Maintenance in Solar Ponds,' Proceedings of the Annual Meeting of the American Solar Energy Society, Part T, pp. 179-184, 1982, Houston, Texas, USA. J. Kamal and C. E. Nielsen, 'Convective Zone Structure and Zone Boundaries in Solar Ponds,' Proceedings of the Annual Meeting of the American Solar Energy Society, Part I, pp. 191-196, 1982, Houston, Texas, USA. A. R. Coates, R. Fench and S. Schweitzer, 'Solar Pond Construction and Cost Performance Analysis,' USADI-82, XVII Convencion de la Union Panamericana de Asociaciones de Ingenieros, August 1-7, 1982, CEER/UPR, GPO Rico 00936. R. P. Fynn and T. H. Short, 'Solar Ponds: A Basic Manual,' Report No. 106, February 1983, The Ohio State University, Ohio Agricultural Research and Development Center, Wooster, Ohio 44691, USA. G. F. Jones, K. A.

Meyer, and J. C. D. P. Grimmer, 'Design, Construction, and Initial Operation of the Los Alamos National Laboratory Salt-Gradient Solar Pond,' Proceedings of the Annual Meeting of the Solar Energy Division of the American Society of Mechanical Engineers, April 19-21, 1983, Orlando, Florida, USA. D. K. Dixit, B. D. Shiwalka and V. M. Dokras, 'Some Studies on an Experimental Solar Pond,' Proceedings of the International Solar Energy Society Congress, Vol. II, pp. 1-77, January 1978, New Delhi, India. Annual Report Number M-43, June 1, 1980 to May 31, 1982, Brace Research Institute, McGill University, Montreal, Quebec, Canada H9X 1C0. R. P. Beldan and J. F. Lane, 'Experimental Operation of a Small Solar Pond,' Proceedings of the Canadian Solar Energy Society Conference ENERGEX-82, Vol. II, pp. 715-120, August 1982, Regina, Saskatchewan, Canada. B. Nimmo, A. Dabbagh and S. Said, 'Salt-Gradient Solar Ponds,' Sunworld, Vol. 5, No. 4, pp. 113-114, 1981. R. P. Fynn, P. C. Badger, T. H. Short and M. J. Sciarini."

"Monitoring Sodium Chloride Concentrations and Density Profiles in Solar Ponds by Electrical Conductivity and Temperature Measurement," Proceedings of the Annual Meeting of the American Section of the International Solar Energy Society, Vol.3.1, pp. 386-390, June 1980, Phoenix, Arizona, U.S.A.

"Salt Concentration Gradient Solar Ponds - Modeling and Optimization," by Jayadev and J. Henderson, Proceedings of the Silver Jubilee Congress of the International Solar Energy Society, Vol.IK, pp. 1015-1018, May 1979, Atlanta, Georgia, U.S.A.

"Development of Performance Information for Large Scale Solar Pond Applications," by Newell, J. Pande and R. Bochm, (abstract), Proceedings of the Annual Meeting of the American Section of the International Solar Energy Society, Vol.3-1, June 1980, Phoenix, Arizona, U.S.A.

"A One-Dimensional Model for the Dynamic Layer Behavior in a Salt-gradient Solar Pond," by K. A. Meyer, Proceedings of the Annual Meeting of the American Section of the International Solar Energy Society, Vol.4.1, pp. 763-767, May 1981, Philadelphia, Pennsylvania, U.S.A.

"Enhanced Ground Storage for Solar Ponds," by D. Crevier, Proceedings of the Annual Meeting of the American Section of the International Solar Energy Society, Vol.4.1, pp. 736-740, May 1981, Philadelphia, Pennsylvania, U.S.A.

"Solar Ponds in Puerto Rico - A Feasibility Study," by J. B. Davila Acaron, Final Report, April 13, 1981, Center for Energy and Environment Research/University of Puerto Rico, Solar Division, Mayaguez, Puerto Rico 00708, U.S.A.

"Solar Pond Salt Gradient Instability Prediction by Means of a Thermo Hydrodynamic Computer Code," by J. Re Mull, K.V. Bis, Y.S. Cha, H. M. Donanus and W. T. Sha, Proceedings of the Annual Meeting of the American Section of the International Solar Energy Society, Vol.4.1, pp. 812-816, May 1981, Philadelphia, Pennsylvania, U.S.A.

"Solar Pond Research at MIT," by F. Atkinson and D.R.F. Harleman, International Solar Pond Letters, Vol.1, No.1,2, pp. 3-4, 1982.

A. Moshref and D. Crevier, "Electric Power Generation..."

Generation by Solar Funds: Modeling and Optimization, Proceedings of the Annual Meeting of the American Section of the International Solar Energy Society, Part 1, pp. 203-208, 1982, Houston, Texas, U.S.A. A. Duyar and W. Bober, Investigation of Thermal Interactions Between a Non-convective Solar Pond and Earth and Ground Water Below, Proceedings of Condensed Papers of the 5th Miami International Conference on Alternative Energy Sources, p. 503, December 13-15, 1982, Miami Beach, Florida, U.S.A. J.B. Hull, Membrane Stratified Solar Ponds, Proceedings of the Silver Jubilee Congress of the International Solar Energy Society, Vol.11, pp. 1000-1004, May 1979, Atlanta, Georgia, U.S.A. J. R. Hull, Membrane Stratified Solar Ponds, Solar Energy, Vol.25, pp. 317-375, 1980. D. Crevier and A. Moshref, The Floating Solar Pond, Proceedings of the Annual Meeting of the American Section of the International Solar Energy Society, Vol.4.1, pp. 801-805, May 1981, Philadelphia, Pennsylvania, U.S.A. E. I. H. Lin, A Saltless Solar Pond, Proceedings of the Annual Meeting of the American Solar Energy Society, Part 1, pp. 215-219, 1982, Houston, Texas, U.S.A. M.S. E. Abdo, A New Chemically Stratified Solar Pond, Proceedings of the Condensed Papers of the 5th Miami International Conference on Alternative Energy Sources, pp. 501-502, December 13-15, 1982, Miami Beach, Florida, U.S.A. J. A. Bonnet, Jr., J.T. Pytlinski and K. G. Soderstrom, Solar Energy Storage for Cooling Systems in the Caribbean, Proceedings of the International Workshop on Solar Energy Storage, March 1982, Jeddah, Saudi Arabia. A. Rabl and C. E. Nielsen, Solar Ponds for Space Heating, pp. 608-616, Chemitech, October 1975. A. Rabl and C. E. Nielsen, Solar Ponds for Space Heating, Solar Energy, Vol.17, pp. 1-12, 1975. C. E. Nielsen, Experience with a Prototype Solar Pond for Space Heating, Proceedings of the International Solar Energy Society Conference, Vol.5, pp. 169-182, August 1976, Winnipeg, Canada.

n. 73. m. 78. 6. 7. 78. 79. 80. an. a3. G. 0M.

Leboeuf, Soler Ponts. "Applied to District Heating and Cooling," Proceedings of the Annual Meeting of American Section of the International Solar Energy Society, Vol. 1, pp. 772-776, May 1981, Philadelphia, Pennsylvania, USA. E. I. H. Lin and K. L. French, "Solar Pond Regional Applicability Study: Summary of Results," Proceedings of the Annual Meeting of the American Solar Energy Society, Part I, pp. 209-214, 1982, Houston, Texas, USA. "Annual Report of 1982," Solar Division, Center for Energy and Environment Research, University of Puerto Rico, Mayaguez, Puerto Rico 00708. D. Crevier, "An Experimental Solar Pond for Industrial Process Heat," Proceedings of the Canadian Solar Energy Society Conference ENEREX-82, Vol-II, pp. 05-714, August 1982, Regina, Saskatchewan, Canada. T. H. N. Short, W. I. Roller and P. Y. C. Badger, "A Solar Pond for Heating Greenhouses and Rural Residences - A Preliminary Report," Proceedings of the Solar Energy Workshop on Foods, Fuel, pp. 41-50, April 5-6, 1976, Tucson, Arizona, USA. Z. He Short, P. C. Badger and W. L. Roller, "The Development and Demonstration of a Solar Pond for Heating Greenhouses," Proceedings of the Silver Jubilee Congress of the International Solar Energy Society, vol.11, pp. 1021-1025, May 1979, Atlanta, Georgia, USA. R. P. Pynn, T. H. Short and S. W. Shah, "The Practical Operation and Maintenance of a Solar Pond for Greenhouse Heating," Proceedings of the Annual Meeting of the American Society of Agricultural Engineers/Energy Symposium, September 30-October 1, 1980, Kansas City, Missouri, USA. M. Collares Pereira, A. Joyce and L. Valle, "Salt-Gradient Solar Pond for Greenhouse Heating Applications," Proceedings of the Annual Meeting of the American Solar Energy Society, Part I, pp. 221-230, 1982, Houston, Texas, USA. H. Tabor, "Solar Ponds," Electronics and Power, pp. 296-299, September 1964. A. B. Difrawi, B. Yudow and R. H. Grotheer, "A New Desalination: The Solar Evaporator and Condenser System (SEACS)," Proceedings of the Annual Meeting of American Section of



"The International Solar Energy Society, Vol. 4.1, pp. 791-795, May 1981, Philadelphia, Pennsylvania, U.S. G. Lesino, L. Saravia, J. Hangussi and R. Caso, 'Operation of 2.4002 Sodium Sulphate Solar Pond in Salta, Argentina,' International Solar Pond Letters, Vol.1, No.1, pp. 42-13, November 1982. W. Tabor, 'Solar Ponds: Large-Area Solar Collectors for Power Production,' Solar Energy, Vol. S, No. D, pp. 189-194, 1363.

24. 85. 87. 89. 90. 91. 92. 93. 94. 95. 96.

G. Assaf, B. Doran, Z. Vsinhaiser, Y. Brockel, H. Kiershman, A. Katz and S. Sariq, 'Leeds 82: Joint Venture for Electricity Production,' Proceedings of the Silver Jubilee Congress of the International Solar Energy Society, Vol. II, pp. 1020, May 1979, Atlanta, Georgia.

W. Tabor, 'Power from Scientific Research,' F.L.Y. Bronicks, Lowes and Hoes, No.4, pp. 121-122, 1982.

Worldwide, Vol.5, J.D. Wright, 'Setrco Rankine Cycle Coupled with Direct-Contact Heat Exchanger for an Organic Solar Pond,' Proceedings of the Fourth Annual Conference of the American Society of Mechanical Engineers, pp. 26-25, 1982, Albuquerque, New Mexico.

B. Osho and others, 'Operation of a Saturated  $\text{Na}_2\text{SO}_4 = 280$  Solar Pond,' Proceedings of the International Solar Energy Society, Vol. 7, pp. Suck, May 1979, Atlanta, Georgia.

O. Ochs, 'Operation of a Large-Scale Solar Pond,' Proceedings of the 15th Intersociety Energy Conversion Engineering Conference, Vol. 2, pp. Last, August 1980, Seattle, Washington, U.S.A.

G. D. Menta, 'Self-Correction in Solar Ponds,' NASA Tech Brief, NPC-15439, Jet Propulsion Laboratory, Pasadena, California.

B.S. Wilkins, E. van der Meer and others, 'Evaluation of the Performance of a Solar Pond,' Proceedings of the 16th Intersociety Energy Conversion Engineering Conference, Vol. Pond, pp. Thakur, November 1982.

G. Assaf, 'The Dead Sea: A Natural Solar Pond,' Solar Energy, Vol.18, pp. 293-296.

R. L. French and I. Mestias, 'Solar Lake,' Solar Energy, Vol. 1, pp. 1-10."

"Caiiin Sua Fewer Pond Project," Proceedings of the 15th Intersocietal Conversion Engineering Conference, Vol. 2, August 1980, Seattle, Washington. P. Bolon, "Power from the Science," pp. 84-86, April. © Fonds, Popular.

7. 8. Winsberg, "Solar Perspectives: Israel, Solar Pond Innovator," Sunworld, Vol. 5, No. 4, pp. 123-125, 1981.

California Energy Commission, "Solar Salt Pond - Electric Power Generation Potential of the Salton Sea," Executive Summary, P700-81-014, August 1981, Sacramento, California, U.S.A.

California Energy Commission, "Solar Salt Pond Generating Facility: A Feasibility Study for California," Consultant Report, Vol. I, P700-61-015, August 1981, Sacramento, California, U.S.A.