

CEER-S-185

CEER-S-185

SOLAR PONDS: RESEARCH, APPLICATIONS AND DEVELOPMENT

sh One,

JuT. PYTLINSKE

a

CENTER FOR ENERGY AND ENVIRONMENT RESEARCH

ec ogo

---Page Break---

Proceedings of the Sth Miami International Conference on Alternative
Energy Sources, Decenber 13-15, 1962, Miami Beach, Florida, U.S.A.

SOLAR PONDS: RESEARCH, APPLICATIONS AND DEVELOPMENT

J. 7. Pytlinski

Center for Energy and Environment Research

University of Puerto Rico.

Mayaguez, Puerto Rico 00708, U.S.2.

ABSTRACT

A description of the status of solar pond research applications and development is provided. Shallow ponds, gel ponds, saturated ponds and salt-gradient ponds are discussed, and many existing ponds in various countries are described. Ongoing field and laboratory work associated with Solar ponds is discussed in relation to residential, commercial, industrial and agricultural applications of pond generated heat. Other present or future applications of salt-gradient ponds such as electricity generation, irrigation water pumping and the more recent absorption and dehumidification cooling are presented. Pond construction and operation, including costs, are discussed and schematic diagrams are used to illustrate textual explanations. An extensive list of references treating theoretical and practical aspects of pond research, applications and development is also provided.

1, nwrropuerroN

Fossil fuels do not exist as a natural resource in many countries, and these countries are forced to rely on imported oil or coal or nuclear technology in spite of the continuous balance of payment problems most of them face. Solar ponds, during the past few years, have received special attention as one of the

solar technologies which have the potential to be economically and technically competitive with energy conversion technologies which use fossil fuels (see Fig. 1). Solar ponds could, therefore, improve the energy situation of some countries.

In addition to their low cost, some solar ponds such as the salt-gradient type offer built-in storage. This makes them independent of the intermittence of solar radiation. Yet, it is the shallow solar ponds, first introduced in the mid-seventies by Lawrence Livermore Laboratory of California, that appear to be the most developed and market ready as illustrated by several publications on the theoretical and practical aspects of shallow solar pond use, including applications for generating industrial process heat [1-6]. The construction methodology of shallow ponds [7] and their internal performance testing have been described in detail [8,9]. In one innovative concept that has

Fig.1. Solar Pond activi

been tested a shallow solar pond's performance was enhanced by Placing a mirror on its north side [10]. In a theoretical study on pond sizing and design optimization, the simulation and modeling of a shallow solar pond was performed by using the TRNSYS program [11].

Although the economics seem to be in favor of shallow solar Ponds [2,12], the demonstration program for them established since applications are restricted mainly to users in the south and the Southwest of the U.S. + Even this research shading solar technology does not contribute much toward developing the production of solar equipment and the commercialization of solar technology. However, a renewed interest in shallow solar ponds seems to be taking place, particularly for applications in the Caribbean.

The concept of collecting and storing solar energy by means of salt-gradient ponds, also known as nonconvecting solar ponds,

was derived from research on natural salt lakes [13]. Salt-gradient solar ponds reached the application level in recent years, although some aspects of their construction, operation and maintenance are still in the research and development stage. Some

of the most important work on salt-gradient ponds was done in Israel [14,15]; the concept of ponds generating process heat was introduced there in the mid-fifties. The continuation of this work in Israel and elsewhere resulted in several review papers

and reports that treat the current status of technology, the

cost, and the physical and thermal phenomena which occur in salt gradient solar ponds [16-21]. The physics of salt-gradient

solar ponds is the subject of theoretical and experimental studies (22,23). Detailed descriptions of pond systems, the state-of-the-art and knowledge of material selection, site preparation and pond construction techniques are available for medium and large ponds (26-48) and small laboratory ponds [49-52], because of the

---Page Break---

Work of many researchers, Experimental aspects of salt-gradient Pond instrumentation have been investigated [53] and theoretical

studies of modeling and simulation have been performed [54-62].

In addition, several innovative pond concepts have been proposed (63-68).

Salt-gradient pond applications that have been studied and/or implemented include absorption and dehumidification cooling [68], commercial and residential space heating [69-71], district heating and cooling [72,73], low temperature (between 50°C and 70°C) industrial water heating (74), agricultural process heat production for grain drying [75], and greenhouse heating [76-79].

Other applications include using salt-gradient solar ponds for salt production enhancement [50-82] and electricity generation [3-87]. The pumping of irrigation water is another area in which salt-gradient solar ponds can be used effectively.

Some laboratory investigations have also been done on saturated salt ponds [88-91] and wet ponds [92,93]. Both of these techniques of solar heat collection and storage are still in the research stage. They do not attract the interest and financial support that shallow solar ponds and salt-gradient ponds do.

The development work on solar ponds is concentrated primarily for the use of large size (up to 50 MK.) nodular salt-gradient ponds for electricity generation [94-99]. The economics of scale, simplicity of construction and technological readiness make such stand-alone plants especially attractive in areas where natural salt lakes already exist and can be converted into production ponds with a minimum of technical effort and cost. Selected research, applications and development efforts in the field of solar ponds are described below to provide a comprehensive description of the present status of solar pond work.

RESEARCH PONDS:

In the United States, research activities on shallow solar ponds, salt-gradient ponds, salt-saturated solar ponds and gel ponds are being conducted at several locations.

A cross-sectional view of a shallow solar pond is shown in Figure 2. A typical shallow solar pond resembles a thermally insulated, plastic water bag partially filled with water. The bag may have a black bottom for absorbing solar radiation, and a clear top to prevent evaporation and assure the greenhouse effect. The most recent design calls for a Slack Hypalon or polyvinyl chloride (PVC) water bag with a clear fiberglass cover supported by concrete curbs and metal struts. The hot water from the pond is drained down to a storage tank once or several times per day depending on the system requirements.

The first shallow solar pond system, designed and operated by Lawrence Livermore Laboratory of California, was built in 1975 near Grant, New Mexico [2,3,12]. The pond system consisted of two nodules of 220 sq. m. (2400 sq. ft.) each, which contained 10cm. (3.9 in.) of water. This prototype system was built at a uranium mining and milling plant of Sohio Petroleum Company. The

---Page Break---

Fig.2. Cross-Sectional View of Shallow Solar Pond Nodule.

shallow pond modules operated on a stand-alone basis without being interfaced with the plant hot water system. Each pond nodule heated 25 tons of water per day to about 54°C (130°F) in the summer and to about 35°C (95°F) in the winter. A twelve-month performance survey of the system operation indicated that the solar ponds operated with an annual average energy collection efficiency of about 45 percent and collected close to 9.37×10^7 Joules/m²-day (825 Btu/ft²-day) .

Figure 3 shows a cross-sectional view of a typical salt-gradient solar pond. Salt-gradient ponds are large pools of water open to the environment and filled out with salty water in such a way so that the liquid top layer (upper convective zone) has a 1-4 percent salt content while the bottom layer (lower convective zone) has a content as high as 23-27 percent salt. In the pro-

cess of being exposed to solar radiation, the denser bottom layer is heated to a much higher temperature than the surface layer. The heat accumulated in the lower convective zone is "trapped due to the low salinity nonconvective zone, which separates the high density brine at the pond bottom from the upper convective zone. In this way, the use of a salt pond eliminates the separate thermal storage that is normally required in many solar installations.

A salt-gradient solar pond of 200 sq. m. (2152 sq. ft.) area, a depth of 2.5 m. (8.2 ft.), and 45° tapered walls has been operating since 1975 at Ohio State University in Columbus, Ohio. In 1976 this pond reached a maximum temperature of 62°C (144°F). Experimental and theoretical research has been done in relation to some of the physical phenomena occurring in the pond, and on the pond operation and maintenance [26]. A second salt-Gradient solar pond of 408 sq. m. (4390 sq. ft.) area was installed at Ohio State University in 1979 [35,36]. This pond is 4.5m. (14.8 ft.) deep at the center and 1.5m. (4.9 ft.) deep close to the walls. The walls of the pond are vertical and are made out of wood planks

---Page Break---

Fig.3. Cross-Sectional View of Salt-Gradient

Solar Pond

thermally insulated by styrofoam and urethane. The pond is extensively instrumented to yield data on solar input, heat gain by the pond, heat loss to the ground, and heat conducted upward through the gradient layer.

Another pond of this type having a 156 sq. m. (1678 sq. ft.) area, a depth of 3.6 m. (11.8 ft.), and vertical wooden walls has been operating successfully on an experimental basis since 1977. Providing heat for a greenhouse of the Ohio Agricultural Research and Development Center in Wooster, Ohio [76-78]. Although this pond provides heat for a greenhouse, its main purpose is to serve as a research base where various aspects of the pond operation and heat extraction are studied.

A research salt-gradient solar pond of 177 sq. m. (1901 sq.ft) with a depth of 2.5 meters and walls tapered at 34° was installed at New Mexico University in Albuquerque, New Mexico, in 1975 [27]. In the second year of the pond's operation, the storage layer reached a temperature of 93°C (199°F). Studies on the operational parameters, the criteria for materials to be used, the cost and performance data, and the physical behavior of the pond exposed to

the environment are being performed. Proof of the technical feasibility of heat extraction was obtained by the successful operation of the pond year around and by the extraction of an amount of heat adequate for heating a 185 sq.m. (1990 sq. ft.) house located in the Southwest region. The same pond reached a boiling temperature of 108°C (226°F) during the summer of 1980.

Work on the construction of a salt-gradient solar pond was also initiated in 1971 by the University of Utah, in Utah. The research pond of 850 sq. m. (9146 sq. ft.) and a depth of 1.1m. (3.6 ft.) was built during 1979 on the southwest side of Great Salt Lake [34]. The maximum temperature reached by the pond was 55°C (131°F), which was reached after about six weeks of pond operation. At the beginning of 1980, however, a very strong wind of approximately 35.8 m/s (80 mph) destroyed the salt gradient and emptied almost one-fourth of the pond into the dike surrounding

---Page Break---

it. The pond was built to investigate the physical processes that occur in a salt-gradient pond and to develop an experimental base for computer modeling of various design schemes for electrical power generation using large size production ponds.

A salt-gradient pond has been operating at the Argonne National Laboratory in Illinois since 1980 [25,42]. The pond has an area of 1075 sq.m. (11567 sq. ft.) and its sides are tapered at an angle of 45° to a depth of 2.7 m. (9 ft.). At the end of 1981 the pond reached a temperature of 63°C (145°F). The major objective of building this pond was to have a research base to assess the salt-gradient pond as a heat collection and storage system for various types of applications, and to set up an operation for a future U.S. solar ponds program. This pond is very well instrumented and has already provided data that can be used to guide future builders of salt-gradient solar pond systems.

The Tennessee Valley Authority (TVA) installed a 4047 sq. m. (43543 sq. ft.) pond in Tennessee in 1981 [34,37,43]. This pond works in conjunction with a 2484 sq. m. (26724 sq. ft.) evaporation pond which is 1.2 m. (4 ft.) deep and has walls tapered at 34°. The TVA pond is extensively instrumented and will provide important information on pond reliability, operating costs and energy collection efficiency, thus making a significant contribution toward the commercialization of pond technology. This pond is available to outside users as a testing site.

One of the most recently installed ponds is a 234 sq. m. (2518 aq. ft.) salt-gradient solar pond that was built in June, 1982 at Los Alamos National Laboratory. in Albuquerque, New Mexico [48]. The pond depth is 3.6m. (11.8 ft.) and the walls are ver~
?Two liners were used for the pond canstruction; the first one is 1.2 mm. (45 mil) thick main hypalon liner and the second fone is 0.5 mm. (20 mil) thick polyvinyl chloride (PVC) liner. The second liner was laid over 15 cm. (6 in.) of sand spread uniformly over the pond bottom. Also a'6.4 cm. (2.5 in.) thick layer of sand was spread between the liners. The walls of the pond ere thermally insulated with 7.6 cm. (3 in.) thick polyurethane foam insulation.

To attain a brine salinity of 21 percent at the pond bottom, about 127 tons of 98 percent pure, granular NaCl were used. The salt was dissolved by using a local fire hydrant; further salt mixing was done by using a couple of pumps of about 400 liters/min. (105 gal./nin.) capacity cach. The salt gradient was established by lowering the diffuser to a depth of 1.2 m. (3.9 ft.) from the bottom which corresponded to the chosen thickness of the lower convective zone. With the diffuser at that position, 5-1 em. (2 in.) of fresh water was added. Tho diffuser was then moved up

10.2 cm. (4 in.), and another 5.1 cm. (2 in.) of fresh water was diffused into the pond. This procedure was repeated several times until the pond's depth was about 2.4 m. (7.8 ft.). At this point another 10 cm. (3.9 in.) of fresh water was added at the top of the pond. In this way the pond reached the chosen parameters of a 1.2 m (3.9 ft.) thick lower convective zone, a 2 m. (3.9 ft.) thick nonconvective zone and a 10 cm thick upper convective zone. One month after the salt g

---Page Break---

had been established, the salinity and temperature of the pond reached 21 percent and 50°C (22°F) respectively. The heating rate of the pond at that time was about 1.2 °C/day (2.8°F/day).

The pond is instrumented with an underwater Eppley pyrano-

meter, two 100 Ohm platinum resistance thermometers (RFD)? « glat=
inum point conductivity probe, and an induction salinometer:

Four leak detection sensors are imbedded in the sand at the pond
Bottom. Twelve vinyl jacketed copper-constantine thermocouples,
in groups of three, are installed in the walls and six are ineeal~
Jed in the pond bottom to determine heat losses from the pond, "A
weather station is employed in conjunction with the other? pond
ipstrumentation. The station consists of a horizontally mounted
Eppley Model 8-48 pyranometer, a wind speed and direction measus=
ing anemometer and a thermally shielded ambient temperature com,
gor, Data from about 80 channels is processed by a Hewlett
Packard Model 87 desk-top computer. ?The pond is mainly used to
study the boundary layer structure at the interface between the
convecting and nonconvecting zones, interactions between the
zones, éurnal heating effect, and wind-induced turbulances

The Los Alamos salt-gradient pond works in conjunction with
gh evaporation pond of 257 2g. m. (2765 sq. ft.) anda depth oF
2,4 Bs (4:6 ft). All the walls of this pond are vertical except
the west wall which is sloped at 2 16° angle to create a ramp for
salt removal and pond maintenance.

The Center for Energy and Environment Research (CEER) of the University of Puerto Rico in Mayaguez is currently installing a research pond of 39 sq. m. (415 sq. ft.) with a depth of 0.921 m, (3-4 ft), and vertical walls [74]. This pond will work in conjunction with an evaporation pond of the same area but of half the depth. The research pond will be well instrumented to study the physics and engineering aspects of pond operations, maintenance and control. Some computer simulation work will also be performed. This research pond will be a pilot system for a one-half acre production pond to be used to generate process heat for a food processing company in Puerto Rico,

Salt-gradient solar pond research is also being done at the Massachusetts Institute of Technology, where the work is primarily directed toward the development of a numerical model. A time-dependent vertical temperature and salinity profile in salt ponds. Wind mixing is also being studied by means of a one-dimensional numerical model [70].

Laboratory research work on salt saturated ponds has been done by the Desert Research Institute in Nevada using borax as salt, and by Inter Technology Company in Virginia using diatom phosphate as salt [90]. In the former case, the area of the pond

built in 1979 was 10 sq. m. (108 sq. ft.) with a depth of 1 m (3.28 ft.); in the latter case, the pond area was 0.37 sq.m (3.7 sq. ft.) with a depth of 0.91 m. (3.0 ft.)., the maximum temperature reached by the Desert Research Institute pond was 47°C (117°F) «Reduced maintenance and lower fresh water usage are some of the advantages of using saturated ponds. The saturated ponds tested had the property of being self-established and maintained a stable density profile during the summer

---Page Break---

and/or extraction processes:
much more

A saturated pond may, however, require more energy than an unsaturated pond which could be a financial disadvantage. | Some studies were done on the chemical and biological contamination of saturated ponds, thermal behavior, and operation and maintenance problems. ?The research performed so far, however, has been restricted to laboratory size ponds and the available data does not cover the operating conditions of large

size production ponds.

Experiments using disodium phosphate in a saturated pond in a laboratory environment were also conducted in 1985 by the Technology Company under a contract with Jet Poonacios Technology (91).

Research on gel ponds has been conducted at the University of New Mexico since 1981 using an experimental pond of 18:7 aq) (201 sq. ft.) [92,93]. The effect of the polymer gel thickness upon the performance of the gel pond is being studied. It was found that the surface heat losses from a pond containing 25 cm, (9.9 in.) layer of gel over about 1.22 m. (4 ft.) of low salinity water were approximately half those from a salt-gradient pond with a 1m. (3.28 ft.) stratified salt zone under the same conditions. For the optimum operation of a gel pond, research indicates that @ 15 cm. (6 in.) gel thickness is adequate. The gel chemical formula, which is the subject of a patent, is not available. The present estimate is that the polymer gel will last three years in a pond under natural solar exposure. Heat is extracted from a gel pond in the same way as it is from salt-tolerant and salt saturated ponds; that is, by using internal or ex-

ternal heat exchangers.

In Israel, research on salt-gradient solar ponds has been underway since 1954, the year the concept was conceived there (Bd). After a nine year pause work in this area was revived again in 1975. | Because of Israel's almost total reliance on imported fossil fuels, salt-gradient solar pond research is oriented primarily toward electricity generation. In 1977 a 1500 sq.m.

(16140 sq. ft.) pond was made operational in Yavne by Ormat Turbine Ltd... The pond reached a temperature of 90°C (194°F) the same year. The pond generated electric power output in the

range of 6 kWe, using an organic cycle system equipped with a turbine as the prime mover. This closed loop self-contained system employed chlorobenzene as the working fluid. Water at 29°C (84°F) from the surface of the pond was used to cool the condenser.

A larger pond of 7500 sq. m. (80700 sq. ft.) area and a

depth of 2.5m. (8 ft.) was installed in Fin Bokek by the Dead Sea in 1976 [94,96,97]. when the temperature of the storage Layer reached 80°C (176°F) the pond started to produce electricity by using a 6 kW, capacity Ormat system. A larger Ormat system of 300 kW capacity was installed in 1979 and the pond delivered 145 kW of electricity the same year operating at 93°-100°C (199-212°F) evaporator temperature and at about 30°C (86°F) condenser temperature. Desalination activities are also planned here as secondary research efforts. The main thrust of the Israeli research effort is toward obtaining a complete understanding of salt-gradient pond technology for electric power

---Page Break---

Production in order to commercialize such systems for domestic and export markets as "turn key" plants,

in Canada, the first research salt-gradient solar pond was installed in 1980 at the Brace Research Institute in Montreal (BRI).

A gross-sectional view of this pond is shown in Figure 4. the same year an experimental pond was implemented by the National Research Council of Canada. the pond area is 17 sq.m. (189 sq. ft) and the depth is 0.96 m. (2.62 ft)- The walls of the pond are vertical. An external, brine-to-air heat exchanger made out of copper tubing is being used. The maximum temperature reached by the storage layer in 1981 was about 50°C (120°F). The general objectives of installing this research pond were to obtain first hand practical knowledge of methods and problems associated with construction, operation, and maintenance of a solar pond in preparation for the design and operation of a larger protection pond. The National Research Council of Canada finances this research for developing equipment and procedures for automating the operation and maintenance of a salt-gradient ponds

In Australia, the first salt-gradient pond was built in Aspendale in 1964. This pond had an area of 106 sq.m. (1140 sq. ft) and a depth of 0.86 m. (2.82 ft.). Locally available clay cul was used to seal the bottom and the walls of the ponds. Limestone was used. The storage layer reached a maximum temperature of 63°C (145°F) in the summer of the second year of operations. The same year the pond developed a leak which contributed to the discontinuation of the project. The results of this research

which was oriented toward studying the pond's thermal efficiency, the sealing techniques and the control of the salinity gradient? were published in the form of a report [26]. The second salt gradient solar pond was built by the University of Moncton in 1981 for research purposes [40]. The pond area is 340 sq.m. (2582 sq. ft.). Research is focused on the stability of the salt gradient, the methodology of pond filling and the evaluation of the performance of thermal phenomena. In 1961 a 2000 sq.m (21820 sq. ft.) Salt-gradient solar pond was built in Alice Springs.

Fig. 4. Cross-Sectional view of salt-gradient solar pond.

Research Pond

---Page Break---

3p Saudi Arabia, a research pond of 4 sq.m. (45 sq. ft.) and
SudgrPeh of 2:3 m. (7.5 ft.) was beile in 290) by the Research Insti>
TEES Of the University of Petroleun and Minerals in Dhahran [52],
This research pond is being used to gain operating experience ard
to design proper instrumentation for s ruture large produceion
pond. | The activities are focused on computer simelation of send
behavior and on gaining experience in deigning and balidingrenct=
gradient solar ponds by employiyy indigenous labor and vecheianey

In-India, a salt-gradiont sols: ond oz 100 sç.m.(1075 sq. ft.)
god a depth of 2.25 m. (7.4 £2.) was bail in 1980 by Tove Enerey
Research Institute in Pond:cherty [35]. The pond hes vertical
walls and works in conjunction with i evaporation pond of \$0 sq.m.
(538 sq. ft.) area and a depth of 0.7 =. () ft.3. Phe mexinun
temperature reached by the pond tho sain veer was 10°C UisbeP),
?The pond is instrumented to provide resesrch results on thermal
Performance and the behavaos of whe stratification layers Exper=
dence was gained about which locelly svailalle materisis ean be
used to build @ pond and about pond construction and operacion?
costs in India?s rural envizunoent

3. APPLICATION ACTIVITIES

The most immediate applications of solar ponds seem to be

for space heating and for water heating/reheating for residential,

commercial, industrial and agricultural uses where the temper-

ature requirement is in the region of 49°C to 66°C (120° to 150°),

A schematic diagram of a possible stratified solar pond system

is shown in Figure 5. In tropical climates such as the Caribbean,

salt-gradient ponds may be used in the future for dehumidification

cooling as proposed by Bonnet et al. [10].

Fig.5.

Solar Fond £1

qo

---Page Break---

In the United States in March, 1983 a shallow solar pond system was installed to supply 2,000,000 liters (528,401 gal.) of hot water per day to two army barracks and the laundry at Fort Benning in Georgia [19]. A total of 89 modules having an area of 25,000 sq. m. (269,000 sq. ft.) were built. Each module contains two water bags made of industrial grade 9.7 mm. (35 mil.) thick Hypalon. A fiberglass cover over the water bags assures the greenhouse effect. After the system's installation, the water bags were sterilized on site by rinsing them twice with Clorox in a four-hour period. An above ground, 1,892,500 liter (500,000 gal.) capacity steel tank is used for hot water storage. The system is located 1402-1463 m. (4609-4800 ft.) from the end use and the hot water is distributed by 15 mm. (1/2 in.) diameter PVC pipes. The installed system cost was \$4,110,000 with a construction cost of \$4,000,000 and a decontamination cost of \$110,000 which gives a total cost of \$164/sq. m. (\$15.28/sq. ft.).

A shallow solar pond of 22 sq. m. (240 sq. ft.) and a depth of 2.54 cm. (1 in.) was installed in January 1903 on the roof of a high school in Mayaguez, Puerto Rico, to collect daily 40 liters (150 gal.) of hot water at the temperature of 60°C (140°F) to the school cafeteria [74]. Another shallow solar pond of 40 sq.m. (430 sq. ft.) area and a depth of 7.6 cm, (3 in.) is planned to be built to heat water for showers at the swimming pool facility at the Mayaguez Campus of the University of Puerto Rico. The project specifications call for heating 3028 liters (800 gal.) of water to a temperature of 43°C (100°F) daily. The solar pond system could reduce the electricity consumption of the electric water heater by 75 percent. A schematic diagram of a typical shallow solar pond system is shown in Figure 6.

A production salt-gradient solar pond of 2044 sq.m. (21993 sq. ft.) was built in 1978 by the city of Miamisburg, Ohio, to supply heat to an outdoor swimming pool in the summer and to recreational building in the winter [30,31,33,41]. The pond

depth was 2.0 m. (10 ft.) and the walls were tapered at an angle of 45°. Polymer-coated polyester liner XR-S 0.7 m, (35 mil) thick and sodium chloride salt were used. The energy storage layer had a thickness of 1.75 m. (5.7 ft.) and contained brine of 28.5 percent concentration. The temperature required at the end use was 25°C (77°F). The maximum temperature reached by the storage layer of the pond was 65°C (149°F) during the summer of 1979. The pond was equipped with a heat exchanger made out of copper tubing of 2.54 cm. (1 in.) diameter which was placed at the bottom of the pond. The effective surface area of the heat exchanger was 180 sq. m. (1937 sq. ft.). The cost of the pond construction was \$35/sq. m. (\$3.26/sq. ft.), excluding the land cost. After a successful initial operation of two years, this Pond developed a leak in the liner in 1980 and had to be rebuilt.

In Canada, a production salt-gradient solar pond of 700 sq.m. (7532 sq. ft.) was built in 1981 in Quebec by the Contract Research Company [75]. The pond is 3m. (10 ft.) deep and has walls tapered at an angle of 5°. During 1981 the pond reached a maximum temperature of about 53°C (127°F). The pond brine-to-air heat exchanger made out of copper tubing with aluminum fins is located outside the pond. The frontal area of the heat exchanger is 2.3 sq. m. (25 sq. ft.). The heat extraction rate was over

n

---Page Break---

Fig.6. Schematic Diagram of Shallow Solar Pond System

100 kilowatts (3.4×10^6 stu/nr) during the f211 of 1981. The construction cost of this pond was below \$50/sg. m. (\$4-6/sq. ft.), excluding the land cost.

In Portugal, a salt-gradient solar pond was built in Lisbon to heat a greenhouse complex belonging to the Portuguese Ministry of Agriculture [79]. The pond has an area of 1024 sq. m (1018 sq. ft.), a depth of 3.60 m. (11.8 ft.) and walls sloped at a 45° angle. The pond uses 1 m. (140 mil.) thick hypalon liners and sodium chloride as salt. A heat exchanger, used to extract heat from the pond, consists of four sections, 2.4 m. x 5.0m, (7.9 ft. x 16.4 ft.) each, made out of galvanized 2.54 cm (1 in.) O.D. iron pipe. The heat exchanger was designed for an expected peak energy extraction rate of 50 kW. A diffuser that is used for maintaining the salinity gradient consists of ϕ galvanized iron tube of 7.6 cm. (3 in.) O.D. welded to a 1.2 m x 1.2m. (3.9 ft. x 3.9 ft.) plate attached to another plate of the same dimension in such a way as to form 2 space of 1.6 cm. (0.6 in.) between both plates. The pond is extensively instrumented with thermocouples, salt solution and soil conductivity probes, underwater and surface pyranometers and wind measuring instrumentation. R16 sqe Mm

(172 sq. ft.) evaporation pond was built as part of the overall salt-gradient pond system.

In Argentina, a 400 sq. m. (4304 sq. ft.) salt-gradient solar Pond was built in 1982 in Salta to purify sodium sulphate salt by using a natural evaporation process [42]. The pond has vertical wells, a depth of 2.4m. (7.9 ft.) and a solution depth of 1-5 m (4.9 ft.). The pond was instrumented by placing several thermocouples in the solution at different depths at three locations across the pond. To detect leaks an electric wire mesh was formed by two layers of wire under the pond. This wire mesh short-circuited, because of water condensing under the pond, and could not

be used to detect leaks. A layer of clay was used to smooth out the pond walls, and 10 cm. (3.3/in.) of sand was put on the pond bottom before installing two layers of black polyethylene, each 0.25 mm. (10 mil.) thick. The pond was filled with 50 cm³ (1.75 ft³) of water, and then 250 tons of mineral salt to be purified were thrown into the pond. To establish, and later control the severe gradient a diffuser consisting of two metal plates, separated by 20.25 cm. (8 in.) space and shaped as a half disk 45 cm. (17.7 in.) in diameter, was used. To establish the salt gradient the diffuser injected 2.5 cm. (1 in.) of fresh water several times, moving up 5 cm. (2 in.) each time. The water velocity was about

2 cm/sec. (0.78 ft/sec.). About 10 kg, (22 lbs) of copper sulphate was added to the pond to eliminate algae growth. After twenty days the pond solution was very clear again. After forty days the pond bottom reached a temperature of 40°C (104°F). and a temperature density gradient of 2.32 g/cm³ at the bottom and 1.05 g/cm³ at the surface was established. The water evaporation rate from the pond has been 3 to 5 mm. (0.12 to 0.2 in.) per day. The pond produces 0.5 tons of industrial grade sodium sulphate salt every three days.

4, DEVELOPMENT WoRK

The development work at present is taking place mostly in Gountries where rosserch and application activities have already gained wonentum. As a natural excension of these activities, the development work is toocused on stand-alone planes 29 produce large amounts of hoe water, heat and/or clestricity, on selection gf materials and components to assure durobility and velisbility, and on automation of operation and mainteneacs.. Twe cypical Gevelopment projects, one taking place in eracl enc one in the United States, can be mentioned as the nost advanced.

In Israel the development plan of salt-gradient pond technology calls for, in the first stage, the use of solar pond power plants interconnected to the power grid with peaking plants to operate between 750 and 1250 hours per year. It is expected that by 1990 solar pond electric power plants can be built economically to supply intermediate loads. Finally, it is assumed that by 1993 large-scale pond-lakes can be built to supply the base load. By following this development plan Israel could be ready by the end of this century to operate a Dead Sea pond of about 600 sq. km (190 sq. mi.) which may supply up to 2000 MW of electric power by using a series of modular units of 30 MW, each [94,96/97]

In the United States the Salton Sea Pond Project in Southern California, sponsored by Southern California Edison and the State of California, has been highly publicized [95,38,99]. The concept of this project is presented in Figure 7. The project consists of three phases. Phase 1, the concept and feasibility study, was completed in 1981. Phase 2 calls for designing a con-

structing and testing a 5-MW prototype power plant by 1968,

Satisfactory results could then lead to the construction of a

600-MW plant comprising 20 to 50 commercial modules. Electric

power generation from the low-temperature heat provided by

the salt-gradient pond can be accomplished by using an organic

fluid turbogenerator as shown in Figure 5. The five-stage

a3

---Page Break---

shapes vary from circular, for small size salt-gradient research ponds, to rectangular (east-west oriented) or square, for large Ponds. The latter are usually built in modular units to provide the required thermal/electrical capacity. Before building a pond, 46-9 B. (20-30 ft.) core sampling should be made to test the soil composition and permeability. The thermal conductivity of the soil around the pond can vary between 1 and 2.5 watts/m*c. It is recommended to test the soil thermal conductivity and to determine the existence of movable underground water.

Borax, disodium phosphate and sodium sulphate have been experimented with and studied as possible salts for saturated ponds. Sodium-chloride is the salt usually used in salt-gradient Ponds, although magnesium-chloride is being used in Israel since it is commonly available there. Refined salt of 95 percent or more purity should be used. The type of salt is of significance (NaCl, MgCl, CaCl, etc.) because of the brine transmissivity factor, and because the salt solubility changes with temperature. About 45 kg. (100 lbs.) of salt per approximately 0-1 sq.m.

(1 sq. ft.) of pond area are needed to obtain the right salt concentration in the lower convective zone. Out of this 0-45-0-90 kg (2-2 lbs.) per 0.1 sq. m. (-1 sq. ft.) per year will diffuse upward.

Diffusers are used to establish the vertical salinity gradient. This is done by lowering the diffuser to the boundary limits of the lower convective zone; this zone should be previously established by dumping salt at the pond bottom and mixing it with fresh water. In the next step, a layer of fresh water @ few centimeters thick (5-10 cm.) is added. This procedure is repeated until the water level in the pond reaches the mark chosen as the pond depth. A similar process is used to maintain and repair the salinity gradient.

A diffuser can be made out of two 1 meter (3.28 ft.) diameter disks made of a noncorrosive material such as plexiglass a few centimeters thick. The gap between the disks and the supply water flow rate should be such as to assure a water velocity from the gap in the range of 0.25-1.0 m/sec. (0.7-3 ft/sec), depending on the pond size. For a 1/4 acre size pond two diffusers located in opposite corners of the pond may be adequate to perform the gradient maintenance work, but in the case of a 1/2 acre pond four diffusers may be necessary. The amount of solar radiation

tion penetrating to the pond bottom can vary between 20 and 40 percent. The thermal efficiency of a large size (1/2 acre) salt-gradient solar pond is usually in the range of 15 to 20 percent, although it could be as low as 9 percent for small size laboratory ponds where high heat losses occur. An operational pond temperature of about 60°C (140°F) with temperature fluctuations of 223°F can be expected. The pond upper convective layer usually has 1-4 percent of salt and the lower convective layer has 23-27 percent of salt by weight.

When an internal heat exchanger is used the rule of thumb is

as

---Page Break---

that about 37 m. (222 ft.) of heat exchanger piping length is needed for every 20 kw of thermal power extraction from the pond. The heat exchanger piping should form a serpentine configuration and be located in the lower convective zone. Copper and brass piping are often used as heat exchangers. To assure the reliability of heat extraction from the pond and equipment durability, a stainless steel heat exchanger and leak proof pump may be recommended. A galvanized iron pipe heat exchanger will corrode easily when the saturated solution level comes down below the heat exchanger and exposes the piping to non-saturated water salt solution. Because of the scarcity of information about

metal corrosion in solutions of high salt concentration, however, an external heat exchanger may be more suitable for a heat extraction system, especially for large size ponds. If an external heat exchanger is used, an effort should be made to prevent any air leaks in the external piping or in the pump, because air bubbles will be introduced into the lower convective zone. A continuous injection of air bubbles could destroy the salinity gradient in the pond. To assure the effective maintenance of the salinity gradient zone, the injection of 2-5 kg/sq.m. (4.4-10 lbs/8sq.ft.) of salt per month may be required. This should be done just below the boundary of the upper convective zone since this zone has a tendency to grow thick, a process which leads to the destruction of the temperature gradient in the pond. Usually PVC valves and PVC piping are used to carry the brine to an external heat exchanger.

Another rule of thumb is that 1-2 kg. (2.2-4.4 lbs.) of chlorine per week per each 1600 sq. m. (10760'sq. ft.) of pond area may be needed to prevent algae build-up in the pond.

An evaporation pond often works in conjunction with the production pond. The evaporation pond, up to half the size of the Production pond, serves to produce highly concentrated brine which is injected into the production pond to maintain the salinity gradient. The evaporation pond can also be used to take care of the rain water overflow from the production pond. Both ponds may have vertical walls or 45° sloped walls, The latter, however, can increase heat losses through thermal convection at the walls.

Heavy-duty plastic liner made from chemically resistant polymer-coated polyester fabric, vinyl liner, EPDM liners OR XR-SSP hypalon fiberglass reinforced liner seem to work Satisfactorily. The second liner (back-up liner) is usually thinner and also cheaper. Beach sand is recommended for use in a 10 cm.

(3.9'in.) thick layer at the bottom of the pond and between the liners. The pond bottom and/or walls sometimes are thermally insulated as well. Floating Pvc pipes can be used to suppress wind disturbances on the pond surface.

Detecting and locating leaks is one of the most difficult problems in a salt-gradient solar pond. Most often the leaks occur in seams of the liner. To locate a leak in the pond either a scuba diver is used or the following method could be employed: a length of perforated rubber or plastic hose in a serpentine arrangement is buried in the sand layer between the liners during the pond construction. The hose is plugged at the buried end and runs above ground at the other end. Upon suspecting a leak,

by routinely checking the salt inventory in the pond, compressed air or nitrogen is introduced into the hose with sufficient pressure to equal the hydrostatic pressure at the bottom of the pond. The leak locations are found by locating gas bubble streams on the pond surface. A sump pump could be connected to the hose to evacuate the leaking solution from beneath the liner. The same pump can also be used to evacuate the brine from the lower convective layer to the evaporative pond; usually it is necessary, to empty the pond to patch up the liner.

Recalibrated platinum electric conductivity probes are used for salinity gradient measurement. Probes of the same type are used for leak detection between liners. Copper-constantan thermocouples in stainless steel or vinyl jackets are normally used for ground temperature measurement. Platinum resistance thermometers, e.g. 100 Ohm RTDs, are used for pond temperature measurement.

Generally the present cost of man-made salt-gradient ponds are in the range of \$50 to \$100/sq. m. (54.60 to \$30/sq. ft.)

Naturally occurring salt lakes can be converted into ponds at a cost much below \$50/sq. m. (54.60/sq. ft.). The major capital costs are for salt, liner, excavation and heat extraction equipment. The salt cost can be up to half of the total cost. When a salt lake is used as a solar pond for the construction of an electric power plant, the total cost can be divided half and half between the pond construction cost and the cost of the power, equipment. In some locations, such as countries in the Middle East, the cost of water for the pond make-up operation may not be negligible, and in others, such as the islands of the Caribbean region, the cost of land may be an important factor. Pond depth ranges from 0.9 m. to 4.5m. (3 ft. to 15 ft.) with deeper ponds being used in areas where seasonal heat extraction is required.

Energy costs between \$6.60 and \$9.50/cu m (37 to 10 per million Btu's) are projected for large size production ponds with an area of 40000 sq. m. (430400 sq. ft.). The cost of the construction of shallow solar ponds is higher and can be estimated to be in the range of \$150 to \$205/cu m. (514 to \$19/sq. ft.).

5. coNcLUsoNS

Solar ponds are technically feasible and can be economically competitive, as proven by some users. Building an experimental pond may be a necessary first step to gain direct experience and to demonstrate engineering proof of the concept. However, out of the 25-30 small and large demonstration ponds which have been built around the world, only about seven are production ponds, Therefore more production ponds should be built to gain market acceptability through the reliable and economical operation of large size ponds integrated into industrial, commercial or agricultural processes.

Although only a few production ponds have been built and operated, the technical simplicity and the research results obtained indicate that shallow solar ponds are market ready while salt-gradient solar ponds may be on the fringe of market readiness. Whereas the technical/engineering problems related to

v7

---Page Break---

Bond applications are being addressed by current research and development activities, the environmental, institutional and policy issues lag behind and could act as obstacles to the large-scale use of solar ponds in the future.

REFERENCES

1. Ay Fy Clark and W. c. Dickinson, Shallow Solar Ponds, Chapter 12, pp. 377-402, solar Energy Technology Handbook, Marcel Dekker, Inc., New York, 1980.

2. W. C. Dickinson, A. P. Clark and A. Yantuono, Shallow Solar Ponds for Industrial Process Heat: The ERDA/Sohio Project, Report UCRI-78288, 1976, Lawrence Livermore Laboratory) University of California, Livermore, Ca. 94550, U.S.A,

3. W. W, Auer and W. R. cherry, ERDA Solar Thermal Energy Program for Industrial Process heat, Proceedings of the International Solar Energy Society Conference (Sharing the sun, Solar Technology in the Seventies), Voll, pp. 176-185, August 15-20, 1976, Winnipeg, Canada.

G. R. Guinn and B. R. Hall, Solar Production of Industrial Process Hot Water Using Shallow Solar Ponds, Proceedings of the Annual Meeting of American Section of the International Solar Energy Society, Vol.2.1, pp. 947-951, August 28-31, 1978, Denver, Colorado, U.S.A.

A.B. Casamajor, The Application of Shallow Solar Ponds for Industrial Process Heat: Case Histories, Proceedings Of the Silver Jubilee Congress of the International Solar Energy Society, Vol.11, pp. 1029-1032, may 1379, Atlanta, Georata, U.S.A.

6. Industrial Process Heat, Solar Age, Vol.4, No.3, pp. 19-24, 1379.

7. Ay B. Casamajor and R. E. Parsons, Design Guide for Shallow Solar Ponds, UCRL~52385, January #, 1973, Lawrence Livermore Laboratory, ?University of California, Livermore, Ca, 94550, Us.AL

8. A. I. Kudish and D. Wolf, A Compact Shallow Solar Pond Hot Water Heater, Solar Energy, Vol.21, pp. 317-322, 1978.

9. R. E. Forbes, Design and Testing of a Plestic Bubble - Film Covered Shatiow Solar Pond, Proceedings of the ASHE Solar Energy Division Fourth Annual Conference, pp. 62-89, April 26=29, 1982, Albuquerque, New Mexico, U.S-A.

20. A. F. Clark, A. B. Casamajor and L. O. Rewett, Shallow Solar Ponds with Mirrors on the orth Side, Proceedings of the International Solar Energy Society Congress, Vol-II, pp. 1078-1079, January 1978, New Delhi, Indias

11. J.C. Silver and F.C. Wessling, Simulation methods Developed
for the Design of Conmorciel Hot Water systems Ueilizing

18

---Page Break---

22.

13.

aa.

1s.

16.

uw.

as.

20.

au.

22.

23.

24.

25.

Shallow Solar Ponds, Proceedings of the Annual Meeting of
American Section of the International Solar Energy Society,
Vol.4-1., pp. 782-785, May 1981, Philadelphia, Pennsylvania,
U.S.A.

Me (G; Dickinson, Economics of Process Heat from Solar Energy,
Chemical Engineering, pp. 101-104, January 31, 1997.

A, -Nallecsinsky, Ungarische Warme und Heisse Kocksalzeen als
Natuerliche Warmeaccumulatoren, Annales der Physik, Yol.J,
No.4, pp. 408-416, 1902.

B, Tabor, Large Area Solar Collectors for Power Production,
Solar Energy, Vol.7, No.é, pp. 189-194, 1963,

H. Tabor and R. Matz, Solar Pond Project, Solar Energy, Vol.9
No.4, pp. 177-182, 1365.

D.L, Styris, R, Zaorski and O. K. Harling, Nonconvecting
Solar Pond: An Overview of Technological Status and Possifle
Pond Applications, BNWL-1891, January 1975, Battelle Pacific
Northwest Laboratory, Richland, Washington, U:S-A.

7. 8; Jayadev and M. Edesess, Solar Ponds, SERI/TR-731-587,
April 1980, Solar Energy Research Institute, Golden, Colotado
80401, U.s!a.

D. Crevier, State of the Art Review of Solar Ponds, Solar
Energy Project Report No. Pond-1, August 1980, National
Research Council of Canada, ottawa, Canada.

\$8, L. Sargent, Overview of the DOE National and International
Program for Salt-Gradient Solar Ponds, Proceedings of the
Annual Meeting of the Anerican Section of the Invernatioval,
Solar Energy Society, Vol.3.1, pp. 395-399, Sune 1980,
Phoenix, Arizona, U.S.A.

H, Tabor, Solar Ponds, Solar Energy, Vol.27, No.3, pp. 181-134, 1981.

M. Edesess, On Solar Ponds: Salty Fare for the World's Energy Appetite, pp. 59-68, Technology Review, November-December, 1982.

G; E. Nielsen, Nonconvective Salt-Gradient Solar Ponds, Chapter 11, pp. 345-376, Solar Energy Technology Handbook, Marcel Dekker, Inc., New York, 1980.

H. Tabor and z. Weinberger, Nonconvecting Solar Ponds, Solar Energy Handbook, Chapter 16, pp. 1-29, McGraw Hill, New York, 1981.

M. Eéesess, J. Henderson and T. S. Jayadev, A Simple Design Tool of Sizing Solar Ponds, SERI/RR-351-347R, December 1999, Solar Energy Research Institute, Golden, Colorado 80401, U.S.A.

J. R. HULL, Y. S. Cha and W. T, Sha, Major besign,Construction

---Page Break---

26.

27.

28.

29.

30.

a.

32.

33.

3a.

35.

36.

and Operational considerations of Salt-gradient Solar Ponds,

PADI-82, XVII Convencion de Union Panamericana de Asociacion

Honores de Ingenieros, August 1-7, 1982, CEER/UPR, GPO BOX 3682,

San Juan, Puerto Rico 00936.

7. R.A. Davey, "The Aspendule Sola Por

CSIRO, Highett, victoria 3190, rustral

Report R15, 1968,

F, Zagrande and H.C. Bryant, A Salt-Gradient Solar Pond,

PP. 21-35, Solar Age, april i97e.

. E. Nielsen, Dquilibrium Thickness of the stable Gradient

Jone in Solar'vonds, Proceedings of the Annual Mesting of

American Section of the International Solar Energy souiety,

Vol.2-, pp. 932-935, August 28-31, 1978, Denver> Colorads,

ULS.AL

ø- B Nielson, Control of Gradient zone Boundaries, Proceed-

ings of the sitver Jubilee Congress of the Internationa)

Solar Energy Society, Vol.II1, pp. 1010-1014, May 1979,
Atlanta, Georgia, U.S.A.

B.S; bryant, R. P. Bowser and L. J. Wittenberg, Construction
ang Initial Operation of the Miamisburg Salt-Gradient Soler
Pond, Proceedings of the Silver Jubilee Congress of the ine
ternational Solar Energy Society, Vol-11, pp. 1003-1009,

May 1979, Atlanta, Georgia, U.S.A.

ZL, 3, Wittenberg and M. J. Harris, Evaluation of a Large
Nonconvective Solar Pond, Proceedings of the Workshop on
Solar Energy storage options, Vol.1, pp. 193-202, March 1979,
San Antonio, Texas, U.S.A

J. R: Hull, Wind Induced Instability in Salt-Gradient Solar
Ponds, Proceedings of the Annual Meeting of American Section
gf the International Solar Energy Society, Vol.3.1, pp. 3710
375, June 1980, Phoenix, Arszona, U.S.A.

Le 9. Wittenberg and M. J. Harris, Management of a Large,
Operational Solar Pond, Proceedings of the 15th Intersecty
Energy Conversion Engineering Conference, Vol-2, "pe, 143s~
1437, August 1980, Seattle, Washington, U.scAL

D. |W. Kuberg, Solar Ponés in the Region Served by the Tennessee Valley Authority, Proceedings of the 15th? Inter=society Energy Conversion Engineering Conference ,Vol.2, bp. 1432-1434, ?August 1980, Seattle, Washington, U-S-A.

?:B, Nielsen, Design and Initial operation of a 400 m? Solar Pond, Proceedings of the Annual Meeting of American Section of ?the International Solar Energy Society, Vol.3.1, pp. 381-385, June 1980, Phoonix, ArizonasU.ScAL

G- E. Nielsen and J. Kemal, The 400 mn? Solar Pond: One Year Operation, Proceedings of the ;nnual Meeting of nactiean Section of the International solar Energy Society, Vol tel, PP. 758-762, May 1961, Philadelphia, Pennsylvania, USUAL

20

---Page Break---

a7

38.

39.

40.

a.

42.

43.

aa.

45.

a7.

48.

Editorial article, Nonconvecting Salt-Gradient Solar Pond a
New Energy, Technology, Energy Demonstration and Technology.

Issue 13, 1981, Office of Power,

Chattanooga, Tennessee 37401, 0

?Tennessee Valley Authority,

S.A.

S. M. Patel and C. I. Gupta, Experimental Solar Pond in a

Hot Humid Climate, Sunworld, Vol.5, No.4, pp. 115-118, 1981,

D. D. Weeks and H. Cc. Bryant, What Happens When

Solar Pond

Boils?, Proceedings of the Annual Meeting of American section
of the International solar Energy Society, Vol-4.1, pp. 168.

771, May 1981, Philadelphia, Pennsylvania, U.S/A.

International Solar Pond Letters, No.4, January 1961, p. 23,

T. Ochs, Editor, Desert Research Institute, Boulder City,

Nevada 89505, U.S.A.

M. J. Harris, D. B. Etter and 1.

J. Wittenberg, observations

Regarding Materials and Site Preparation for Salt-gradient

Solar Ponds, Proceedings of the

Annual Meeting of American

Section of the International Solar Energy Society, Vol.4a1,

Pp. 787-790, May 1981, Philadelphia, Pennsylvania, U.S.A.

Y. S. Cha, W. T. Sha and J. R. Hull, Design, Construction and

Initial Operation of the AL Research Salt-Gradient Solar

Pond, ANL-81-55, August 1981, Argonne National Laboratory,

Argonne, Illinois 60439, U.S.A.

D. W. Kuberg, A Review of TVA's

Nonconvecting Solar Pond

Activities, Proceedings of the Annual Meeting of American

Section of the International Sol

ar Energy Society, Vol.4-1,

pp. 777-781, May 1981, Philadelphia, Pennsylvania, USUAL

GB. Nielsen, Salt Transport and Gradient Maintenance in

Solar Ponds, Proceedings of the
American Solar Energy Society, Part T
Texas, U.S.A.

Annual Meeting of the Ameri-
+ pp. 179-184, 1982, Houston,

J. Kamal and C. E. Nielsen, Convective zone Structure and

Zone Boundaries in Solar Ponds,
Meeting of the American Solar En-

Proceedings of the Annual
Energy Society, Part I,

pp. 191-196, 1982, Houston, Texas, 18-A.

R. Coates, R. Fench and S. Schweitzer, Solar Pond Construc-
tion and Cost Performance Analysis, USADI-82, XVII Convec-
tion de Union Panamericana de Asociaciones de Ingenieros,

August 1-7, 1982, CEER/UPR, GPO
Rico 00936.

R. P Fynn and T. H. Short, solar

Box 3682, Sand Juan, Puerto

Ponds = A Basic Manual,

Report No.106, February 1983, The Ohio State University,

Ohio Agricultural Research and Development center, Wooster,

Ohio 44691, U.S.A.

G. F. Jones, K. A. Meyer, 3. c.

D. P. Grimmer, Design, Construct

Of the Los Alamos National Laboratory

Pond, Proceedings of the annual

ar

Hedstrom, J. S. Dreicer and

ion, and?Initial Operation

?ory Salt-Gradient Solar

?eeting of the Solar Energy

---Page Break---

50.

1.

52.

53.

55.

56.

57.

58

59.

Division of the American Society of Mechanical Engineers,

April 19-21, 1983, Orlando, Florida, U.S.-h-

D. K. Dixit, B. D. Shiwalka and V. ti. Dokras, Some Studies
on an Experimental Solar Pond, Proceedings of the Intec,
Rational Solar Energy Society Congress, Vol.II. op. iera~
21077, January 1978, New Delhi, India

Aonual Report Number M-43, 1 June 1980 to 31 May 1982,
Brace Research Institute, McGill University, Montreal Quebec,
Canada H9 x lco.

R. P. Beldan and J. F. Lane, Experimental Operation of a
Snall Solar Pond, Proceedings of the Canadian Solar Energy
Society Conference ENERGEX-82, Vol.II, pp. 715-120, August
1962, Regina, Saskatchewan, Canad

B. Nimmo, A. Dabbagh and S. Said, Salt-Gradient Solar Ponds,
Sunworld, Vol.5, No.4, pp. 113-114, 1981.

R, p. Fynn, P. C. Badger, T. H. short and M. J. Sciarini,
Monitoring ?Sodium Chloride Concentrations and Density Pro-
files in Solar Ponds by Electrical Conductivity and temper
ature Neasurement, Proceedings of the Annual Meeting of
American Section of the International Solar Bnergy society,
Vol.3.1, pp. 386-390, June 1980, Phoenix, Arizona, U.S-A>

7.8: Jayadev and J. Henderson, Salt Concentration Gradient
Solar Ponds - Modeling and Optinization, Proceedings of the
Silver Jubilee Congress of the International Solar Energy
Society, Vol.IK, pp. 1015-1018, May 1979, Atlanta, Georeia,
U.S.A.

7. Newell, J. Pande and R. Bochm, Development of Performance
Information for Large Scale Solar Pond Applications (abstract,
Proceedings of the Annual Meeting of the American Section of
International Solar snergy Society, Vol.3-1, June 1980,
Phoenix, Arizona, U.S.A.

K. A. Meyer, A One-Dimensional Model for the Dynamic Layer
Behavior in?a Salt-cradient Solar Pond, Proceedings of the
Annual Meeting of American Section of the Internacional
Solar Energy Society, Vol.4.1, pp. 763-767, May 1981, Phila~
delphia, Pennsylvania, U.S.A.

D. Crevier, Enhanced Ground Storage for Solar Fonds, Pro-

ceedings of the Annual Meeting of American Section of the
International Solar Energy Society, Vol.4.1., pp, 736.600,
May 1981, Philadelphia, Pennsylvania, U.S/A.

J; Bs Davila Acaron, Solar Ponds in Puerto Rico ~ A Feasi-
bility Study, Final?Report, April 13, 1981, Center for Energy
and Environment Research/UeR, Solar Division, Mayaguez,
Puerto Rico 00708, U.S.A.

J. Re Mull, KV. bis Y. S. cha, HI. Mm. Donanus and W. 7.

Sha, Solar Pond Salt Gradient Instability Prediction by
Means of @ Thermo Hydrodynamic Computer Cone, Procecditgs of

22

---Page Break---

60.

ee

62.

64.

6s.

66.

6.

69.

70.

n.

the Annual Meeting of American Section of the International
Solar Energy Society, Vol.4.1, pp. 812-816, May 1981, Philadelphia,
Pennsylvania, U.S.A.

9. F. S. Atkinson and D. R. F. Harleman, Solar Pond Research at
Miami, International Solar Pond Letters, Vol.1, No-1,2, pp. 3-4,
1982.

A. Moshref and D. Crevier, Electric Power Generation by
Solar Ponds: Modeling and Optimization, Proceedings of the
Annual Meeting of American Section of the International Solar

Energy Society, Part 1, pp. 203-208, 1982, Houston, Texas,
U.S.Ae

A. Duyar and W. Bober, Investigation of Thermal Interactions
Between a Nonconvective Solar Pond and Earth and Ground Water
Below, Proceedings of Condensed Papers of the St. Miami
International Conference on Alternative Energy Sources,

P. 503, December 13-15, 1982, Miami beach, Florida, U.S.A.

J.B. Hull, Membrane Stratified solar Ponds, Proceedings of
the Silver Jubilee Congress of the International Solar
Energy Society, Vol. 11, pp. 1000-1004, May 1979, Atlanta,
Georgia, U.S.A.

J. R. Hull, Membrane Stratified Solar Ponds, Solar Energy,
Vol. 1.25, pp: 317-375, 1980.

D. Crevier and A. Moshref, The Floating Solar Pond, Pro-

ceedings of the Annual Meeting of American Section of the International Solar Energy Society, Vol.4.1, pp. 801-805, May 1981, Philadelphia, Pennsylvania, U.S.A.

E. I. H. Lin, A Saltless Solar Pond, Proceedings of the Annual Meeting of the American Solar Energy Society, Part I, pp. 215-219, 1982, Houston, Texas, U.S.A.

M.S. E. Abdo, A Now Chemically Stratified Solar Pond, Proceedings of the Condensed Papers of the Sth Miami International Conference on Alternative Energy Sources, pp. 501-502, December 13-15, 1982, Miami Beach, Florida, U.S.A

J. A. Bonnet, Jr., J.T. Pytkineki and K. G. Soderstrom, Solar Energy Storage for Cooling Systems in the Caribbean, Proceedings of the International Workshop on Solar Energy Storage, March 1982, Jeddah, Saudi Arabia.

A. Rabl and C. E. Nielsen, Solar Ponds for Space Heating, PP. 608-616, Chemitech, October 1975.

A. Rabl and C. E. Nielsen, Solar Ponds for Space Heating,

Solar Energy, Vol-17, pp. 1-12, 1975.

C. E. Nielsen, Experience with a Prototype Solar Pond for
Space Heating, Proceedings of the International Solar Energy
Society Conference, Vol.5, pp. 169-182, August 1976, Wine
nipeg, Canada

23

---Page Break---

n.

73.

m.

78.

6.

7

78.

79.

80.

an.

a3.

G. M. Leboeuf, Solar Ponds Applied to District Heating and Cooling, Proceedings of the Annual Meeting of American Section of the International Solar Energy Society, Volume 1, Pp. 772-776, May 1981, Philadelphia, Pennsylvania, US A.

E. I. H. Lin and K. L. French, Solar Pond Regional applicability Study: summary of Results, Proceedings of the Annual Meeting of the American Solar Energy Society, Part I

Pp. 209-214, 1982, Houston, Texas, U.S.A.

Annual Report of 1982, Solar Division, Center for Energy and Environment Research, University of Puerto Rico, Mayaguez Puerto Rico 00708.

D. Crevier, An Experimental Solar Pond for industrial Process

Heat, Proceedings of the Canadian Solar Energy Society

Conférence ENERCEX-82, Vol-11, pp. 05-714, August 1982,

Regina, Saskatchewan, Canada

T. H. Short, W. L. Roller and P. C. Badger, A Solar Pond
for Heating Greenhouses and Rural Residences - A Preliminary
Report, Proceedings of the Solar Energy Workshop on Food,
Fuel, pp. 41-50, April 5-6, 1976, Tucson, Arizona, U.S.A.,

2. H. Short, P. C. Badger and W. L. Roller, the Development
and Demonstration of a Solar Pond for Heating Greenhouses,
Proceedings of the Silver Jubilee Congress of the International
Solar Energy Society, vol.11, pp. 1021-1025, May
1979, Atlanta, Georgia, U.S.A.

R. P. Pynn, T. H. Short and S. M. Shah, The Practical opera-

tion and Maintenance of a Solar Pond for Greenhouse Heating,
Proceedings of the Annual Meeting of the American Society of
Agricultural Engineers/Symposium, September 30
October 1, 1980, Kansas City, Missouri, USA.

M, Collares Pereira, A. Joyce and L. Valle, Salt-Gradient
Solar Pond for Greenhouse Heating Applications, Proceedings
Of the Annual Meeting of the American Solar Energy Society,
Part I, pp. 221-230, 1962, Houston, Texas, USA

H. Tabor, Solar Ponds, Electronics and Power, pp. 296-299,
September 1964.

A, B. Difrawi, B. Yudow and R. H. Grotheer, A New Desalination:
The Solar Evaporator and Condenser System (SEACS) »
Proceedings of the Annual Meeting of American Section of the
International Solar Energy Society, Vol.4.1, pp. 791-795,
May 1981, Philadelphia, Pennsylvania, U.S.

G. Lesino, L. Saravia, J. Hangussi and R. Caso, Operation of
2.4002 Sodium Sulphate Solar Pond in Salta, Argentinas
international Solar Pond Letters, Vol.1, No.1e?s pp. 42-13,
November 1982.

W. Tabor, Solar Ponds: Lerge-Area Solar Collectors for
Power Production, Solar Fregy. Vols}, Nood, pps 189-194,
1363.

24

---Page Break---

a4.

8s.

87.

89.

90.

ou.

92.

93.

94.

95.

96.

G. Assaf, B. Doran, Z. vsinhaiser, © Yrockel, H. iershman,

Al Katz and?S. Sariq, Letcs 82. Jota: vende for Slectri-

city Production, Progenuiros ?Liver Jubilee Congress

of the Internatfonel sols fn Sets, Yolell, ps 1020,

May 1979, Atlanta, Geos si

WM, Tabor, Power from?

Scientific Resnorch F<

L,Y. BrOnicks » Lowes er 8 Hoes

No.4, pp. 121-f22,"iee2

unworld, Vol.5,

J.D. Wright, Setrco.su

Rankine Cycle Coupied +

Direct-contart lest Sx

Annual Conzeren

of Mechanical! :

Albuguerque, Siow

& for an Organie

ar Pond by

fo of the Fourth

merican Society

Ve Spel 26-25, 2982,

Bebe Osho and go oe eee of a Saturated

Naj0 = 280, ° 1) #50 Ko: whew oy So1 0 Sond, Proceedings

ofthe sifvér suhitee : Lvernstional Solar

Energy Society, Yot.7%, Suck May 1979, Atlanta,

Georgia, 0

7. Ochs, opera bxperio, 2 nivre-e@ Sorax Solar

Pond, Proceed, the ists Inlescos wets Energy Conversion

Engineering cantecence, Yo! > | vasy, August 1980,

Seattle, Washington, U/S.x

8. C. Jain ard G.

Self-correct:on

15th Intersoc:

ration of

cedings of the

G conference,

Vol.2, pp. Laat shington, U.S.A.

G. D. Menta, st vt toe Sear Ponds, NASA

Tech Brief, NPC-15439, 9% Vesouision Laboratory,

Pasadena, Californ

B.S. Wilkins, E. van

of the 16th 1

ference, vor.

Pond, Proceedings

sion Phasneering Con

B. 8. Wilkins, M. E1-ce> Poctuseein! and p. Thakur,

Aa Evaluation of the Get fon. iscformance, Proceedings of

the Winter Mecting of the» ies cociaty of Mechanical,

Engineers, November 1982, / >

rr

G. Assaf, The Dead Sea: A
Energy, Vol.18, pp. 293-296,

= Sciar Lake, Solar

R. L. French and J. Mestieri in Sua fewer Pond Project,
Proceedings of the 15th International Conversion?
Engineering Conference, vol.1.2, SI, August. 1980,
Seattle, Washington.

P. Bolon, Power from the
Science, pp. 84-86, April

© Fonds, Popular

---Page Break---

7.

8. Winsberg, Solar Perspectives: Israel, Solar Pond Innovator, Sunworld, Vol.5, No.4, pp. 123-125, 1981,

California Energy Commission, Solar Salt Pond - Electric Power Generation Potential of the Salton Sea, Executive

Summary, P700-81-014, August 1981, Sacramento, California, U.S.A.

California Energy Commission, Solar Salt Pond Generating Facility: A Feasibility study for Californie, Consultant Report, Vol.I, P700-61-015, August 1981, Sacramento, California, U.S.A,

26

---Page Break---

---Page Break---