

CEER-X-113

BIOGAS POTENTIAL IN THE,
REPUBLIC OF PANAMA

ictae 0. ERDMAN

CBER ?X-113

---Page Break---

?TABLE OF CONTENTS

Page

er vevettetettetteeseree

Introduction+

Batch Fermentations . : ce 3

Continuows Fermentations . 4

High-rate Fermentations . bones 4

Anaerobic Filtration .. cece 5

Anaerobic Contact Fermentation : 5

Multistage Fermentation, 6

Methods and Materials . 6

Results

Current Biogas Program in the Republic of Panna 7

General Characteristics and Geographic Sites for

Biogas Production . sae 8

Recommended Studies to be Undertaken to Fully Assess
the Biogas Potential

Resource and Energy Studyu

Biodegradability Study000..00eecsseeeeeeeeeereee 18

Design and Material Study0++ vieeteeseeeeee 19

National Biogas Plan- : 2

Biogas Projects to be Developed . . + 2%

Residential Biogas Project « vee 25

Cooperative and Community Biogas Project « ve

Industrial and Governmental Biogas Project

---Page Break---

Specific Recommendations 229

Conclusion 30

Acknowledgment 31

Bibliography ... 232

Appendum

Itinerary ... - 3h

Sites Visited .. ce 36

Physical and Chemical Survey of Available Resources

Sources of Biogas Information

Resource and Energy Study Requirements . 43

Biodegradability Study Requirements « = hs

Design and Material Study Requirements « 245

Residential Biogas Project Requirements .. - 46

Cooperative and Community Biogas Project Requirements 48

Industrial and Governmental Biogas Project Requirements ... 49

it

---Page Break---

BIOGAS POTENTIAL IN THE REPUBLIC OF PANAMA

M.D. Erdman

ABSTRACT

A technological assessment of biogas production potential and the impacts of this technology were undertaken in the Republic of Panama. The assessment data were collected from various National government agencies, during interviews, and from site observations during a two-week period. An estimated 34.1 to 132.3 11.3, 103.1 to 181.4 and 20.5 to 34.5 x 10⁸m³ of biogas could be

Produced annually from readi

y collectable animal, aquatic, agro

industrial and community wastes, respectively. This biogas would

provide 3.1 to 8.71×10^7 MJ of energy, which is equivalent to

61.5 to 172.8% of the electrical energy supplied nationwide in

1979. Plant biomass and other organic residues also could be

anaerobically fermented to produce biogas. Although biogas pro-

duction potential exists, limited effort and resources have been

devoted to this alternate energy production process in Panama.

Three studies and three projects were proposed to evaluate and

stimulate biogas production and use. The proposed study or proj-

ect, estimated time (years) requirement, numbers of staff members

and cost requirement (dollars) were: resource and energy study,

1.0 , 2.0 and $\$36,700$; biodegradability study, 1.5 , 1.0 and $\$41,620$;

design and material study, 0.33 , 3.0 and $\$21,800$; residential bio-

gas project, 3.0 , 11.0 and $\$996,380$; cooperative and community

---Page Break---

biogas project, 3.0, 5.0 and \$784,630; and industrial and governmental biogas project, 2.0, 2.0 and \$109,000, respectively. Biogas production and use could impact: 1) the residential sector where 46% of the population does not connect to the electrical grid; 2) cooperatives and small communities with biomass resources and 3) industrial and governmental sectors producing sufficient organic matter waste by-products during normal operation.

INTRODUCTION

Electricity production in the Republic of Panama is under the authority of the Institute de Recursos Hidraulicos y Electrificación (IRHE). In 1979, IRHE produced a total of 1.4×10^8 million watt hours of electricity, which was obtained from petroleum (55%) and hydro (45%) sources (2). Due to increasing costs of petroleum fuels and high capi

tal investment costs for hydrogenerating systems, alternative energy resources are being investigated.

Biogas, a mixture composed primarily of methane and carbon dioxide, is produced during the anaerobic fermentation of organic

matter. The anaerobic fermentation process is currently viewed

as a three-stage process. During the first stage, the ferment

tive bacteria hydrolyze complex carbohydrates, proteins and lipids and metabolize these simpler compounds to fatty acids, hydrogen and carbon dioxide. During the second stage, the aceto-

genic bacteria metabolize the simpler fatty acids and produce

---Page Break---

3

acetate, carbon dioxide and hydrogen. During the third stage, which is strictly anaerobic, methanogenic bacteria metabolize the products of the first two stages (primarily acetate, carbon dioxide and hydrogen) to produce a gaseous mixture of methane and carbon dioxide (5), commonly called biogas.

The advantages of biogas production and use are: the fermentation substrate can come from local origin; the fuel can be used to perform useful work in a variety of ways (i.e., cooking, Light-

ing, refrigera

mn, electricity production); the fermentation

equipment can be fabr:

ated from locally available materials and

labor skills and the energy source can be stored (1). The pollu-

tion potential of discarded organic matter also can be greatly re~

duced and many pathogenic

Microorganisms can be destroyed during

the anaerobic fermentation.

Biogas production has been conducted by batch, continuous, plug flow, anaerobic filtration, contact processes and multistage fermentation techniques. These fermentations also have been evaluated under low and high solids loading rates, at various fermentation temperatures and pl (14). A brief review of the various

approaches used during the anaerobic fermentation process is presented below.

Batch Fermentations.

In batch fermentation, organic matter and inoculum are added to the fermenter. The fermenter is then sealed to exclude oxygen and the fermentation is allowed to proceed until the substrate

---Page Break---

4

supply is depleted or biogas production decreases or stops. The fermenter contents are then removed and the process repeated.

Batch fermentations have the advantage of requiring small labor inputs; however, this advantage is offset by a long lag period and discontinuous biogas production. This type of fermentation is generally considered impractical for agricultural waste or biomass

fermentations because of the high capital costs for the fermenter.

Continuous Fermentations.

Ferment.

Systems of this type are fed on a continual or semi-continual basis. Due to feeding routine and fermenter capacity, an equal amount of material is generally displaced from the fermenter at the time of feeding. The IRME is currently constructing a fermenter of this type. This fermentative approach has the advantages of continuous operation and relatively constant biogas production. Furthermore, the fermenter capacity can be more closely designed to meet the biogas operating requirements, which reduces capital investment costs. In a plug flow fermentation, the waste substrate is periodically added to the fermenter and successively displaced through the system by subsequent substrate additions. Plug flow fermentations have been reported in Germany (11), South Africa (9), England (4) and Puerto Rico (7)

High-rate Fermentation

A high rate fermentation uses agitation and temperature control to insure that the fermentation proceeds at a stable optimum rate. This approach was initially developed for use in sewage disposal. This fermentation approach is generally recognized as

---Page Break---

5

essential for optimizing fermentation rate (14). Potential disadvantages of the high-rate approach are high energy inputs to maintain agitation and temperature, sophisticated control mechanisms and high capital equipment costs. Since this type of approach has been widely used in human waste treatment plants, much information and technical expertise is available. However, the costs for these services or equipment may be prohibitive

Anaerobic Filtration.

In an anaerobic filtration process the microbial populations attach and colonize on a support structure within the fermenter. The media substrate is then passed over the microorganisms. In this fermentative approach the microorganisms essentially stay within the fermenter and are not

placed as in the high-rate or plug flow fermentations. Although this approach has been demonstrated, only wastes with a relatively low biological oxygen demand (BOD) of 200 to 10000 mg/l were considered applicable (14).

Anaerobic Contact Fermentation

The anaerobic contact process returns settleable solids and microorganisms back to the fermenter for further degradation. This approach allows for a rapid fermentation, which decreases the fermenter capacity requirements. The major difficulties with this type of approach are the poor settling characteristic of various wastes, especially those with trapped gas particles attached, and the low solids requirement in the inlet waste stream

---Page Break---

Multistage Fermentation,

A multistage fermentation is designed to isolate and optimize the individual metabolic conditions for the major groups of bac~

teria involved in the process. Theoretically, this would result in improved fermentative efficiency and reduced capital and operating costs. Pfeffer (12) reports that a multistage fermentation is more efficient than a complex mix system, but if the system is stressed, failure of the multistage system is more rapid (14).

All the preceding fermentation approaches have been successfully demonstrated. The advantages and disadvantages of each approach, however, vary depending upon many variables, such as: substrate type and supply; operating parameters; biogas needs; labor; economic and social considerations

The objectives of this study were to identify geographic areas where biogas production and utilization would interface in the Republic of Panama; identify and evaluate existing biogas technologies; identify studies and resources to develop biogas production potential; develop a national biogas plan and identify a series of projects to be developed within five years to expand the national biogas program.

METHODS AND MATERIALS

The assessment data was obtained from various national governmental agencies in the cities of Santiago and Panama, during interviews and at site visits during a two-week period (March 23

to April 3, 1981). An itinerary for the assessment period is

---Page Break---

7

Presented in appendix 1. Summary reports of the site visits and

interviews are presented in appendix 2

RESULTS

Current Biogas Program in the Republic of P:

A biogas development program was initiated in 1979 by IRHE

through an Agency for International Development (AID) grant program. The biogas

gran was situated within the Alternate Energy and Conservation group of IRHE. The program is directed by an engineer who is presently the only full-time program member, operating with a budget (excluding salary and overhead) of twenty

thousand dollars for the two-year program. IRHE is currently in-

stalling a 20-m³ flexible, horizontal, plug-flow, semi-continuous

anaerobic fermenter at a farming cooperative near the city of San-

tiago. The fermenter is being constructed of hypalon and will use

a solar collector operating by thermosyphon for auxiliary heating.

Swine waste (Si) solids will be manually collected from a concrete-

floored farrowing building and diluted with water to approximately

10% total solids. The mixture will then be added to the fermenter

daily. The design resembles the Taiwan, Republic of China, red-

mud plastic methane converter (3) fitted with a premixing tank

commonly found in the Gobar design from India (13). Materials for

the fermenter construction and monitoring are being supplied by

IRHE, Land, construction labor, daily operating labor and moni-

toring will be performed by the farm cooperative members under the

supervision of IRHE.

---Page Break---

A second fermenter is currently being designed by IRHE for installation at another site. Both IRHE fermenters are expected to cost approximately twenty thousand dollars.

The Instituto Agropecuario Jesus Nazarano (see appendix 2) has an operating 14-m³ anaerobic fermenter with 20-m³ of biogas storage capacity. This fermenter has been in operation since 1979 and the biogas is being used for cooking in the school cafeteria. Digested effluent from the fermenter is added to an aquaculture pond, which is harvested annually. The amount of SW produced at the farm was greater than the fermenter capacity; therefore, maximum t

ogas production potential has not been obtained

A red-mud plastic flexible fermenter has been ordered and is awaiting arrival and installation at the school. The additional fermenter capacity is expected to provide sufficient biogas for all cooking at the school and the excess will be used in spark-ignited, internal combustion engines.

No other biogas plants have been located within the Country

at the present time, although plans are being considered for biogas plant installation at @ municipal slaughterhouse currently being constructed.

General Characteristics and Geographic Sites for Biogas Production

Biogas production, in order to be economical and energy efficient, must be located near substrate resources. The Republic of

Panama is politically subdivided into nine major provinces and a

---Page Break---

9
nonprovincial area known as Comarca de San Blas. Due to the low population and limited accessibility of the San Blas area, little information was available for consideration in this report

?The national economy of Panama is based primarily upon agriculture and services. The principal agricultural commodities are bananas, sugar, rice and coffee. Secondary agricultural products of importance are meat and animal by-products, vegetables and root crops and fruits.

The data presented in Table 1 lists some general characteristics of the Country. The population of Panama is approximately 1.8 million and 45% of the population reside within the province of Panama. The provinces of Darién and Bocas del Toro have the lowest populations and densities within the Nation. The population density varies from 0.4 to 0.7 persons per hectare (HA) in Darién and Panamá, respectively. Provincial densities are comparable for low density areas of Darién and Bocas del Toro, intermediate areas of Los Santos and Veraguas and average density areas of Coclé, Colón, Chiriqui and Herrera

The greatest production of cattle, swine and poultry occurs in the areas of Chiriqui, Veraguas and Panamá, respectively.

The lowest animal production areas are Darién, Bocas del Toro, and Colón. Chiriqui and Coclé produce the greatest amount of coffee and rice, while the least amount of these commodities is produced in Bocas del Toro and Darién. Banana and sugar cane production (data not presented) are greatest in the areas

of Chiriqui and Bocas del Toro, Coclé and Panamá, respectively

---Page Break---

---Page Break---

a

The electrical power distribution characteristics are presented in table 2. In 1979, IRHE provided electrical service to a total of 220,058 customers. The distribution of residential, commercial and industrial users was 90.1, 9.5 and 0.4%, respectively. The numbers of residential customers were greatest in Panam, Los Santos, Colén and Herrera provinces and represented 76, 55, 53 and 49% of the total number of families within these provinces. Currently an estimated 46% of the nation's families are without electricity and could, therefore, be greatly impacted upon by the biogas technology for nonelectrical cooking, Lighting and refrigeration, Although electricity production from biogas is feasible, the capital investment costs and low efficiency preclude this method for the residential sector. The areas and relative importance of biogas production are greatest in Bocas del Toro > Darién > Veraguas > Coclé > Chiriquit > Colon > Los Santos > and Panama.

The residential and commercial energy sources used in Panama are presented in table 3. Wood provides an estimated 70.4% of the total energy requirement used in the residential and commercial segments within the Nation; electricity and refined gas represent the other major energy sources currently used. In areas without

electricity, wood and charcoal, kerosene and refined gas would increase in importance.

The major uses of biogas are presented in table 4. Biogas

production has been used for cooking, lighting, refrigeration,

---Page Break---

12

*1 eqns toss saouunu uosaeqeded !4q 7005 /su0s30ç g6*y Jo ofoz0K0 aya Suyen poawssaez,
oust;

~ ~ vosise oe 99907 stes6t rere:

sera sore sure 9 we rest svndeaay

view oerse zzu99t 1 soeet veveet evar

ars ases s6ovt a sve wove so2u8s 501

wes eran eevot ee we ozoa wxaaz0y

8205 ws recs - 66 as voraeç

orteas os'se reLes zu cove cusoz wbn

69°99 res rece 9 wre sreat ote

we aeree cate ? 862 otzs e180

06°56 ory esto - os 1 exe, rep sva0q

@) zerrteeg ? qwsarsapey ? yesoamaog ?TeyauapTsOy souynoza

Aap 0r9 vee

ata ERAS TAT

seria) soxisaes

Tersuapison ?_revawoptsou

sorasys029"seys vosangysasyp s9n0d TesTAI90Ts

+z otaen

---Page Break---

3

*eu6t ?aunt

Bupy009 ro Teo0z849

Sup 4009 woe Poon

st suaso203,

uoyavazodsueay. ?3034009 ror 09 pourzeu

sore ?uopawaoSpasou ?depagtyT sat Aayoraa0Ta

on wo wioy £82003

yeeueg Jo 2yTgRdoy 942 UT S96 puE soDznos ABsoUD TeTDZOMBOD pUE TOTIUAPTSOU ?f

STAEL

---Page Break---

os6t ?Te 22 orouruser #0234

LU6T ?so2uay0§ 30 Keapeay TeuOTIEN ora,

Aovororsge use ?ey 0d vopiwzeus8 3921001

(ist) not TSr0-S9"0

wiry gto ste fuyrrog Jo aasrT zed wane 20 a99e8 3oy TersleNRET

saeypoue37 ort fayovies ga x04 wopaez08paj9u

savypaazeaey gto duet aonod orpuv> gor sed sora

wiry yzvronvero fepysoszed 20d suPt009

sousyors3a wwor3eay3490ds sosn

---Page Break---

3

steam and electricity production. The major uses and relative importance ranking of biogas production in the residential areas of Panama are for cooking > lighting > and refrigeration.

A list of identified, underutilized resources of potential biogas production value and estimated annual biogas production

potential are presented in table 5. Five major sources of or-

ganic matter have been identified: animal residues, plant biomass, agro-industrial residues, commercial residues and residues accumulated as a result of governmental services. An estimated 34.1 to 132.3, 11.3, 103.1 to 181.4 and 20.5 to 34.5 x 10⁶m³ of biogas could be produced annually from readily collectable animal, aquatic, agro-industrial and government collected wastes, respectively. The biogas would provide 3.1 to 8.71 x 10⁹ MJ of energy, which is equivalent to 61.5 to 172.8% of the electrical energy supplied nationwide in 1979. Plant biomass and other organic residues also could be anaerobically fermented to produce biogas

Animal, plant and human residues appear to be the greatest potential resource base for the residential sector outside the capital city, Although animal residues are produced in the greatest amounts, the usual non-confinement housing of animals throughout the Nation greatly limit the amount of waste which is readily collectable.

In the capital city, garbage and human residues are the residues of greatest importance. Both renewable resources are under

---Page Break---

16

vsre0q acy

*4quo 4249 reewee,

*Aquo veg TeUED,

surowyun se pouryep ~ Kay

ute -t'8t seo o0t-04 ze ean

ee ore m0°0 oor ore-et erteqreo

Teauewuseacg

~ £0 09-07 aKa soasen otqrio%o,

~ £0 oot-08 axa ?seze0n 93028

- £0 0r-08 aKa season 272929309

ero396200

s78et-8"000 sto oor-08 errt-7'8 sopsoTts3s50

ez -e2 0 oor-08 eo soenoyaaaysner §

Tersisnpoy-025y

~ r0-e70 09-07 aaa seat9

wo so 09-09 £00°0 993309

~ ~ 09-07 xia eunueg

ent 0 os st SORT. PT

ze1ueyé 97 2enby

- so oz pea saese25

auore

oro -0r co oc-or siz Aaazned

9-02 8°0-L°0 of-01 a eras

orozt-0"0e eo ozs oveet ora3e9

esr

(ajo09 se26ve (Saye) (a)_orsen (e109 3 seoanos anpyeay

atirisette> 033 auton stqra39tT89 ore

verauezed uoraonp ?ayun add Loy ATEpOOY vofaanpo2d

woad soBorg TonuLy ? -snpoad seSoTa ?Teuy

seanosea pazyryansepun woay Tey3uased uoyaonpoad seBoTE ?ç STE

---Page Break---

7

governmental regulation, and produced in large amounts

Although only five major sources of organic matter have been

identified, essent

?ly all organic matter

could be a potential fermentative substrate for biogas production.

Optimization and exploitation of additional microenvironments with suitable resources and energy needs also could enhance biogas.

energy production.

Recommended Studies to be Undertaken to Fully Assess the Biogas

Potential.

Resource and Energy Study.

The first step in evaluating the potential for bio-

gas production in Panama would be to make an accurate resource and energy assessment for the entire Country. This study would be subdivided into two sections: 1) resource identification, characterization and supply; and 2) energy requirements. The major objective of the study would be to identify and quantitate all potential resources and energy interface locations within the Nation. This information could be obtained through surveys, site visits and laboratory analysis. A partial list of important physical and chemical parameters to be identified during the study are listed in appendix 3.

Successful collection of this information would document and identify the size, potential and impact of developing the biogas technology in the Country. The information collected also would

---Page Break---

a

assist engineers in matching the biogas plant size to the present and future energy needs of the area.

The estimated time, staff and budget requirements necessary to carry out this study are presented in appendix 5. It is estimated that two staff members could complete this study within one year with an operating budget of \$36,700.

vi Biodegradability Study.

The primary objective of this study would be to determine the

biodegradability rate and biogas production potential for the individual substrate resources previously identified. The biode-

gradability rates could be determined by any of three approaches:

Literature review, *in-vitro* and *in-vivo* assays. A literature review approach would rapidly reveal previous research efforts for common substrates such as animal wastes, thereby reducing the time, effort and costs incurred in laboratory evaluations. Uncommon re-

sources or resources with Limited published data would require biodegradability assays using the in-vitro fiber analysis procedures (6) and chemical determinations (see appendix 3). These procedures are rapid and can be easily performed in analytical fiber and forage laboratories. ?The in-vitro approach is advantageous when compared to in-vivo assays because many different resources can be evaluated rapidly (generally within one week) and economically.

?The disadvantage of this approach is that actual biodegradability is only assumed.

The in-vivo method to evaluate biodegradability of a resource

---Page Break---

19

is to conduct controlled, laboratory-scale anaerobic fermentations and determine the chemical changes and the biogas yield. In this approach the actual biodegradability is determined and the fermentation parameters (i.e., pH, total and volatile solids loading rate, retention time and temperature) are optimized for each resource type. This type of evaluation provides the necessary information to enable engineers to design a biogas plant when supplemented with the data collected in the resource and energy study. ?The disadvantages of this approach are the long time re~

quirements and the high equipment and labor costs. For example, a single substrate could require up to two years to be fully evaluated in a well-equipped Laboratory

Due to time and economic restraints, it would appear most advantageous to perform the literature and in-vitro evaluations first, and then conduct the in-vivo analysis only on resources of major importance

?The estimated time, staff and budget requirements necessary to carry out this study are presented in appendix 6. It is estimated that 1.0 staff member could complete this study within 1.5 years with an operating budget of \$41,620.

Design and Material Study.

?The primary objective of this study would be to educate, select the optimum biogas design, construction materials, and produce working designs for residential, cooperative, community and governmental eized biogas plants in Panama. This relatively

---Page Break---

short study would essentially demonstrate to the engineering staff the various approaches and materials that have been used throughout the World. The information collected along with the engineering skills and knowledge of the economic, cultural and social characteristics in the Country would allow for selection of an optimum system for local use.

Economic and social conditions within Panama would tend to reflect the need for the fermenter to be economical and simple to construct, operate and maintain. The residential fermenter designed and built in the People's Republic of China (g) and India (13) may be best suited for use in Panama. These fermentation systems are generally constructed from locally available materials and at relatively low cost. Construction is also labor intensive and would result in increased employment potential for the Labor force. The plants basically contain a masonry constructed fermenter and biogas storage system. The biogas produced is used primarily for cooking and lighting. Alternatively, the red-mud Flexible line from the Socialist Republic of China is easy to install and can be operated almost immediately. However, the cost of importing the fermenter to Panama may be economically prohibitive. Development of a locally produced, flexible, self-contained fermenter system may be desirable if an economical, durable liner can be produced,

Biogas fermentation equipment has been constructed out of var-

four types of steel, reinforced concrete, ferro-cement, concrete

block and mortar, plastic, glass and flexible covered pits. The

---Page Break---

21

selection of construction materials can greatly influence the cost and economics of the complete biogas system, and should, therefore, be carefully considered at the system design stage.

An ideal construction material would be one which is: locally available; durable and resistant to material fatigue; easily installed and repaired in place with local labor skills. The construction material also should be economical and easily modified.

Pipe lines for

biogas transfer between fermenter, storage

and end-use locations have been made from plastic, rubber, metal

and glass tubing.

portant considerations in selecting the correct tubing would be one which has a minimum of joints which tend to become susceptible to leakage with time. Although conventional standard lengths of PVC piping have been successfully used for biogas transfer, the number of connections required and the detrimental effects of insolation to the exposed pipes may reduce its cost advantages. Continuously extruded PVC pipe, which is buried or protected from insolation and mechanical damage, would reduce the possibility and danger of biogas leaks.

The estimated time, staff and budget requirements necessary to carry out this study are presented in appendix 7. It is estimated that 3.0 staff members could complete this study within 0.33 years with an operating budget of \$21,800.

---Page Break---

22

National Biogas Plan

The primary objective of a national biogas program would be to develop biogas production from underutilized resources for use

as a petroleum substitute in residential areas, cooperatives and small communities with biomass resources, and the industrial and governmental sectors. Secondary objectives would be to: increase the net available energy within the Country; improve the standard of Living for people without electrical power; increase overall national employment; and recycle valuable nutrients present in the fermented effluent and residue. Implementation of this program would reduce the rate of petroleum importation and environmental pollution currently resulting from the direct discharge of wastes into waterways

The national biogas plan should be designed to provide the greatest impact to the areas within the population where the need is the greatest and the technology is most applicable. Three potential targeted areas of impact have been identified: individual residential housing areas without electrical grid connections, water or municipal sewage disposal facilities; cooperatives and small communities with biomass resources; and the industrial and governmental sectors producing sufficient organic matter waste by-products. The rural communities appear to offer the greatest impact potential for this technology

?The national program goals should be to: identify, collate and disseminate vital statistics on the size and description of the currently available underutilized resources throughout the Country

---Page Break---

23

(a List of important physical and chemical characteristics of the resources and the energy needs near the resource areas are presented in appendix 3); determine the energy needs and biogas applications in the targeted impact areas; collect available published information concerning biogas production from World sources (a partial list of potential information sources is presented in appendix 4); identify the biogas production potential of available resources (see appendixes 3 and 4); disseminate available information; educate the targeted area groups of the biogas technology; secure funding and/or establish loan programs from the Government and private sectors to finance actual construction (alternative sources of funding may be obtained through grants or direct loan programs by the U.S. AID, the Food and Agriculture Organization of the United Nations, the World Health Organization of the United Nations, the World Bank and the Caribbean Development Bank); make available designs for cost effective biogas plants; provide information and advise on operating, maintaining and troubleshooting biogas plants; assist in the development of large-scale biogas plants; provide technical assistance to individuals and groups within the targeted impact areas; strive to improve the energy concentration and yield of biogas from available resources; and improve the efficiency of devices using biogas fuel.

The national biogas plan should be designed to increase the knowledge and use of this technology wherever applicable throughout the Country. Seminars, bulletins and public affairs

---Page Break---

2%

advertisements may stimulate interest and development. Attempts to stimulate interest within the universities, technical schools and secondary schools would further result in improved interest, knowledge and development of a biogas resource base

Bionas Projects to be Developed.

Three major areas have been identified where biogas production could impact the Panamanian energy situation. These impact areas are the rural residential family units currently without electricity, cooperatives and small communities with biomass resources and electrical energy limitations, and industrial and governmental sectors with sufficient organic matter resources.

Electricity av

lability within the Nation {s generally confined to the relatively level southern regions along the major roadway. Therefore, development of the biogas technology in areas removed from the grid or future grid areas would appear most desirable. Although hydro resources abound in the western region, electrical development and grid connections may require a considerable time frame in order to connect the rural homes in the mountainous regions. Therefore, biogas development in this area may be applicable

The relative abundance of wood, compared to the low population densities in the eastern region, tend to support the continued use of wood for cooking. However, since biogas can be used for lighting and refrigeration (1), development of this technology in this

---Page Break---

25

area may also be desirable. The northern coastal region, which has limited electr:

al resources, also appears to be a region ideally suited for the residential and community development of the biogas technology.

The western and northern regions of Panama and the more arid southern region appear to be best suited for development of

biogas technology

Residential Biogas Project

The rural residential housing areas appear to offer the greatest opportunity to impact upon the largest population (46%) within the Country. In order to develop this area, a residential biogas project is proposed. The objectives of the project are to educate the rural community of the importance and benefit of the biogas technology and to install regional demonstration biogas plants at homesites. The design to be used for these biogas plants should be as economical and as simple as is technically feasible.

The biogas produced in the residential units would most easily be used for cooking, lighting and refrigeration. Simple and cost effective designs for burner and mantle lamp construction have been reported (8,13). Since 70% of the energy needs of rural Panama

is derived from wood, the biogas technology could greatly reduce overall wood consumption and cost. Also, the use of readily available underutilized resources (i.e., human and animal wastes and plant biomass) would reduce labor requirements currently expended

---Page Break---

26

for wood collection or charcoal production and distribution.

The fermented residue and effluent from the anaerobic fermentation have good nutrient and irrigation value (1,8). These by-products should be recycled upon the soil to increase crop Productivity, which is not possible when wood is directly combusted, since most of the nitrogen is lost to the atmosphere.

Public health hazards can occur when human waste is used in biogas fermentations or the residue and effluent are used as fertilizer and irrigation water, The Academy (1), however, states

that in spite of the eu

ival of some pathogens and parasites,

the Literature documents no disease outbreaks associated with the

use of digested night s

and animal wastes in erop production.

Furthermore, they state that the inhabitants of most vil-

lages or rural areas in developing countries are probably already

exposed to the enteric diseases indigenou s to their area, The

introduction of anaerobic digesters for night soil or animal

wastes, therefore, should not create any new or additional health

hazards; on the contrary, it should reduce the present health

hazards significantly (1).

?The rural biogas fermentation system generally contains the

fermenter, biogas storage container and the piping connections

necessary to complete the system. An economical, durable and

simple design should be used. The design should attempt to reduce

material deterioration (i.e., metal rusting), biogas loss due to

leakage, fermenter contents leakage and feed and effluent line

---Page Break---

27

plugging. The unit should be sited to take maximum advantage of gravity feeding whenever possible, and installed in such a manner (G.i.e., underground) so that the agricultural productivity of the biogas plant land area is not lost. The fermenter should also be situated away from water supplies to reduce the potential of water contamination. The Chinese design constructed from masonry materials appears to be the most desirable fermentation system for immediate construction in Panama

Two construction methods can be employed to develop this

project: an individual approach where each recipient of the fer-

mentation plant constructs the system from a common design; or an assembly line approach. The estimated resources necessary to develop the individual construction program would be core staff mem-

bers to develop t

design and educational materials, field staff

members to transfer the technology in actual demonstration pro-

grams, and capital to partially subsidize the biogas plant construction. The subsidy program should have within its design a means of collecting the money loaned so that future units can be constructed.

The estimated time, staff and budget requirements necessary to carry out this project are presented in appendix 8. It is estimated that 11 staff members could complete this project within 3.0 years with an operating budget of \$996,380.

Cooperative and Community Biogas Project

Many agricultural cooperatives and small communities exist

---Page Break---

28

throughout the Nation. These groups have the advantages of increased labor supplies, land resources and capital, which could be directed toward construction and operation of a centralized biogas plant. This type of centralized plant would be more cost effective due to the benefit derived from economy of scale, also

the distribution of the biogas could affect a greater number of

people within a given area.

The primary objective of the project is to establish commun-

lized

ity-sized biogas plants throughout the Country.

Secondary objectives of the project are to increase the standard of living in the targeted areas, the stability of the economy, and

reduce environmental pollution

resulting from the direct discharge

of the underutilized resources:

In order to accomplish the project objectives, the following tasks have been identified: quantitate and qualitate the characteristics of the cooperatives and small cities, identify the energy needs and substrate resources in these areas, design the biogas system to best accommodate the area, conduct an economic and social impact evaluation of the proposed project and construct the system, Af the previous evaluations were positive.

The goal of the project should be to establish a minimum of one plant per province to act as an educational and demonstration facility.

The estimated time, staff and budget requirements necessary to carry out this project are presented in appendix 9. It is

---Page Break---

29

estimated that 5.0 staff members could complete this project within 3.0 years with an operating budget of \$784,630.

Industrial and Governmental Biogas Project.

Certain industrial and governmental sectors within the Nation have resource potential for biogas production. The biogas produced at these locations could easily be used to replace a portion of the costly petroleum fuels currently used. A partial list of industrial and governmental residues with biogas potential is given in table 5. Therefore, the goal of the industrial and governmental biogas project should be to educate the respective groups and to promote biogas production within these sectors.

The estimated time, staff and budget requirements necessary to carry out this project are presented in appendix 10. It is estimated that 2.0 staff members could complete this project within 2.0 years with an operating budget of \$109,000.

Specific Recommendations

The following specific recommendations are made:

(1) TRUE should continue to develop and promote biogas

technology within the Republic

(2) IRHE's program should be expanded to include a resi-

dential biogas project, a cooperative and community

biogas project, an industrial and governmental

biogas project, and energy studies.

(3) IRHE should expand its biogas program by including

individuals from academic, private and govern-

mental sectors.

---Page Break---

30

(4) IRHE should attempt to stimulate biogas construction and demonstration units throughout the Nation.

(5) IRHE, in cooperation with the academic sector, should develop teaching aids and regional conferences to edu-

cate the citizens of this alternative energy form.

CONCLUSION

The advantages of developing biogas production in Panama are the year-round tropical environment, which is conducive to opti-

mum biomass growth, high insolation levels, relatively low Labor costs, available labor force, a genuine need for the energy in areas not serviced by the electrical power grid and a lack of Known petroleum or coal resources, Development of this technology would increase the standard of living in rural areas and retain the national currency within the local economy by reducing petroleum expenditures to foreign countries.

The most advantageous approach to biogas production in Panama should satisfy the below listed criteria. The biogas system should be economical: simple to construct and operate; incorporate gravity feeding and effluent and digested residue removal and secondary use as a feed and/or fertilizer; provide manual agitation capability or mechanical agitation by wind or water driven impellers; use solar heating by thermosyphon to maintain optimum fermentation temperatures; insulated to reduce heat losses; minimize the use of and loss of dilution water

---Page Break---

31

from the system, and recover and use the valuable nutrients in the digested effluent and residue. In addition, the construction requirements should use skills that are already present within the

society or can easily be learned. Education of the citizens to the background theory and practical operating requirements for the anaerobic fermentation process would greatly increase bio-gas development success.

Biogas production and use can improve the standard of Living within the Country. However, the bio-gas technology may not be the complete answer to solving the energy shortage and distribution Limitations within the Nation. However, for today, and the near future, this technology appears well-suited for use in the Republic of Panama

ACKNOWLEDGMENT

The technical assistance of engineers B, A. Martinez and 1, Bryson is greatly appreciated.

This work was performed for the Republic of Panama, contract number 31-80-DG, project for the master plan for the development of the renewable energy resources in Panama, ?This work was funded in part by @ grant from the United States Agency for International Development, contract number 5250207, through the University of Delaware, in cooperation with the University of Puerto Rico.

---Page Break---

32

BIBLIOGRAPHY

Ad Hoc Panel. 1977. Methane generation from human, animal, and agricultural wastes. National Academy of Science, Washington, DC,

Anonymous, 1980. Consumo de energia electrica in la Republica por Provincias afos 1974A1979. IRHE, Direccion de desarrollo, departanento de energia Y tarifas, seccion de estadisticas.

Anonymous, 1980. Red-mud plastic material methane convert-

ex. Lupton Engineeri

Corp., 803 World Trade Building.

50 HSIN S Heng S. Ré., Sec. 2, Taipei, Taivan.

Anonymous. 1981. Biogas Plant, Eastbourne Lane, Midhurst, Sussex.

Bryant, M. P. 1979, Microbial methane production - theoretical aspects. J. Anim, Sei., 48:193-206.

Chandler, J. A., W. J. Jewell, J. M. Gossett, P. J, Van Soest and J. A. Robertson, 1980, Predicting methane fermentation biodegradability. Biotechnol. Bioeng. Symp. 10:93-107

Erdman, M.D., B.A. Erdman and R. Paton, 1981. Energy-integrated farm-scale anaerobic fermentation system. Abs., Tard Ann. Mes. Amer. Soc. Animal Science. North Garolina State Univ.

Food and agriculture organization of the United Nations. 1978
China-Azolla propagation and small-scale biogas technology.

FAO soile bulletin. 81 pp.

---Page Break---

10.

a.

12.

13.

1,

33

Fry, J. L. 1976. Practical building of methane power plants.
Standard Printing, Santa Barbara, CA

Hashimoto, A. G., ¥. R. Chen, V. H. Varel, and R. b, Prior
1980. Anaerobic fermentation of agricultural residue. In
Utilization and Recycle of Agricultural Wastes and Residues,
M.-L. Schuler (Ed.), CRC Press, Ine., Boca Raton, FL.

Noack, W. 1955. Biogas m der Landwirtschafte, Elsner,
Dormstadt.

Pfeffer, J. 1978. Biological conversion of biomass to
methane. U.S. Department of Energy, Contract EY-76-S-02-2917.

Singh, R. B. 1971. The biogas plant, generating methane from
organic wastes, gas research station, Ajitmal, Etawah, U.P.,
India.

Stafford, D. A., D. L. Hawkes and R. Horton. 1980. Methane
Production from waste organic matter. CRC Press, New York,
NY. 264 pp.

---Page Break---

March 23,

1981

23 -

24 -

25

26 -

27 -

28 -

38

Appendix 1 - Itinerary

Travel to Panama City, Panama

Met with Drs. K. Soderatrum and R. Lompart to
discuss project and work plan

Met Ing. B. Martinez and travelled to Santiago

Worked at IRHE - Santiago

TRIE

Interviewed Dr. R. Preto Malea

National Aquaculture Director

NIDA

Santiago

RHE

Rae

Visited IRHE flexible biogas plant construction site

Interview and site visit - Ing. M. Seiplay

Nestlé Co.

Nata, Coclé

Biogas digester aquaculture pond

Instituto Agropacreatario Jesus Nazarano

Atalaya

Site visit - 2 dairy farms in Santiago

Site visite

State operated duck farm (Bontyo)

Site vitit - Santiago municipal slaughterhouse

TRHE

Returned to Panama City

---Page Break---

29

30

aL

April 1, 1981

2

3

Site visit -

Open

TRE, Panama

TRH, Panama

IRHE, Panama

TREE, Panama

Canal Zone

city

city

caty

city

35

---Page Break---

36

Appendix 2

Sites Visited

Nestlé Company

Ing. Martin Seiplay

Jefe Depto. Tecnico

Cia. Pananena De Alimentos

Fabrica De Nata

Nata. Prov. De Coclé, R. De Panama

?The Nestle Company has two plants within the Republic of Panama (Los Santos and Nata), The products produced are canned condensed milk, tomato products, vegetables and soups. The plant can

process 200,000 lit

of milk/day. Currently the plant is running at 67.5% milk capacity due to low milk production. The site has 1500 Ki installed electrical eapacity (IRHE) and Ss using between 60-70% of the installed capacity. The plant operates 24 hrs/day year-round. Bunker fuel (1135.6 iters/day) is used to fuel the steam generators at the plant. The plant also has an 800 and a 400 KW diesel backup generator to operate when the grid fails, The two factories employ 1000 personnel during maximum production periods and the overall plant in Nata is operating at 60% of capacity during the harvest seasons

?The plant in Nata does produce wast:

however, all of the waste

is returned to the adjacent farms and used as an animal feedstuff

Low temperature solar collectors appear to be the best method

to impact upon the energy demands of the factory. Also, the

---Page Break---

37

reduction in use of artificial lighting would reduce electrical

demand

Thursday - Site Visit - Instituto Agropacreativo Jesu  Nazarano

Atalaya

This institute is a parochial high school and an agriculture

training center where students come and live during class periods

The students are also trained on the farm operations connected with

the school. The students live and eat at the school in a dormitory

environment. Student numbers vary from 130-160 students.

In order to reduce costs and to recover energy in the waste,

an anaerobic digester was constructed and began operation in Octo-

ber 1979.

?The school maintains 2 34 sow farrow to finish farm. Swine waste (SW) is manually flushed from some of the pens into a settling tank (2.24 m³), The settled solids are then diverted into another tank for further solids separation. The supernatant is drained to an aquaculture pond and the solids are added to the fermenter. The second tank is flushed 12-13 times/day and the solids added to the fermenter. The fermenter (14.0 m³ waste capacity with 4.0 m³ gas storage) consists of a cylindrical concrete tank buried in the ground with a floating metal cover. A 16 m³ waterluted gas holder

s also used for gas storage. Following digestion the fermented solids are retained in a sack filter and the effluent enters the aquaculture pond. The pond is stocked with tolepia and carp and is drained, harvested and cleaned annually. The fish are

---Page Break---

38

consumed at the school or sold. The small fermenter capacity is insufficient for the herd. A second fermenter (red-mud plastic) has been ordered and is currently awaiting arrival and installation

at the site. The added capacity will give greater gas production potential to the school; currently an estimated 90% of the cooking is conducted with biogas. The added capacity would be used for cooking and for operating internal combustion engines.

?The school staff are proposing to compress and use the extra biogas in mobile engines, which does not appear to be energetically efficient. It would also appear that since so much labor is used in separating the solids by settling, it may be simpler to collect the solids by hand and add them to the final separating tank. This would decrease € usage and probably reduce production costs since swine normally defecate in one area of the pen.

The mariculture pond at the farm receives the digested effluent. The pond is 400 m² and is 1.5 m deep in the center and 1.25 m deep at the edge. The pond density is 2.5 fish/m.

Dairy Farm Visits.

Two dairy farms were visited near Santiago. The first farm was an unautomated farm, which had a 45-cow milking population. The cows were individually roped and brought to the milking area, The

cow's calf was then released and allowed to suck until milk let down occurred at which time the calf was tied and the cow milked by hand. The milk was then transferred to milk cans and left alongside the road for pickup and transportation to the Nestlé Company. The cows

---Page Break---

39

were then placed out on pasture until the next milking period

This farm used no electricity and the small amount of waste collected in the corral area was deposited near the parlor.

The second farm was semi-automated and consisted of a 4-cow milk parlor. A single electrically driven vacuum pump connected to 4 bucket milkers was used at the farm. Following milking, the milk was transferred to milk cans for transportation to the processing plant.

A third dairy was observed in which the cows were herded and milked by hand. The milk was placed in the bulk cans and transported by horseback to the roadway for truck transportation to the

processing plant.

Although cattle produce an estimated 1.29×10^6 Kg of waste annually, current cattle husbandry techniques in Panama do not result in a concentrated waste problem. The only periods when collection would be feasible is during the milking period. All other times the animals are generally on pasture, which makes collection impractical

A state operated duck farm (Montjo) was visited. The operation maintained a 200 head duck flock. The objective of the farm was to educate and develop a duck population within the Country. Waste from the site was collected periodically from the ground and could be used for biogas; however, the small flock population and long exposure time to the environment would result in nutrient losses

The Santiago municipal slaughter plant was also visited. The

---Page Break---

40

plant processes 90 head daily (cattle and swine). All blood, feces, rumen and intestinal contents are flushed into an anaerobic lagoon. The plant employs 30 workers and 10 administrators and operates 6 days a week. The plant consumed 12,080, 12,400, 11,360 KW of elec-

tricity during August, September and October, respectively. The plant also used diesel fuel to power some of the equipment.

This plant appears to offer great potential for biogas production. A careful analysis of the power requirements and demand

periods would define the biogas impact potential for the facility.

Also an analysis of the biodegradability of the waste stream would

be needed to fully estimate the biogas production potential

A floating cover over the existing lagoon would probably provide

the simplest solution for the fermenter. If biogas production

was sufficient, the gas could be used for hot water/steam production

or refrigeration. Use of the gas for electricity is also a

potential since the plant uses about 520 KW of electricity/day

If the demand is relatively constant, a 75 KW generator would be

able to meet this demand.

---Page Break---

aL

Appendix 3. Physical and Chemical Survey of Available Resources

Waste Characteristics

Amount produced/time

Total solids

Volatile solids

Ash content

Mineral composition

Total nitrogen content

Ammonia nitrogen content

Total carbon

Inorganic carbon

Organic carbon

pH

Bop

cop

Gross energy

Amino acid profiles

Mineral composition

Viscosity

Particle size distribution

Lignin content

Cellulose content

Energy Needs

Kil electrseity

Peak power demand

Power denand profile/unit

Steam or hot water requirements

Other

1. Land area available for biogas plant

2. Potential funding sources

3. Current waste disposal history

4, Discharge locations

5. Proximity to other buildings,

residential areas

---Page Break---

42

Appendix 4. Sources of biogas information

Libraries

Journals

Biotechnology and Bioengineering

Compost Science

Conservation and Recycling

J. Animal Science

Poultry Science

Transactions of the American Society of Agriculture Engineers

Agriculture Experiment Stations in the United States, Canada,

United Kingdom, India, Taiwan

Commercial £4

ms produc:

4 biogas production

Biogas of Colorado, Inc.

Sheaffer and Roland, Washington, DC

Hamworthy Engineering Led., U.K.

The Energetic Hog, P.R.

Hamilton Standard, Tne.

Koplan Industries, Bartow, FL

Commereial human waste treatment firms

Organizations

National Academy of Sciences, U.S.

Department of Energy, Washington, DC

39

---Page Break---

Appendix 5.

Objectives:

Duration

Staff =

Budget

43

Resource and Energy Study Requirements

Identify and quantitate all potential biogas
resources and energy requirements and energy
interface locations within the Nation

1.0 years

2.0 ~ Formal education to include @ degree in Science
and/or engineer. Prior experience in energy auditing

techniques and anaerobic fermentation techniques

Salaries and wages \$20,000.00

Equipment

Drying oven 1,000.

Muffle furnace 3,000.

Portable pil meters (2) 1,200.

Chemical analysis 5,000

Office supplies 1,500.

Travel,

Domestic (2 vehicles) 5,000.

?Total \$36,700

---Page Break---

4h

Appendix 6. Biodegradability Study Requirements

Objectives: Determine the biodegradability rate(s) and biogas production potential(s) of identified resources

Duration : 1.5 years

Staff: 1,0 - Formal education to include a degree in bio-chemistry or bioengineering. Experience in anaerobic microbiology techniques and assay procedures.

Budget: Salaries and wages \$18,000.

Equipment

Large water heating/cooling bath 3,500.

Jer fermenters/tubing/glassware 5,000.

pH meter 700.

Balance 2,500.

Laboratory contingency 1,170.

Chemical analysis (commercial) 8,000.

Office supplies 1,500.

Travel

Domestic

Literature searches, photocopy fees

Total 941,620.

---Page Break---

Appendix 7.

Objectives:

Duration

Staff

Budget:

45

Design and Material Study Requirements

Educate engineering staff; select the optimum biogas design and construction materials; and produce working designs for residential, cooperative, community and governmental sized biogas plants

0.33 years

3.0 - Formal education to include engineering degree and applied microbiology degree. Drafting and

knowledge of culture characteristics desirable.

Salaries and wages \$19,800.

Office supplies 2,000.

Total \$21,800.

---Page Break---

Appendix 8

Objectives:

Duration,

Staff

Budget

46

Residential Biogas Project Requirements

To educate the rural community of the importance and benefit of the biogas technology; installation of regional demonstration biogas plants at homesites

3.0 years

11 = 1 coordinating and education staff member to be formally educated in engineering and bioengineering technology; 9 regional field staff members to work

in each province. Regional field staff members to have formal education in engineering and training and

experience in biogas technology. The field members
WLLL secure participants, adapt biogas designs for use
at specific homesites, supervise construction, opera.
ting techniques, biogas plant maintenance and repair
and be capable of trouble-shooting field problems.

1 secretary.

Salaries and wages

Coordinating and education staff member

(\$20,000/yr) \$ 60,000.

Regional field staff (\$10,000/year) 330,000.

Secretary (\$6,500/year) 19,500.

Equipment

Office supplies (\$20,000/year) 60,000.

Portable pil meters 5,400.

Construction tools (tapes, saws, shovels,

trowels, etc) for

member 4,500.

?Transportation

Vehicles (10) 100.000.

---Page Break---

7

Subsidy loan program, assuming an \$800

material cost/residential biogas plant,

50% loan from the government, and the

construction of 10, 20 and 30 residential

biogas plants in years 1, 2 and 3 for

each region 216,000

Subtotal, 905,800.

Contingency 90,580,

Total 9996, 380.

---Page Break---

Appendix 9.?

Objective

Duration

Staff

Budget

48

?Cooperative and Community Biogas Project Requirements

Establish community-sized centralized biogas plants

in each province

3.0 years

5 - 1 coordinating and education staff member to be

formally educated in engineering and bioengineering

technology: 3 regional field staff members, each to work

in a3 province area, Regional field staff members

to have formal education in engineering and training

and experience in biogas technology. The field members will secure project participants, adapt biogas design for use at specific cooperatives and communities, supervise construction, operating techniques, biogas plant maintenance and repair and be capable of trouble-shooting field problems. 1 secretary for main office.

Salaries and wages

Coordinating and education staff member

(\$20,000/yr) \$ 60,000.

Regional field staff (\$10,000/year) 90,000

Secretary (\$6,500/year) 19,500

Equipment

Office supplies (\$10,000/year) 30,000

pH meters 1,800

Construction tools (tapes, saws, shovels, towels, transits for each regional staff member) 4,000.

?Transportation

---Page Break---

Appendix 10.

Objective

Duration :

staff

Budget

49

Industrial and Governmental Biogas Project

Requirements

Educate the industrial and governmental sectors of
the potential impact of the biogas technology to
their individual operations

2.0 years

2.0 - 1 coordinating and education staff member to
be formally educated in engineering and bioengineer-

ing technology. 1 secretary.

Salaries and wages

Coordinating and education staff member

(\$20,090/yr) \$ 40,000.

Secretary (\$6,500/yr) 13,000.

Equipment

Office supplies and training aids

(\$20,000/yr) 40,000

Transportation

Vehicle (1) 10,000.

Fuel and maintenance (\$3,000/ye) 6,000

Total \$109,000

---Page Break---