

1978

---Page Break---

Part I.

Part 11,

Part IT,

TOXIC METALS IN THE ATINSTHERE

by

Fausto J. ?fuioz-Ribadeneira, Tin Mo, and M.J. Canoy

Nondestructive multielenent instrumental neutron activation
analysis of toxic metals in the atmosphere of southern
Puerto Rico

Tin Mo and J. Canoy

Applications of atomic absorption spectrophotometry for the
analysis of toxic metal concentrations in the atmosphere of
the South and west coasts of Puerto ico

Fausto J, Muñoz-Rivadeneira

Preliminary survey of the concentrations of trace metals in the atmosphere of eight selected sites in southwestern Puerto Rico

Fausto J, Muñoz-Rivadeneira

---Page Break---

PART 1

[NONDESTRUCTIVE MULTIELEMENT INSTRUMENTAL NEUTRON
ACTIVATION ANALYSIS OF TOXIC METALS IN THE ATMOSPHERE
(OF SOUTHERN PUERTO RICO

by

Tin Mo and M..

---Page Break---

Figure 1.

Figure 2,

Figure 3.

Figure 4,

Figure 5.

Table 1.

Table 2.

Part I

LIST OF FIGURES

Air particulate sampling stations in southern Puerto Rico

(971 = 1972)

Gama ray spectra of irradiated air particulate sample five
minutes after irradiation

Gamma ray spectra of irradiated air particulate sample one day
after irradiation

Gamma ray spectra of irradiated air particulate sample one month
after irradiation

Variations within a day of elemental concentrations in the
atmospheric aerosols of San German, Puerto Rico

LIST OF TABLES

Production and decay characteristics of nuclides of metals of
interest observable with Ge(Li) detectors in neutron irradiated
atmospheric aerosols

Concentrations of metals in aerosol samples taken November 10-25,
1972, San German, Puerto Rico

---Page Break---

INTRODUCTION

During the past several years there has been increasing concern with

environmental problems. These problems were ushered in by a rate of technological Progress not in harmony with nature, In the attempt to cope with the demands for improved standards of Living, sound ecological planning was overlooked. | In particular, the quality of the air necessary for the sustenance of life has Suffered from the encroachment of industrialism and urbanization. For this reason, techniques to measure toxic compounds in the atmosphere have been developed.

Malignancies and other deleterious effects induced by the carcinogenic and synergistic action of varying levels of different metals on humans are discussed in detail by Mlamilton (1934), Elkins (1959), and Lee (1972). Data on the levels of these pollutants in the air are necessary before they can be judged hazardous. ?After collection of these data, their relation to statistical data on public health problems in Puerto Rico?can be studied.

This study is concerned with the metallic elements Ni, V, Mn, Sb, Se, He, Pb, Cd, and Cr. These metals are being introduced into our atmosphere by industry, automobile exhaust emissions, the burning of municipal wastes, building construction, and agricultural insecticides, and are considered hazardous when they reach certain levels of concentration.

?The study of aerosols and atmospheric particulates is not an easy task because of problems in the collection and analysis of samples and in the interpretation

of results, No single analytical method can cope with all the problems involved, including sufficient speed to deal with air pollution emergencies. The instrumental neutron activation analysis (INAA) method that is being adopted and developed in our laboratory is described. This method is quite accurate and sufficiently sensitive for the determination of almost all the metals with which we are concerned, This technique has great potential usefulness, particularly?

For several metal concentrations (V, Mn, Al, etc.) can be determined within about

an hour after receipt of the samples. Thus, the method can be applied rapidly to indicate pollution crises and to suggest the most serious contributors to the crisis.

For most studies of atmospheric particulates, samples are collected on filters or in particulate impactors. Many of the analytical methods require dissolution of the sample followed by chemical and instrumental analyses. A serious shortcoming of such methods is that dissolution and subsequent wet chemical steps may introduce large errors, either by loss of material or contamination of the sample. The sample materials themselves, especially pollution aerosols, are generally insoluble in water since the majority of them are carbonaceous and may even be refractory (Junge 1963), West and coworkers (1966) stated that even with the use of strong acids, ion exchange of trace metals with glass and plastic containers may be quite severe, West (1968) and Christian (1969) showed that matrix effects in many of the usual analytical methods (e.g. emission spectrography, atomic absorption, or microchemical techniques) may be serious if particulate material and/or interfering ions are present.

Activation analysis has not been commonly used in atmospheric studies. The pioneering work was done mostly by Winchester and coworkers (1947) who applied

---Page Break---

Radiochemical techniques to study mainly the halogens Na, V, and Cu in the atmosphere, ocean, rain, and snow. Brar et al. (1969) used NaI(Tl) detectors without chemical separations to measure the concentrations of several elements in aerosols from the Chicago metropolitan area. Ducey et al. (1969) observed gamma rays from irradiation products of about 23 elements in Ge(Li) gamma ray spectra of marine aerosol samples after chemical removal of Na and additional ion exchange steps. Dans et al. (1970, 1971), Gordon et al. (1971), and Tuttle et al. (1971) then successfully applied a nondestructive multi-element neutron activation analysis procedure to determine up to 33 elements in air pollution.

EXPERIMENTAL METHODS

The method adopted follows quite closely the procedures employed by Dans et al. (1970). This method involves collecting aerosols from 5 to 15 m³ of air on a filter and irradiating the filter with nuclear reactor thermal neutrons to determine concentrations of all metals under study, except nickel. To measure

Ni concentrations, the fast neutrons of the reactor were used to effect the $^{58}\text{Ni}(n,p)^{58}\text{Co}$ reaction. The ^{58}Co gamma rays were detected to determine nickel concentration. The gamma rays from all the irradiated samples were observed with high resolution Lithium-drifted germanium, or Ge(Li), detectors.

Ling Procedures

Eight air tape sampling machines (Bendix Corporation Model No. 23000 paper tape samplers) were placed at six different locations around the south coast of Puerto Rico. The sampling stations were diverse with respect to the density of population, industrial plants, and automobile traffic. The exact locations were given in the Aguirre Power Project Environmental Studies Annual Report for 1971 and are shown in Figure 1.

Atmospheric aerosols were collected on a filter paper tape by drawing air through an electric vacuum pump. Air particulates were collected on a circular spot (1.27 cm²) on the filter paper. The filter paper used (Rendix Corporation Catalog No. 6102, acid-washed paper, type W-41) has high collection efficiency for particulate material down to the 0.1 μ m range. The paper also has fine chemical quality and purity, so that the interferences or contributions from superfluous background concentrations of the trace metals in the blank samples are kept to a minimum or essentially to zero.

Each paper tape sampler had an automatic tape advance and clamping system. The machine cycle was adjusted so that every 20 hours the incoming air would pass through a fresh part of the air tape assuring an average air flow of 11 Liters/minute. The amount of pollutants collected during periods of 8, 12, and

24 hours made up a sample for Neutron activation analysis." in this way 1e° was
Possible to observe variations in the concentrations of the contaminating metals
Within one-day and to measure the average daily concentrations of the contaminants
in the air at different sampling stations and under varying meteorological conditions.

---Page Break---

Ze6k ~ 146 ?suoraeas Buytdwes oaeoyaaed ayy *1 RITE

1S Nyaeetev>

Jus SANVTU GAOg ENO aus ooymay

\

?_z?

NYEDC 2uNWuy

---Page Break---

Laboratory Procedures

Preparation of Samples for Irradiation

Samples. Plastic gloves and stainless steel surgical scissors were used to cut out a piece of the air tape containing four spots of air particulates (corresponding to 8 hours flux of air or 5.28 m³ of air collected). The sample was then placed in a 7 cm diameter Petri dish and dried under a heat lamp. After cooling in a desiccator, the sample was weighed and sealed in a small polyethylene snap-top irradiation vial (10 mm x 25 mm, Bel Art Plastics Co., Pequannock) which had been washed with a warm 1:1 nitric acid-sulphuric acid solution and de-ionized distilled water. The polyethylene vial was then heat-sealed with a heated quartz tube. The outside of the vial was washed with warm nitric acid-sulphuric acid and de-ionized water and wiped dry. The sample was then placed inside a clean plastic bag.

Blanks, Blank samples were prepared in the same manner.

Standards: Fifty microliters each of well-titrated mixtures of the appropriate elements were deposited on each piece of clean paper tape (approximately the same length as the samples and blanks), allowed to dry and cool, then weighed and sealed inside the irradiation vials. One standard consisted of 0.1 micrograms each of the elements vanadium and manganese which gave, short-lived fission products upon neutron irradiation. Another standard consisted of 0.1 micrograms each of arsenic, chromium, selenium, mercury, nickel, cobalt, and silver which yielded longer-lived radioactive species upon neutron irradiation.

Irradiation and Counting Procedures

The irradiation and counting scheme given by Dans et al. (1970) was followed.

For the analysis of elements giving rise to short-lived isotopes, samples, standards, and blanks were irradiated for five minutes in a flux of about 10^{13} neutrons/cm² in the Puerto Rico Nuclear Center reactor's fast transfer rabbit irradiation facility. Because the neutron flux from one irradiation to the next could not be assumed to be constant, an accurately weighed titanium standard wire was coirradiated with each sample to serve as a flux monitor. These wires were taped to the sides of the irradiation vials before they were encapsulated inside the outer irradiation rabbit.

The short-lived gamma ray nuclides ²⁸¹Pb, ²¹²Pb, and ²¹⁴Pb were detected in the irradiated samples about three minutes after irradiation by counting for 400 seconds live-time with a large, co-axial detector of effective volume 26 cm³ (Canberra) coupled to a 1024 channel analyzer (Packard). The flux monitors were counted for 20 seconds each. Then the samples were counted again for 1000 seconds live-time 15 minutes after the end of irradiation.

Another set of samples with appropriate standards and blanks was irradiated for five to eight hours and counted at decay-times of one to two days for 2000 seconds live-time to determine the elements As, Cu, Zn, and Sr. To determine the elements Ni, Co, Zn, Ig, Se, Cr, As, Sd, Sc, and Fe (which give rise to long-lived nuclides), the same samples were counted for either 100 minutes live-time (high activity samples) or for 1000 minutes live-time (low activity samples) after 10 to 30 days of cooling. For the long irradiation, the irradiation vials were

---Page Break---

encapsulated inside an aluminum canister provided with a screw cap and lowered into the irradiation position on the periphery of the reactor core. The aluminum canister was rotated during irradiation to effect normalization of the neutron flux received by the samples.

After irradiation and cooling, the paper samples were transferred from the snap-top vials to clear plastic vials to be counted for different live-times on the Ge(Li) detector. The resolution of the Ge(Li) detector used in this study was 2.3 keV full-width at half maximum (FWHM) of the photopeak produced by 1352 keV gamma rays from ^{60}Co . The peak to Compton ratio was about 16.

DATA REDUCTION,

Presence of Isotopes

Radioactive nuclides were identified solely on the basis of energies and half-lives of the photopeaks. Comparison of the gamma ray spectrum of the unknown sample with that of the standard sample and prior calibration of the gamma spectro-

meter with standard sources of known energies facilitated the identification of radioactive nuclides in the irradiated samples. Most radioactive species emit several gamma rays, so the intensity pattern of the several gamma rays can be utilized for very clear identification in those cases. The importance of accurate determinations of gamma ray energies must be emphasized. Gamma ray energies of nearly all (n,p) products of reasonable half-life have been accurately determined, nearly always to ± 0.5 keV and often much better (Table III in Gordon et al. (1968) and Table 1 in this report). If one can determine the gamma ray energies of photopeaks in spectra of the unknowns to ± 0.5 keV or better, there is little ambiguity in the assignments of the gamma rays to particular radioactive nuclides. For identification of species, the spectra were analyzed by hand, in which case it was assumed that the energy versus channel number calibration curve is linear over small energy regions.

Figure 2 represents the gamma ray spectrum of an air particulate sample irradiated for three minutes and after five minutes decay. Since from the end of irradiation. The spectra were dominated by 2.3 minute ^{214}Pb , 3.8 minute ^{214}Bi , 17.6 minute ^{214}Po , and 2.58 hour ^{210}Pb .

Figure 3 shows the gamma ray spectra of air particulate and blank samples (which were co-irradiated for five hours in a fluence of about 10^{20} neutrons/cm² and at a decay time of 24 hours from the end of irradiation. The 35.3 hour ⁶⁰Co and 15.0 hour ²⁴Na photopeaks dominate the spectrum of the irradiated air particulate. The gamma ray spectrum of the irradiated blank samples shows no photopeaks of appreciable magnitude corresponding to those in the air particulate sample except for the 511 keV annihilation and 1308 keV ²⁴Na peaks. This attests to the chemical purity and purity of the paper tapes used for collecting aerosol samples:

Photopeaks produced by nuclides with half-lives up to 12 years (¹³⁷Cs) are observed in the spectrum of Figure 4, taken 36 days after a long irradiation (five hours) of an air particulate sample. Even though most of the peaks are well

7

---Page Break---

page 30

0 30

hy 04 WD oe, aan

94 9"Udz)8sç 84 Hat posestoa

siquatasyo asoaout

?nw

sua2ads 942 uo post uoy329110>

2X 1602) Stkgys BratsousoulN 34

1 Yo Zou9pduou3 paueago wae

wauou 4 ave suit wus out 245 2

awe 4 998 25,800 wt ey 2s

woe zsz? 8601 adgchtP St iy a a

dep: or asta ?t59

uo | suit eer ?yy ?

puou ow wo By 1K

?vow 1 s09 ve sera \$421

?pan | Ws stis sit s

wauow ozs wy 245 2

uo sit SigeAOP cw UNE oT

wwe svt our Oss 50 UL ast ao 3s

? sum 3407

soanaqe 07-0 ei roy rs ous "95g 9

sano 4 st gst 9st out Yigg 4

soamutu 02-0 er Jegutaue?s at Ms \

serrwyy 02-0 su WYgHtH '2 vot We y

sumy Laos

Buyrumo 103 say ?won :

speust ia3ye_-eururnnay 0} soupunge altos

aula asaq syealoiaw soy 839531 optim sonpany ?Seoaosy??GebseL uaa

---Page Break---

UOT3elpLZY Joye soumuTu oATy oTdues openoTased Te porerpexit 30 wsrseDs dex wD *2 SDI

---Page Break---

vorawrpexar-soa3e Ap ouo oqdaws ozetnotzied rye poseypessy 30 exazeds dex eum) *ç aUROLE

10

---Page Break---

woraeypeasy 10358 (puow ouo oTdues oreqnoyaied sy poeypeLsy Jo eiz0eds Aer mE) ?» BUDTA

/

only vB,

come

---Page Break---

resolved, the spectrum is quite complicated up to 347 keV. The strongest peak in the low energy part of the spectrum is the 320 keV line of ^{51}Cr . The predominant peak in the medium energy part of the spectrum (500 to 800 keV) is the 602 keV ^{125}Sb photopeak. In the high energy region (800 to 1500 keV) ^{137}Cs , ^{60}Co , ^{228}Ac , and ^{228}Pb

dominate the spectrum,

Calculation of Net Peak Areas

Areas of the photopeaks were determined by summing the counts in the channels of the peaks and subtracting a smooth background determined from the channels on each side of the peaks (Covell 1959).

Conversion of Peak Areas to Weights of Trace Metals

The amount of a given element in a sample was calculated from the ratio of

the peak areas in the sample spectrum to the areas of the corresponding peaks for the client's irradiation products in the standard sample's spectrum. Because of variations in background activity under the peaks and possible changes in peak width due to high count rates or gain shifts, net peak areas rather than peak heights were used for quantitative assays. Corrections were applied for decay between the counting times of samples and standards. As often as possible attempts were made to deposit amounts of standard solution on comparison standard paper tape that gave counting rates similar in order of magnitude to the samples. This enabled the use of the same counting positions at about the same counting rates for both samples and monitors. It was reported by Gijhels et al, (1968) that errors on the order of 10% can result from coincidence summing and other geometrical effects if the various samples are counted in different positions, even if one attempts to use an efficiency versus position curve. The same authors stated that errors can also arise from large differences in count rates, about 10% for count rates differing by a factor of three if the dead-time fraction is high. This is because analyzers do not necessarily correct accurately for dead-time losses even in the live-time mode.

Calculations of Met

Concent:

ions

The concentration of C_x of a metal x in air is computed by the formula:

Weight of metal $W_x = \frac{A_x}{A_s} \times \frac{W_s}{V} \times \frac{1}{\epsilon}$

Where A_x = net gamma counts under the photopeak of the nuclide of element x present in the sample; A_s = net gamma counts under the photopeak of the same energy as for A_x in corresponding to the same nuclide of element x present in the standard sample (Corrected for decay also to the end of irradiation); W_s = weight of element x present in the standard sample, usually expressed in micrograms or nanograms; V = Volume of air (usually expressed as m^3) sampled to collect the aerosol sample; W = weight of paper sample with air particulates; and W_s = weight of paper sample

With Standards.

---Page Break---

Subtraction of Analytical Blanks

The net activities or counts due to the sample and standard, A_y and A_s , respectively, are further defined by equations (2) and (3):

$$B = R_{ex} - A_{pex} - ABL + @$$

$$A_s = A_{gs} - A_{BKS} = ABL - s_{see} @$$

where A_{gr} or A_{gs} = gross counts under photopeak; A_{SK} or A_{pks} = total counts

due to the background in channels containing the photopeak; and A_p = net counts

under the photopeak of the same nuclide in the aerosol sample. (A_{gr} is shown

experimentally to be essentially zero in most cases for the paper tape used in

this study and can be neglected.) ALL the quantities on the left side of equations

(2) and (3) should be values obtained after extrapolation to the time at the end

of irradiation. The values should also be corrected for differences in weights

of the blank, sample, and standard paper tapes.

Calculation of Errors

The error reported in this study for a single determination of metal concentration in a single aerosol sample is the standard deviation due to counting statistics (Friedlander et al. 1964). The standard deviations σ_g and due to counting statistics for net counts A_g and A_y respectively are defined as:

$$\sigma_g = \sqrt{G} + \sigma_{so} + \sigma_{9} \quad (1)$$

$$\sigma_{A_g} = \sqrt{2 + \sigma_{sys} + \sigma_{DY}} \quad (3)$$

where σ_g or σ_{gg} = standard deviation due to counting statistics of gross counts under the photopeak; σ_{so} or σ_{pgs} = standard deviation due to counting statistics of background in channels containing the photopeak; and σ_{9} = standard deviation due to counting statistics of net counts under the photopeak in the blank sample which corresponds to the photopeak of a common nuclide in the aerosols and standards.

The standard deviation due to counting statistics. for the calculated concentration of the metal in air is computed by the following relation (No 1971):

$$= S_x (\text{SPA?} + 27452)^{1/2} \quad (6)$$

As defined in equation (1). However, when duplicate determinations are made of the metal concentrations, the average value is reported together with the relative standard deviation calculated from the spread of the individual values.

13

---Page Break---

Discussion

Air Pollution in San Germin, Puerto Rico during November 1972

The data given in Table 2 for eight hour average concentrations of the polluting elements for morning, daytime, and night, in the air of San German are Plotted in Figure 5. The graph illustrates the variations in the metal concentrations within one day during the period 10 through 23 November, 1972. For each of the trace metals and for Bromine, the concentrations in the air reached their maxima from about 8:00 a.m. to 4:00 p.m. A fraction of the Br found may be of natural origin, but most of it probably indicates pollution from automobile exhaust emission (Winchester 1967).

The aerosol samples were collected before the burning of sugar cane began in January. The major sources of pollution might be a combination of exhaust emission from cars, dusting and spraying of herbicides on major crops like sugar cane or pineapple, and earth moving and excavating activities. Most of the terrain around San German consists of serpentinite, which has high Cr (~1000 ppm), Ni (~1000 ppm), and Co (~100 ppm) content. (Hedepohl 1971). The dust stirred up by automobiles, earth movers, and wind may contribute to the peaking of these elements during the day. Figure 4 clearly indicates that the concentrations of the trace metals and Bromine were highest during the day when traffic, construction, and wind turbulence were at the maximum. It is also possible that some of the trace metals may have been transported from the industrial operations in the southern part of the island,

The multi-element ratios in different brands of gasoline should be obtained and fuel oils used in power plants analyzed by the INAA technique for Br and other trace metals to ascertain the origin of pollution. The aerosol samples collected during the sugar cane burning season should also be analyzed for trace elements to appraise the extent of pollution {iron metal compounds contained in herbicide residues released during the combustion process,

Instrumental Neutron Activation Analysis (INAA)

It has been shown in this preliminary study and elsewhere (Salmon and Creevy

1971, Dans et al. 1970, Hoffman et al, 1969, and Pillay and Thomas 1969) that the INAA technique is potentially useful for the study of atmospheric pollution. With

the INAA method one can determine simultaneously the concentrations of up to 33

elements with high precision and sensitivity without destroying the sample. After

the INAA process has been completed, the same samples can be used to confirm results :

or to measure additional elements by other techniques. Determination of many

elements simultaneously also enables one to look for correlations among elements

that are largely emitted from a common source of pollution. The INAA technique

can be used to determine the concentrations of most elements in suspected sources

of pollution. The main advantage of the INAA method is the security against

contamination or loss of material.

The INXM method is fast and convenient. For elements having highly active, short-lived irradiation products (Al, Dr, V, and Mn), the time from receipt of sample until the concentrations are available can be under one hour. With high Volume pumps mounted on mobile collecting units (a truck and/or snail aircraft),

16

---Page Break---

§ g

&

CONCENTRATION OF ELEMENTS (Nanograms /M³ OF AIR)

FIGURE 5, Variations within a day* of elemental concentrations in the atmospheric aerosols of San German, Puerto Rico

+

400 HOURS

600

MORNING DayTiME Night

?* Time period: 10-23 November 1972

"

---Page Break---

sample collection time could be reduced considerably and the most serious contributors to a pollution crisis could be discovered with some additional groundwork. Such a system would enable public health and environmental agencies to issue warnings about developing air pollution emergencies.

Most of the steps in the INAA technique can be automated and assisted by a computer (Fite et al. 1961). With computer analysis for species emitting intense gamma rays, very little manpower per sample would be required. Without a computer, 4 trained technicians could manually calculate the results from a short irradiation (three samples and one standard!) in about one hour. The manual computations for

the elements observed in a long run would take about two hours per sample.

?The PRNC nuclear reactor has been modified to provide several irradiation sites with higher thermal neutron fluxes (10^{13} neutrons/cm²/sec) and fast neutron fluxes. Better fluxes of neutrons, increased time of irradiation (up to eight hours), and increase in sample size (up to 18 mg of sample during

24 hours) would greatly improve the sensitivity and precision of the INAA method in future experiments,

Important pollutant metals like cadmium, lead, boron (as hydrides), and platinum (as ammonium chloroplatinate dust) cannot be measured by the INAA technique.

Excellent facilities for atomic absorption spectrophotometry exist at PRNC, the technique and methodology are being developed by *Afonso-Ribadeneira to determine Pb, Ca, Cu, and Zn by this method.

?The INAA and atomic absorption and emission spectrophotometry methods will not yield any information about the molecular form of air pollutants, e.g., the important organic constituents and the various compounds of sulphur and nitrogen.

?Therefore, these methods must be considered complements to other techniques in current use for general air pollution studies since INAA and AAS can detect only elemental concentration data. However, the INAA method can and will contribute substantially to our understanding and control of air pollution in Puerto Rico.

---Page Break---

PART T

REFERENCES

Brar, D.M, Nelson, D.M. Kanabraocki, et al., 1969. In Modern Trends in

5.

Activation?Analysis (J.R, DeVoe, ed.).? National Bureau of Stantards,

Nashington, Dice

Christian, G.D., 1969, Anal. Chom. 41: 24A,

Covell, D.F., 1959. Anal, Chem. 31: 1785.

Dans, R. et al., 1970. Nondestructive neutron activation analysis of air

pollution particulates, Anal. Chem. 42: 861-867.

Dans, R. et al., 1971, Nondestructive multielement neutron activation analysis of air pollution particulates. In Nuclear Methods in Environmental Research. Proc. Am. Nucl. Soc. Top. Meeting, August 23-24. University of Missouri.

Dutey, N.D. et al., 1969, In Modern Trends in Activation Analysis (J.R. DeVoe, ed.). National Bureau of Standards, Washington, D.C.

Elkins, H.B., 1959, The Chemistry of Industrial Toxicology, 2nd ed, John Wiley and Sons, New York.

Fite, L.E., D. Gibbons, and R.E. Wainendi, 1961. Texas Engineering Experiment Station Report No. TFES-2671-1.

Friedlander, G., J.W. Kennedy, and J.M. Willer, 1954, Nuclear and Radiochemistry, 2nd ed. John Wiley and Sons, New York,

Gijbels, R., J.C. Dran, H. Erten, W. Zoller, J. Fasching, and G. Cordon, 1968. In Chemistry progress report, MIT 905-133. MIT Laboratory for Nuclear Science.

Gordon, G.E., 1971. Trace elements in the urban atmosphere. Proc, Am. Nucl. Soc! Top. Meeting, August 23-24. University of Missouri.

Gordon, G.F, et al., 1968, Geochim, Cosmochim. Acta 32: 369.

Hanilton, A., 1934, Industrial Toxicology. Hoeber, New York.

Hoffman, G.L., R.A. Duce, and W.HI. Zoller, 1969, Environ, Sci, Technol. 3: 1207,

Junge, C.E., 1963. Chapters 2 and 5, Air Chemistry and Radioactivity. Academic
ress, New York,

Lederer, C.M., J.M, Hollander, and I, Perlman, 1967. Table of Isotopes, 6th ed.
John? Wiiey?and Sons, New York.

Lee, D.IILK., 1972, Metallic Contaminants and Human Health. Academic Press,
New York,

19

---Page Break---

Lowman, F.G., 1973. Personal communication to Tin Mo, Puerto Rico Nuclear
Center, Mayaguez.

Mo, T., 1971. Uranium concentrations in marine sediments, Ph. 0, dissertation,
?Taxis \ ahd M University.

Muioz-Ribadeneira, F.J., 1973. Personal commication to Tin Mo. Puerto Rico .
Nuclear Center, "ayaguer.

Pillay, K.K.S., and C.C. Thomas, Jr., 1969. Report No. WWY-046. Western New York .
sucfear Research Center, buffalo.

Puerto Rico Nuclear Center, 1971. Aguirre Power Project Environmental Studies
Annual Report 1971, PRNC=153.

1973, Personal communication to Tin No. Puerto Rico Nuclear Center,

Salvon, Ly and ?I.G, Creevy, 1971, In Nuclear Techniques in Environmental
Polfution. IAEA, Vienna.

Tuttle, R.P., 1971, Neutron activation analysis of trace elenents in airborne
particulates, in Nuclear Techniques in Environmental Pollution. IAA, Vienna.

Wedopohl, Kull, 1971, Geochemistry. Holt, Rinehart, and Winston, New York.

West, FX. and PW, West, 1966, Anal. Chem, 3

Yost, P.W., 1968. Chapter 19. In Air Pollution, Vol. TI, 2nd ed. (A.C. Stern,
ol.) Academic Press, New York.

Winchester, J.W. W

Frviron! 1! Tas,

]. Zoller, R.A. Duce, and C,S. Benson, 1967, Atmos.

2

---Page Break---

Peer 11

SIMARY REPORT

APPLICATIONS OF ATOMIC ABSORPTION SPECTROPIOTERETRY

FOR THE ANALYSIS OF TOXIC METAL CONCENTRATIONS

1N THE ATMOSPHERE OF THE SOUTH AND WEST

OMSTS OF PUERTO RICO

by

Fausto J. Mufioz-Ribadeneira

au

---Page Break---

TABLE

TABLE,

?TAL

TABLE

?TAB:

2

PART T

LIST OF TARLES

Average percent of trace metals recovery from filter paper tape :

samples after dry ashing at high temperatures

Statistical analysis of effect of extracting calcination residues

of air filter tape samples by hot {il 28 and comparison of results

between single and triple extraction by Hcl 2.

Experimental design to test effects of different variables used
in chemical preparation of air tape samples

Average percent metal recovery from filter paper tape samples
submitted to different chemical treatments

Statistical analysis on data obtained by atomic absorption spectro-
Photometry from samples submitted to different chemical treatments

2

---Page Break---

INTRODUCTION

During 1971 and 1972 air tape particulate samples were collected in different towns on the south and west coasts of Puerto Rico. The studies focused on the determination of concentrations of Cr, Mn, CO, Ni, Cu, Zn, and Pb by Atomic Absorption Spectrophotometry (AAS)." This report summarizes the methodology developed for preparation of air filter paper tape samples, for AAS and the inventory of metal concentrations in the aerosols retained by filter paper tapes at different sampling stations.

A review of the literature indicated that several elements in chloride form can be volatilized at high ashing temperatures (430 to 450°C) and that sulfatation can reduce this volatilization, increasing the recovery of metals. However, salts of these metals form more insoluble compounds with glass beakers under the influence of high ashing temperatures (HAT)

First Experiment

In order to test the results of these investigations, twenty replicate air tape samples (10 on x 2,54 cm) were cut from a paper tape Toll (type W-41, Bendix Environmental Division) and placed in 100 ml Pyrex beakers which had been washed three times with hot C1 2N, rinsed with de-ionized distilled water, and dried. Standards of the metals were added to the paper tapes with a certified micropipette. The concentrations of the standards were chosen to obtain an easily readable percent of absorption (251). The standards were in chloride form with lead as nitrate. The samples were then slowly dried under an infrared lamp.

Data from Table 1 show the low recoveries of the chlorides of Zn, Cd, Cu, and lead nitrate and indicate the tendency of these compounds to volatilize at the muffle temperatures used in these investigations. The value of wetting samples with 12504 prior to ashing is evident by the increased yield of metal, as shown in Table Tr

Under the influence of the heat treatment, some insoluble compounds were formed between the traces of the metals and the Pyrex glass of the beakers.

In most cases, an increase in metal recuperation resulted from samples having been submitted to several washing-extractions by hot HCL. In order to inquire into the statistical meaning of this increase, Student's "t" test with equal number of degrees of freedom and different variance was carried. It was hypothesized that if the theoretical distribution for 95% probabilities (69.09) was smaller than "t" calculated (t_c), the difference would be significant,

this favorable difference in metal recovery would be determined by the repetition of the hot HCL 2N washing-extraction. Results indicate the value of repeating the HCL treatment of the calcination residue of the paper tape samples (table 2).

Results obtained from samples submitted to the 1204 treatment showed even better metal recuperation. The substances formed by the treatment between the residues of the air tapes and the Pyrex beakers were more easily extracted by the hydrochloric acid (when the samples were in sulfate form) prior to the heat treatment in the muffle,

3

---Page Break---

quossed uvau worry uoTleTAap prEpURIS ()

luvou wo.) uoraetxap puepuErs

suoyaeoy{dor aaty jo aBvoay

(s9°9) v9 F 286 (ue"et) WSL F 2°68 (euros) vee vue (u9tus) ZLLF Z795 ?saBeaoAy

Teo

- oroot - oral (srs) 68 F cris (uoret) cro + bus Prot

(zs"y) os ¥ 068 (is'9) sts ¥ 9ru8 (op'ss) stoi + 2°97 (sere) ove + cron wyupeg

GU wns 228 (ures) Lae F Sees (zuri2) stu > ores (zo'v2) v9 F Vee pure

(@s"0) sto F 2°26 (o2"y) ov F Gru 79 9°68 (ze"s2) ovst F 9°99 eddy

(o's) 08 F 66 (cart) 91 688 Gus) oes ou Gow) cy Fis ep

(61'2) 072 > 8°56 (0e"0) \$0 + 8a6 (ory) we or86 (Sev) aren FoTURaTEHRD

(6D sth Une (ost) sh 96 & F 5°86 (o9" Li) Z'uL F s7sçosauesum,

se es5 anquony

Stes 7°96 (96°2) 82 ¥ 8r¥6 «

(ao"9) "8 F s*26 (39

TOH soura ay poysey (YUEN SOU pOyseN ? TH SOUTA |aMya paYsEY ?TOHL HATH |DUe ous

auoureea tus? guano, Mystiy anon yt awowaT

aw wupyse Lap saaze ,sopdaws ode

Ooo Pow voesy JO wusolad OBeLaNy | HAL.

soimesodiaa

---Page Break---

TABLE 2, Statistical analysis of effect of extracting calcination residues of air filter paper tape samples by hot HL 28 and comparison of results between single and triple extraction by HCL

Samples without 12504 Samples with H2S04

Statistical Statistical

Element te Significance te significance

0.019 None 1,207 None

2182 Yes 6.682 Yes

3.110 Yes 91279 Yes

3.858 Yes 7,806 Yes

3.609 Yes 3.771 Yes

43561 Yes aaa Yes

1577 None 5.709 Yes

12085 None sieee

(Student) distribution function at 95% probability and 8 degrees of freedom = 2.308,

* Favorable to samples washed only once with hot HCL 2%

Other Experiments

Other experiments were designed with these conditions:

a) 95% recovery of the metals would be acceptable;

b) 5% standard deviation from the mean would be considered reasonable;

c) Hydrogen peroxide should be used instead of perchloric acid, and Pyrex

beakers should be used rather than Teflon beakers and/or plastic

crucibles;

d) acid inventory should be kept as low as possible; and

e) organic matter should not be present in the metal solution to avoid

enhancement of the signal in the spectrophotometric detector.

It was agreed that the acid inventory could be reduced if the air tape samples were bummed with alcohol prior to their acid dissolution. Table 3 shows the variables taken into account in the design of the experinents for this new phase of the investigation,

2s

---Page Break---

TARLE 3, Experinental design to test effects of different varishles used in chemical preparation of air tape sanples*

Experinent Variables

Code

Alcohol Chemical Muffie Chemical

Burning Treatment(1) eating ?Treatment (2)

a a a o

a o y * ° a

R 0 a ° ?

T 0 * E y ?

* Rive replications for each code set of samples

?Presence of Variable

0 Absence of Variable

Notes to Table 3

1. Alcohol burning. After the addition of the standards, the samples were dried as in previous experiments, wetted with 2 ml of alcohol of spectroscopic quality, and burned.

2, Chemical Treatment(1), To each of the samples, 6 ml of inverse aqua regia (Ginos-Ticl) was added, The beakers were covered with watch glasses in a retort and put on a hot plate for slow boiling. The watch glass permits some reflux of the acids, so the reaction may last until the paper tape dissolves. The samples were then Boiled rapidly, and the evaporation was continued. Almost to dryness. Then 4ml of concentrated HNO₃; and 1 ml drop of H₂O₂ (30 per volume) were added, "The samples were again boiled, first slowly and then at higher temperatures. When the samples were almost dried, 3 drops of concentrated H₂O₂ was added to test the presence of organic matter, found to be negligible or nonexistent. Samples were then evaporated up to complete disappearance of

Sy fines. ?Samples Code P and T were submitted to the heat treatment in the

le oven following these procedures.

3, Chemical Treatment(2). The residues from the calcination and other chemical treatments were extracted three times with hot HCl 2, The results obtained in these experinents are presented in Table 4,

---Page Break---

TIDE 4. Average percent netal recovery from filter paper

Suples hulmitted to different chemical treatments

Variables involved as indicated in Table 2

Elenents P Q R T

of

Total Average

of

In order to evaluate the results obtained from samples submitted to different chemical treatments, Student's "t" test was applied to data from Table 4. The summary of these calculations is presented in Table 5 and includes the comparison of data obtained by different chemical treatments for each one of the elements under study.

2

---Page Break---

TABLE 5, Statistical analysis on data obtained by stonic absorption spectrophotometry from Samples submitted to different chemical treatments

Elements ? PR PT aR wr RT

Cr 1.284Q) 2.5170) 9.43208) 2.96109 0.9570) 2.601(¥)

Tn 1255¢N)?-21326(¥) 11765ES) ? Sloaaeyy ?1as0(%) _0:703(N)

Zi7OV(y) 0.908) 9.829(8) 21127) 1.70500),

As900y) ? 2.003(¥) 1822(K) 118380) 26260"

256219) Sogeqy) N94) -2:713(%) T6080)

1S.97R(Y) 9.672() _9:895(Y) _TI10S(¥) _2:489(8) (908)

Olan) 26.789() 17 La3ACY) 19/4250) AANA) 26150)

15030) O)* or oF a ©

he" Stunlent Distr!

ion Function at P (0.05) and 8 degrees of freedom = 2.306

(No statistical significance

(9) Statistical significance at P (0,05) confidence level

The difference is so large that it is accepted as significant,

Samples submitted to treatments P and (show the lowest percent of metal recovery, but Table 5 indicates no statistical difference between their results. Both sets of samples were submitted to alcohol burning prior to other treatments. The statistical comparison between P and T is significantly favorable for T for Ni, Cu, Mn, Cr, and Pb (Table 5). These sets of samples were submitted both to the 11250 treatment and later to the effects of heating at high temperatures in the muffle, but T did not receive alcohol burning. As observed in Table 4, there was a significant statistical difference in the Results, especially for the more easily volatilized elements. Their low recovery could be attributed to the high temperatures associated with flaming in alcohol burning.

For all the elements studied there were significant favorable statistics for samples R compared to samples P (Table 5). Samples R received the aqua regia~ IEDs ~ H₂O₂ treatment (AN) and were not submitted to alcohol burning or the muffle.

The statistical comparison of data between () and R and Q and T also indicates significant differences in favor of samples R and T in chemical elements that could be more easily volatilized at high temperatures. Samples R and | were not submitted to alcohol burning and the negative effects of flaming.

Table 4 shows that metal recovery from samples submitted to the ANI method was higher than from those submitted to the [12S muffle heating. Also, the overall percent of metal recovery was higher and the variations in the data were smaller. If the same statistical analysis is applied to the data (iron samples Rand ?T, the differences between them are statistically significant at P (0.05); (te = 21955). In data from Table 5 these differences are statistically significant

28

---Page Break---

for Ni, Cd, and Cr, because Ni and Cd were volatilized by muffle treatment and Cr, under heat effects, was retained in the Pyrex beaker and extracted with more difficulty by HC1'2N. Recovery is improved when samples are submitted to wet ashing compared to ashing at high temperatures, even when samples first receive the H2SO4 treatment.

Application of Chemical Treatments to Natural Aerosol Samp!

The two most successful chemical treatments, sulfatation of the samples

coupled with IAT and the wet digestion of samples by the ANI method, were used

to determine toxic metal concentrations from air tape samples obtained at
Mayaguez, Puerto Rico. These investigations will be reported later in 1975
(Muioz-Ribadeneira, F.J., 1975. Preparation of air filter paper tape samples

for multielement analysis by atomic absorption spectrophotometry, in preparation.)

2

---Page Break---

PART 111

PRELIMINARY SURVEY OF THE CONCENTRATIONS OF TRACE METALS
IN THE ATMOSPHERE OF EIGHT SELECTED STATES IN SOUTHWESTERN
PUERTO RICO

by

Fausto J, Muioz-Ribadeneira

30

---Page Break---

Figure 1,

Figure 2.

Figure 3.

Figure 4,

Table 1.

Table 2.

PART 11

LIST OF FIGURES

Relationship between Coefficient of Haze and Optical Density using

different values of Optical Density as parameters

Relationship between the (Of! unit and the amount of contaminants

ac a Fimction of the tine of sampling at Como Station

Relationships between the COI unit and the amount of contaminants

as a function of the tine of sampling

Correlation of Optical Nensity as a function of the conservation of
Yead (micrograns/n3) at Salinas Station

LIST OF TABLES

?Average trace metal concentration at different sampling stations
(wicrograns/n3)

Average total amount of contaminants in particulate matter obtained
?and average values of the Coefficient of llaze Unit

an

---Page Break---

PARTS 11 AND ITT

ci

NCES

Barnett, Wells, 1°72. Acid interferences in atomic absorption spectrophotometry.

Teal? Chem, 41(4): 0

1 1968, Preparation of metallic air pollutants for atmospheric absorpti

Beyer,

sis. Avon, Abs. News. S(T): 23. .

Konetani, V.Y., 1960, Effect of temperature of volatilization of alkali salts
during dry ashing of tetraflueroethylene (unrocarbon resin. Anal, Chem.
Sati): 1597,

Konetani, .Y. ant t.L. tove, 1072,

plass? filters for trace metal ari

aching particulate matter on paper and

WS, Env, Se. Techn, 6(7): 617,

1972, *Metals Contaminants and Human Health*, Academic Press

Iwano, Delle

Yori

1. *Metodos de Investigacion Cientifica*, Editorial "Tipografica de Casals", Barcelona.

Thompson, R.L., (ies Morgan, and L.L. Durie, 1979, Analysis of selected elements in atmospheric particulate matter by atomic absorption. *Atom. Abs. News*.

9(3): 58,

Criteria for

U.S, Dept. of Health, Education and Welfare, 1969, Air Quality

Particulate Matter. Washington,

U.S, Environmental Protection Agency, 1971, A Mathematical Method for Relating

Air Quality Measurements to Air Quality Standards, Publ. No. TPA 19-89,

APONTE ANTONS,

The cooperation of Alice Vepa, Maria L. Nazario and J. Ramirez Narbot, co-authors of the reports of which these are summaries, is acknowledged. The authors also express their gratitude to Oscar Pérez-Rios who collected the air particulate samples and measured optical densities of the samples.

---Page Break---

NOTICE

This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the United States Atomic Energy Commission, nor any of their employees, nor any of their contractors, subcontractors or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness or usefulness of any

information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights.?

---Page Break---